

TS 100 521 V7.0.0 (1999-08)

Technical Specification

Digital cellular telecommunications system (Phase 2+); Network functions (GSM 03.01 version 7.0.0 Release 1998)



GSM®
GLOBAL SYSTEM FOR
MOBILE COMMUNICATIONS

ETSI 

Reference

RTS/SMG-030301Q7 (4to030c3.PDF)

Keywords

Digital cellular telecommunications system,
Global System for Mobile communications
(GSM)

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16
Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr
Individual copies of this ETSI deliverable
can be downloaded from
<http://www.etsi.org>
If you find errors in the present document, send your
comment to: editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1999.
All rights reserved.

Contents

Intellectual Property Rights.....	5
Foreword.....	5
1 Scope.....	6
1.1 References.....	6
1.2 Abbreviations.....	8
2 Network functions for basic service provision.....	8
2.1 Call handling.....	8
2.1.1 Call from a mobile subscriber registered in VLR.....	8
2.1.2 Call from a mobile subscriber not registered in VLR.....	8
2.1.3 Call to a mobile subscriber.....	8
2.1.4 Call handling functions in HLR.....	9
2.1.5 Call handling functions in VLR.....	10
2.1.6 Call handling functions in MSC.....	10
2.1.7 Call handling functions in SGSN.....	10
2.2 Subscriber identity authentication.....	10
2.3 Emergency call.....	10
2.3.1 General.....	10
2.3.2 Routeing.....	10
2.4 Supplementary services.....	10
2.5 Voice group services.....	11
2.6 Short Message Service.....	11
2.6.1 Short Message Handling functions in the HLR.....	11
2.6.2 Short Message Handling Functions in the VLR.....	11
2.6.3 Short Message Handling Functions in the MSC.....	11
2.6.4 Short Message Handling Functions in the SGSN.....	11
2.7 Signalling information element confidentiality.....	11
2.8 Packet Handling.....	11
2.8.1 Packet handling functions in SGSN.....	12
2.8.2 Packet handling functions in GGSN.....	12
2.8.3 Packet switched service functions in HLR.....	12
3 Network functions for supporting cellular operation.....	12
3.1 Location registration.....	12
3.1.1 Definitions.....	12
3.1.2 Procedures.....	12
3.1.3 Information stored in location registers.....	13
3.2 Handover.....	13
3.2.1 Definitions.....	13
3.2.2 Procedures.....	13
3.3 Call re-establishment.....	13
4 Additional network functions for call handling.....	14
4.1 Queuing.....	14
4.2 Off-Air-Call-Set-Up (OACSU).....	14
4.2.1 General.....	14
4.2.2 Signalling procedures.....	14
4.3 Security related services.....	14
4.3.1 Identity confidentiality.....	14
4.3.1.1 Circuit switched services.....	14
4.3.1.2 Packet switched services.....	15
4.3.2 User data confidentiality.....	15
4.3.2.1 Circuit switched services.....	15
4.3.2.2 Packet switched services.....	15
4.3.3 Signalling Information Element Confidentiality.....	15

4.3.3.1 Circuit switched services 15

4.3.3.2 Packet switched services 15

4.4 Discontinuous Reception 15

4.5 Discontinuous Transmission 16

4.6 Support of DTMF 16

5 Network management oriented network functions 16

Annex A (informative): Change Request History 17

History 18

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by the Special Mobile Group (SMG).

The present document defines the network functions required to support services and facilities provided by a Public Land Mobile Network (PLMN) within the digital cellular telecommunications system (Phase 2/Phase 2+).

The contents of the present document is subject to continuing work within SMG and may change following formal SMG approval. Should SMG modify the contents of the present document it will be re-released with an identifying change of release date and an increase in version number as follows:

Version 7.x.y

where:

- 7 indicates Release 1998 of GSM Phase 2+
- x the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- y the third digit is incremented when editorial only changes have been incorporated in the specification.

1 Scope

The present document defines network functions which are necessary to support services and facilities provided by PLMNs. A summary of the network functions is given in Table 1, where also an indication is given whether the network must support the function. The table also indicates whether or not a function requires internetworking signalling between PLMNs (i.e. use of Mobile Application Part, Technical Specification GSM 09.02).

All functions require signalling on the radio path as specified in Technical Specification GSM 04.08.

1.1 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.
- For this Release 1998 document, references to GSM documents are for Release 1998 versions (version 7.x.y).

- [1] GSM 01.04: "Digital cellular telecommunications system (Phase 2+); Abbreviations and acronyms".
- [2] GSM 02.04: "Digital cellular telecommunications system (Phase 2+); General on supplementary service".
- [3] GSM 02.09: "Digital cellular telecommunications system (Phase 2+); Security aspects".
- [4] GSM 02.60: "Digital cellular telecommunications system (Phase 2+); General Packet Radio Service (GPRS); Service Description - Stage 1".
- [5] GSM 03.03: "Digital cellular telecommunications system (Phase 2+); Numbering, addressing and identification".
- [6] GSM 03.07: "Digital cellular telecommunications system (Phase 2+); Restoration procedures".
- [7] GSM 03.08: "Digital cellular telecommunications system (Phase 2+); Organisation of subscriber data".
- [8] GSM 03.12: "Digital cellular telecommunications system (Phase 2+); Location registration procedures".
- [9] GSM 03.13: "Digital cellular telecommunications system (Phase 2+); Discontinuous Reception (DRX) in the GSM system".
- [10] GSM 03.14: "Digital cellular telecommunications system (Phase 2+); Support of Dual Tone Multi-Frequency signalling (DTMF) via the GSM system".
- [11] GSM 03.20: "Digital cellular telecommunications system (Phase 2+); Security related network functions".
- [12] GSM 03.22: "Digital cellular telecommunications system (Phase 2+); Functions related to Mobile Station (MS) in idle mode".
- [13] GSM 03.40: "Digital cellular telecommunications system (Phase 2+); Technical realization of the Short Message Service (SMS) Point to Point (PP)".

- [14] GSM 03.60: "Digital cellular telecommunications system (Phase 2+); General Packet Radio Service (GPRS); Service Description; Stage 2".
- [15] GSM 03.64: "Digital cellular telecommunications system (Phase 2+); Overall Description of the General Packet Radio Service (GPRS) Radio Interface; Stage 2".
- [16] GSM 03.81: "Digital cellular telecommunications system (Phase 2+); Line identification supplementary services - Stage 2".
- [17] GSM 03.82: "Digital cellular telecommunications system (Phase 2+); Call Forwarding (CF) supplementary services - Stage 2".
- [18] GSM 03.83: "Digital cellular telecommunications system (Phase 2+); Call Waiting (CW) and Call Hold (HOLD) supplementary services - Stage 2".
- [19] GSM 03.84: "Digital cellular telecommunications system (Phase 2+); MultiParty (MPTY) supplementary services - Stage 2".
- [20] GSM 03.85: "Digital cellular telecommunications system (Phase 2+); Closed User Group (CUG) supplementary services - Stage 2".
- [21] GSM 03.86: "Digital cellular telecommunications system (Phase 2+); Advice of Charge (AoC) supplementary services - Stage 2".
- [22] GSM 03.88: "Digital cellular telecommunications system (Phase 2+); Call Barring (CB) supplementary services - Stage 2".
- [23] GSM 04.08: "Digital cellular telecommunications system (Phase 2+); Mobile radio interface layer 3 specification".
- [24] GSM 05.08: "Digital cellular telecommunications system (Phase 2+); Radio subsystem link control".
- [25] GSM 09.02: "Digital cellular telecommunications system (Phase 2+); Mobile Application Part (MAP) specification".
- [26] GSM 12.00: "Digital cellular telecommunications system (Phase 2+); Objectives and structure of Network Management (NM)".
- [27] GSM 12.01: "Digital cellular telecommunications system (Phase 2+); Common aspects of GSM Network Management (NM)".
- [28] GSM 12.07: "Digital cellular telecommunications system (Phase 2+); Operations and performance management".
- [29] GSM 12.02: "Digital cellular telecommunications system (Phase 2+); Subscriber, Mobile Equipment (ME) and services data administration".
- [30] GSM 12.03: "Digital cellular telecommunications system (Phase 2+); Security management".
- [31] GSM 12.04: "Digital cellular telecommunications system (Phase 2+); Performance data measurements".
- [32] GSM 12.05: "Digital cellular telecommunications system (Phase 2+); Subscriber related event and call data".
- [33] GSM 12.06: "Digital cellular telecommunications system (Phase 2+); GSM Network change control".
- [34] GSM 12.10: "Digital cellular telecommunications system (Phase 2+); Maintenance provisions for operational integrity of Mobile Stations (MS)".
- [35] GSM 12.11: "Digital cellular telecommunications system (Phase 2+); Maintenance of the Base Station System (BSS)".
- [36] GSM 12.13: "Digital cellular telecommunications system (Phase 2+); Maintenance of the Mobile-services Switching Centre (MSC)".

- [37] GSM 12.14: "Digital cellular telecommunications system (Phase 2+); Maintenance of location registers".
- [38] GSM 12.20: "Digital cellular telecommunications system (Phase 2+); Network Management (NM) procedures and messages".
- [39] GSM 12.21: "Digital cellular telecommunications system (Phase 2+); Network Management (NM) procedures and message on the A-bis interface".
- [40] GSM 12.22: "Digital cellular telecommunications system (Phase 2+); Interworking of GSM Network Management (NM) procedures and messages at the Base Station Controller (BSC)".

1.2 Abbreviations

Abbreviations used in the present document are listed in GSM 01.04.

2 Network functions for basic service provision

2.1 Call handling

This set of functions enables the establishment of communications between a mobile subscriber and another network subscriber in one of the following types of network PSTN, ISDN, PSPDN, CSPDN and other PLMNs.

2.1.1 Call from a mobile subscriber registered in VLR

This is the normal case where the call is routed according to the dialled number. After the call, the MSC will send the charging information to the HLR, a billing entity and/or store the charging data on tapes or discs as described in Technical Specification GSM 12.05.

2.1.2 Call from a mobile subscriber not registered in VLR

When the VLR receives a request for call set-up parameters from an MSC for an MS originating call, where the MS is not registered in the VLR, the VLR shall initiate a location updating procedure towards the HLR and in response parameters are given concerning category, services and restrictions. The call is then set up as in 2.1.1. This case only happens when a VLR or an MS failure has occurred.

2.1.3 Call to a mobile subscriber

The call is routed (re-routed or forwarded) according to location data obtained from the HLR to the actual MSC and the MS is paged over the standardised radio interface.

For MSs in mode of operation A and B the paging may be performed via SGSN. This optional network function is further described in the Technical Specification GSM 03.60.

Table 1: Overview of network functions

Class of Network Function (NF)	Network Function	Network Support	Interworking with MAP
NF for basic service provision	Call Handling (Note 3)	M	X
	Packet Handling (Note 4)	M	X
	Subscriber Authentication	M	X
	Emergency calls (Note 3)	M	-
	Supplementary Services	M	X
	Voice group services (Note 3)	O	X
	Short Message Service (SMS)	M	X
	Signalling information element confidentiality	M	X
NF for supporting:	Location registration	M	X
	Handover (Note 3)		
	- in the same BSS	M	-
	- in the same MSC	M	-
	- in the same PLMN	M	X
	Call re-establishment (Note 3)	M	-
Additional NF for call handling	Queueing	O	-
	OACSU (Note 3)	O	-
	Security related services	M	X
	Discontinuous reception	M	-
	Discontinuous Transmission	M/O Note 2	-
	DTMF (Note 3)	M	-
Network management oriented NF		M (Note 1)	X

NOTE 1: The function will not be fully specified by GSM (national specifications will complement).

NOTE 2: Only the receiver requirements are mandatory, the transmitter requirements support are optional.

NOTE 3: Only applicable for circuit switched services

NOTE 4: Only applicable for packet switched services

2.1.4 Call handling functions in HLR

The HLR should also support control functions for handling of supplementary services as described for each service in the GSM 03.8x series of Technical Specifications.

The HLR should provide information to the gateway MSC to allow it to route calls directed to a mobile subscriber: either a Mobile Station Roaming Number (MSRN) to allow the call to be routed to the visited MSC or a forwarding number if the call is to be forwarded to a destination different from the original one.

The HLR should provide the identity of the visited MSC to the SMS gateway MSC to allow it to route short messages directed to a mobile subscriber; further detail is given in Technical Specification GSM 03.40.

2.1.5 Call handling functions in VLR

The VLR must provide subscriber parameters to the MSC as required for call handling.

The VLR must also support control functions for handling of supplementary services as described for each service in the GSM 03.8x series of Technical Specifications.

For a MS in mode of operation A or B, the VLR may optionally support establishment and maintenance of an association with an SGSN. This allows paging for a circuit switched call to be performed via SGSN.

2.1.6 Call handling functions in MSC

The MSC must perform normal call routing and call control functions. The MSC will obtain subscriber parameters from its associated VLR.

The MSC must also be capable of performing handover as defined in section 3.2.

In some cases, the MSC must be able to act as a gateway MSC to provide an interface to other circuit-switched networks.

2.1.7 Call handling functions in SGSN

For a MS in mode of operation A or B, the SGSN may optionally support establishment and maintenance of an association with a VLR. This allows paging for a circuit switched call to be performed via SGSN.

2.2 Subscriber identity authentication

The purpose of subscriber identity authentication is defined in Technical Specification GSM 02.09.

The authentication mechanism is defined in Technical Specification GSM 03.20 and corresponding procedures on the MS-BSS interface are defined in Technical Specification GSM 04.08.

2.3 Emergency call

2.3.1 General

The land mobile system should be capable of efficient handling of emergency calls from MS. The signalling procedures on the radio path for emergency calls are given in Technical Specification GSM 04.08.

2.3.2 Routing

The call should be routed automatically to an appropriate emergency centre based on the geographical location of the MS (e.g. based on the identity of the cell on which the call is established).

2.4 Supplementary services

PLMN may offer supplementary services as shown in Technical Specification GSM 02.04. The support of supplementary services will require control procedures in HLRs, VLRs and MSCs in addition to the control procedure in the fixed network. The technical realisation of supplementary services is given in the GSM 03.8x series of Technical Specifications.

2.5 Voice group services

The PLMN may offer the voice group services. These are the voice group call service (VGCS) and voice broadcast service (VBS), as shown in GSM 02.68 and GSM 02.69, respectively. The support of the voice group call and voice broadcast services will require control procedures in HLRs, VLRs, MSCs and Group Call Register (GCR) and possibly control procedures in the fixed network. The technical realisation of these services is given in GSM 03.68 and GSM 03.69, respectively.

2.6 Short Message Service

This set of functions allows the transfer of short messages in either direction between a mobile station and a short message service centre. More detailed information is given in Technical Specification GSM 03.40.

2.6.1 Short Message Handling functions in the HLR

The HLR should be able to provide information to allow a short message to be routed from the SMS gateway MSC to the visited MSC and/or visited SGSN and then to the required MS.

2.6.2 Short Message Handling Functions in the VLR

The VLR should provide subscriber parameters to the MSC as required for handling short messages.

2.6.3 Short Message Handling Functions in the MSC

The MSC should perform the functions of relaying short messages in both directions between the fixed network of the PLMN and the BSS.

In some cases the MSC should be able to act as an SMS Gateway MSC to relay short messages from a Short Message Service Centre (SC) to a PLMN, or an SMS Interworking MSC to relay short messages from a PLMN to an SC.

2.6.4 Short Message Handling Functions in the SGSN

The SGSN should perform the functions of relaying short messages in both directions between the fixed network of the PLMN and the BSS. The SGSN should also provide subscriber parameters required for handling the short messages relaying function. The SGSN should also download (from HLR or another SGSN) and store subscriber parameters required for handling the short message relaying functions.

2.7 Signalling information element confidentiality

A procedure should be implemented providing for the confidentiality of signalling information elements on the radio path. In Technical Specification GSM 02.09 the signalling information elements which need to be protected are given.

The Encryption Key is calculated in both the MS and the network. Detailed information is given in Technical Specification GSM 03.20.

2.8 Packet Handling

This set of functions enables routing of packets between an MS and a network host in one of the following types of network: PSPDN, networks based on the Internet Protocol (IP) and other PLMNs.

2.8.1 Packet handling functions in SGSN.

The SGSN should perform the functions of routing packets in both directions between one or more GGSN's and the BSS. The SGSN should also download (from HLR or another SGSN) and store subscriber parameters required for handling the packet routing functions.

2.8.2 Packet handling functions in GGSN

The GGSN should act as a gateway that provides interface(s) to other packet data networks. The GGSN should further perform the functions of routing packets in both directions between these networks and one or more SGSN's. The GGSN should also download (from SGSN) and store subscriber parameters required for handling the packet routing functions.

2.8.3 Packet switched service functions in HLR

The HLR should provide permanent storage of subscriber data.

The HLR should provide the identity of the visited SGSN to the SMS gateway MSC to allow it to route short messages directed to a mobile subscriber; further detail is given in Technical Specification GSM 03.40.

3 Network functions for supporting cellular operation

3.1 Location registration

3.1.1 Definitions

Location registration means that the PLMNs keep track of where MSs are located in the system area. The location information is stored in functional units called location registers. Functionally there are four types of location registers:

- the home location register (HLR) where the current location and all subscriber parameters of a MS are permanently stored;
- the visitor location register (VLR) where all relevant parameters concerning a MS are stored as long as the station is within the area controlled by that visitor location register.
- the serving GPRS support node (SGSN) where all relevant parameters concerning a MS using packet switched services are stored as long as the MS is controlled by that SGSN,
- the GGSN node where routing information for all static PDP addresses related to a mobile subscriber is stored.

See also Technical Specification GSM 03.02 where the network architecture is described.

3.1.2 Procedures

Procedures related to location registration are specified in Technical Specification GSM 03.12.

They comprise:

- i) location updating which enables the MS to inform the network that its location area has to be updated, i.e. the MS has received a location area identity which is different from that contained in its memory. In order to avoid unnecessary updating, the current location area identity should be stored in a non-volatile memory in the MS;
- ii) location cancellation which is used to delete an MS from a VLR or from an SGSN;
- iii) periodic location updating which enables the location of stationary MSs to be confirmed at a rate determined by the operator;
- iv) as a network option, IMSI detach/attach operation. When a MS has informed the network that it is IMSI detached, the network is aware that the subscriber is not active;

- v) routing updating which enables the MS to inform the network that its routing area has to be updated;
- vi) periodic routing updating which enables the location of stationary MSs to be confirmed at a rate determined by the operator;
- vii) GPRS detach/attach operation. When a MS has informed the network that it is GPRS detached, the network is aware that the subscriber is not active;
- viii) cell updating which enables the MS to inform the network that its cell has been updated.

The procedures i) to iv) are defined for circuit switched services, and ii) and v) to viii) are defined for packet switched services. Combined procedures for circuit and packet switched services are also defined in GSM 03.60 for GPRS. The procedure i) may be combined with v), iii) may be combined with vi) and iv) may be combined with vii).

The procedures also include mechanisms for restoration of location registers after failure. These procedures are defined in Technical Specification GSM 03.07.

3.1.3 Information stored in location registers

Information to be stored in location registers is listed in Technical Specification GSM 03.08.

3.2 Handover

3.2.1 Definitions

The following cases are required:

- i) handover between physical channels of the same Base Station System (BSS). This capability could be used in the following situations:
 - when the physical channel carrying the call is subject to interference or other disturbances;
 - when a physical channel or channel equipment carrying a call has to be taken out of service for maintenance or other reasons;
- ii) handover between Base Station Systems (BSSs) of the same MSC;
- iii) handover between BSSs of different MSCs of the same PLMN.

Cases ii) and iii) are used in order to ensure continuity of the connection when an MS moves from one BSS area to another.

For case iii) two procedures are defined:

- a) basic handover procedure where the call is handed over from the controlling MSC (MSC-A) to another MSC (MSC-B);
- b) subsequent handover procedure where the call is handed over from MSC-B to MSC-A or to a third MSC (MSC-B').

3.2.2 Procedures

The procedures are described in Technical Specification GSM 03.09.

3.3 Call re-establishment

Re-establishment of a call may be performed when a traffic channel (TCH) has been lost during the call, e.g. when a handover could not be completed in time.

Call re-establishment is only performed on TCHs and when the call is in the connected state (see Technical Specification GSM 04.08). The procedures are specified in Technical Specification GSM 04.08.

4 Additional network functions for call handling

4.1 Queuing

As a PLMN option MS originating and/or MS terminating calls may be queued at the BSS. (NOTE: this queuing is additional to that for normal call handling). However, the following condition must be met:

- for MS terminating calls the queuing must not conflict with abnormal release conditions in the fixed network. In general, calls that may have passed international circuits should not be queued, i.e. it should not be applied to calls where the originating network is not known to the PLMN.

4.2 Off-Air-Call-Set-Up (OACSU)

4.2.1 General

OACSU may be implemented in PLMNs in order to increase the call handling capacity of the PLMN.

OACSU may be implemented in PLMNs on an optional basis subject to the following conditions:

- i) OACSU should not be used for calls to an international number;
- ii) OACSU should not be used for incoming international calls, except where bilateral agreement has been reached to allow such an application of OACSU. For the avoidance of doubt, OACSU shall not be applied to calls where the call type or originating network is not known by the PLMN;
- iii) foreign MSs not supporting the OACSU procedure should be allowed to access the PLMNs where OACSU is used;
- iv) MSs supporting OACSU should be capable of operating in PLMNs where OACSU is not implemented;
- v) OACSU should only be used for telephone calls.

4.2.2 Signalling procedures

Signalling procedures supporting OACSU are specified in Technical Specification GSM 04.08.

4.3 Security related services

PLMNs will offer three security related services on the radio path: confidentiality of the user identity, confidentiality of user data and confidentiality of signalling information elements and connectionless user data.

4.3.1 Identity confidentiality

This service provides for the privacy of the identities of subscribers. An intruder cannot identify which subscriber is using a certain resource on the radio path. Instead of IMSI a temporary identity is used.

4.3.1.1 Circuit switched services

This identity (TMSI) is a local number only valid in a given location area. The TMSI is allocated by the VLR and is sent to the MS in a ciphered mode, when ciphering is available as a network option. The IMSI and IMEI should also be transmitted in ciphered mode, whenever the procedure allows this, and when ciphering is available as a network option.

The structure of the TMSI is defined in Technical Specification GSM 03.03.

4.3.1.2 Packet switched services

The packet temporary mobile subscriber identity (P-TMSI) is a local number only valid in a given routing area. The P-TMSI is allocated by the SGSN and is sent to the MS in a ciphered mode, when ciphering is available as a network option.

The structure of the TLLI is defined in Technical Specification GSM 03.03.

4.3.2 User data confidentiality

This service provides for the confidentiality of anything transmitted on a traffic channel.

4.3.2.1 Circuit switched services

Encryption/decryption is done in the MS and BSS with a key which is calculated in both the MS and network. Detailed information is given in Technical Specification GSM 03.20.

4.3.2.2 Packet switched services

Encryption/decryption is done in the MS and SGSN with a key which is calculated in both the MS and network. Detailed information is given in Technical Specification GSM 03.20.

4.3.3 Signalling Information Element Confidentiality

This service provides for the confidentiality of anything transmitted on a signalling channel

4.3.3.1 Circuit switched services

Signalling information to control the service offered to a subscriber or connectionless user data can be encrypted/decrypted. Encryption/decryption is done in the MS and BSS with a key which is calculated in both the MS and the network. Detailed information is given in Technical Specification GSM 03.20.

4.3.3.2 Packet switched services

Signalling information to control the service offered to a subscriber can be encrypted/decrypted. Encryption/decryption is done in the MS and SGSN with a key which is calculated in both the MS and the network. Detailed information is given in Technical Specification GSM 03.20.

4.4 Discontinuous Reception

Discontinuous reception is a technique used to reduce the battery consumption of MSs. The operation of the technique is specified in Technical Specification GSM 03.13. This function must be supported by the network, but is optional for MSs.

4.5 Discontinuous Transmission

Discontinuous transmission is a technique used to reduce overall interference level on the radio interface, and to reduce the battery consumption in the MSs. The operation of the technique is specified in Technical Specification GSM 05.08. This function must be supported by the MSs, whereas only the receiver requirements are mandatory in the network.

4.6 Support of DTMF

DTMF is supported as defined in Technical Specification GSM 03.14.

5 Network management oriented network functions

Network management functions are dealt with in the 12 series of GSM Technical Specifications. An overview is given in Technical Specification GSM 12.00.

Annex A (informative): Change Request History

Change history					
SMG No.	TDoc. No.	CR. No.	Section affected	New version	Subject/Comments
SMG#07				4.0.4	ETSI Publication
SMG#17	101/96	B001		5.0.0	Inclusion of "Voice group services" as network function Release 1996 version
SMG#18	287/96	A003		5.1.0	Queuing indication to the MS in case of Mobile Originating Calls
SMG#27				6.0.0	Release 1997 version
SMG#28	P-99-153	A004		6.1.0	
SMG#29				7.0.0	Release 1998 version

History

Document history		
V7.0.0	September 1999	Publication