

3GPP TR 23.cde V0.3.1 (2003-01)

Technical Report

3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Commonality and Interoperability between IMS CNs; (Release 6)



The present document has been developed within the 3rd Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP.

The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification. Specifications and reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organizational Partners' Publications Offices.

Keywords

<keyword[, keyword]>

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2002, 3GPP Organizational Partners (ARIB, CWTS, ETSI, T1, TTA, TTC).
All rights reserved.

Contents

Foreword	4
1 Scope	5
2 References.....	5
3 Definitions, symbols and abbreviations	5
3.1 Definitions	5
3.2 Symbols.....	6
3.3 Abbreviations.....	6
4 Key architectural items	6
4.1 Access network capabilities.....	6
4.2 Backwards compatibility.....	8
4.3 General architectural considerations.....	8
4.4 User and service profile	8
4.5 QoS and Service-Based Local Policy	8
4.6 UE and ISIM/USIM	8
4.7 IP version issues	8
4.8 Security.....	8
4.9 Charging.....	9
4.10 Bearer level considerations	9
4.11 SIP Compression.....	9
4.12 Emergency calls	9
4.13 Documentation and Terminology aspects.....	9
Annex <A>: <Annex title>	10
A.1 Heading levels in an annex	10
Annex <X>: Change history.....	11

Foreword

This Technical Report has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document defines the key architectural items that are the building blocks for achieving commonality and interoperability between IMS core networks that possibly use different IP Connectivity Networks. Specific IP-connectivity access network technologies and their details are not within the scope of the present document. It is expected that one solution will be developed and finetuned for each of these architectural items. The present Technical Report serves as a placeholder for the solutions under development. When the solution reaches maturity, Change Requests against the relevant Technical Specifications will be raised.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 41.001: "GSM Release specifications".
- [2] 3GPP TR 21 912 (V3.1.0): "Example 2, using fixed text".
- [3] 3GPP TSG SA WG2 tdoc [S2-030176](#) " Re-organization of IMS specifications to better reflect aspects of interoperability and commonality between IP Multimedia Systems using different IP-Connectivity Networks"

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions given in TS 21.905 and the following apply.

Interworking: allows communication between users of different networks and systems.

Interworking of the IMS with other networks: allows an IMS user to communicate with users of non-IMS networks. For example, interworking of the IMS with the PSTN allows IMS users to communicate with PSTN users.

Interoperability between IP Multimedia Systems: means interworking between IP Multimedia Systems without (or with minimal) restrictions on the services, which can be used by users of the different IP Multimedia Systems.

IMS Boundary Point: an entity which performs both IMS specific functionalities and non-IMS specific functionalities.

IMS specific function: A function that is specified only for IMS usage and depends on IMS specific characteristics

Non IMS specific function: A function that is not required by IMS or a function that is not exclusive for IMS.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

<symbol> <Explanation>

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

IMS	IP Core Network Multimedia Subsystem
P-CSCF	Proxy Call Session Control Function
QoS	Quality of Service
SBLP	Service Based Local Policy

4 Key architectural items

4.0 Introduction

The IMS access independence work defines the key functional items that are the building blocks for IMS access independence. And this work should attempt to:

- Define the IMS Boundary Points at the edge of the IMS network to differentiate between the IMS specific functionality and non-IMS specific functionality.

The consequence of this work should be:

- Maximise easy adoption (Plug & Play) of the IMS network to different IP Connectivity Networks.
- Allow the changes and developments inside IMS and outside IMS network to be independent therefore achieve minimum or free of the impact between each other.

4.1 IP Connectivity Network Capabilities

Editor's note: This clause is planned to contain considerations on certain IP connectivity network capabilities that may effect the architecture work on IMS commonality and interoperability. E.g.: IPv6 capability, mobility (Mobile-IPv6), Security, QoS, Charging, etc...

No assumptions are made about the QoS capabilities of the IP Connectivity Network.

It is a deployment issue to ensure that the QoS capabilities in the IP Connectivity Network are sufficient to support the service set offered by the operator.

Whether and how to ensure that services are not invoked on IP Connectivity networks which do not have the QoS capabilities to support them requires further study. The possibilities below have been suggested. Other possibilities may also exist.

- The P-CSCF may apply policies to limit the user to the supported service set for a given IP Connectivity Network, or
- The UE should not activate services if it cannot obtain the necessary QoS from the IP Connectivity Network

Whether the P-CSCF needs to know, or how the P-CSCF determines which IP Connectivity Network is being used, or how the UE determines the QoS available from the IP Connectivity Network is for further study.”

4.1.1 Requirements for Service Based Local Policy

The following capabilities may be supported by the IP Connectivity network in order to enable Service Based Local Policy. (The exact capabilities that are required depend on the mode in which Service Based Local Policy is used as described below.)

- 1a. The ability to inform the IMS when a resource reservation is requested in the IP Connectivity Network
- 1b. The ability to act on an authorisation decision received from the IMS in response to the indication in 1a. The decision contains an upper bound on the QoS for the resource reservation.
2. The ability to provide the IMS with correlation information identifying the charging information associated with the resource reservation identified in 1a above.
3. The ability act on revocations of the authorisations sent by the IMS
4. The ability to inform the IMS when a resource reservation is removed in the IP connectivity network

The capabilities 1 to 4 exist in Release 5 for GPRS. The following capabilities are speculative: they do not exist for any 3GPP-specified IP connectivity network and are dependent on the outcome of investigations in Release 6.

5. The ability to provide Diffserv Edge Functions for individual IP flows configured based on the policy information from the IMS.
6. The ability to provide the IMS with correlation information identifying the charging information associated with an individual IP flow

Service Based Local Policy, if supported at all, may operate in several modes:

A) Authorisation & Charging Correlation

SBLP operates essentially as described in Release 5, performing resource authorisation and correlation of charging information.

B) Authorisation Only

SBLP allows resource authorisation in the IP Connectivity Network to be controlled by the IMS, but there is no support for charging correlation.

C) Charging correlation only

SBLP allows correlation of charging for IP Connectivity Network resources with the IMS session, but does not support any control of resource authorisation.

In each of these modes, the operation of SBLP could be either:

- **Reservation-based**, in which the granularity of authorisation and charging correlation is a single resource reservation in the IP connectivity network
- **IP flow based**, in which the granularity of authorisation and charging correlation is a single IP flow identified by the IMS

Reservation-based Authorisation requires capabilities (1), (3) and (4).

Reservation-based Charging Correlation required capabilities (1a) and (2)

IP flow based Authorisation requires capability (5)

IP flow based Charging Correlation requires capability (6)

Combinations of these SBLP functions require the appropriate combination of IP connectivity network capabilities.

Where Service Based Local Policy is used in reservation-based modes, then resource reservation signalling in the IP-connectivity network must support either:

- Complete specification of the IP flows which will use the resource (uplink and downlink) in terms of standard IP flow classifiers, or
- Carriage of Flow Ids as defined for IMS Release 5

Where Service Based Local Policy is used in reservation-based modes, the IP connectivity network must support carriage of a media authorisation token (see RFC3313) in association with signalling for resource reservation/allocation.

4.2 Backwards compatibility

The possible architectural enhancements for IMS access independence shall be backwards compatible with the IMS architecture specified in Rel5 to the farthest extent possible.

4.3 General architectural considerations

Editor's note: This clause is planned to identify the access specific "parts" and the possible split of access -specific and access independent "parts" of IMS functional elements, where applicable.

4.4 User and service profile

Editor's note: If needed, this clause is planned to contain the architectural solution on user profile and HSS -related concepts.

4.5 QoS and Service-Based Local Policy

Editor's note: This clause is planned to contain the architectural concepts for IMS commonality and interoperability related to Service-Based Local Policy (Go interface) and end-to-end QoS.

4.5.1 Service Based Local Policy functions

Service Based Local Policy performs two functions:

- Correlation of access resource usage with an application level session instance. This allows charging for the resources used for a particular session to be based on features of the session, rather than simply resource usage. For example, the resources used at the called party could be charged to the calling party ("A party pays model").
- Network control of the QoS authorised for resources to be linked to a session instance

4.6 UE and ISIM/USIM

Editor's note: This clause is planned to contain the UE-related architectural concepts and ISIM/USIM related considerations to the extent applicable for SA2.

4.7 IP version issues

Editor's note: This clause is planned to look at the architectural effects of mandating IPv6 in IMS.

4.8 Security

Editor's note: This clause is planned to analyze if Rel5 IMS Security mechanisms (built on AKA) are sufficient for IMS running over any access network, or some enhancement to the current standardized security solutions are needed.

4.9 Charging

Editor's note: If needed, this clause is planned to develop architectural concepts for enhancing the charging architecture developed in Rel5.

4.10 Bearer level considerations

Editor's note: This clause is planned to contain the architectural concepts on bearer-level connectivity, e.g.: AMR support, transcoding, etc...

4.11 SIP Compression

Editor's note: This clause will contain the architectural considerations on providing SIP compression over different kind of accesses (cellular, non-cellular, etc...).

Support of SIP signaling compression is mandatory for P-CSCF for IMS and UEs using a cellular access (e.g. UTRAN, GERAN, CDMA2000).

4.12 Emergency calls

Editor's note: This clause is planned to contain the architectural considerations for providing IMS Emergency calls over different access networks. This might overlap with the generic IMS Emergency call work to be conducted in Rel6.

4.13 Documentation and Terminology aspects

Editor's note: This clause is planned to address generalizing the terminologies used throughout IMS Technical Specifications. The initial goal is to find terminologies facilitating IMS commonality and interoperability over different IP-Connectivity networks.

This clause is also planned to address the possible re-organization of IMS-related Technical Specifications.

The following set of 3GPP Technical Specifications was identified as the core set subject to (re-)structuring to better facilitate IMS commonality and interoperability:

1. 3GPP TS 23.218: IP Multimedia (IM) session handling; IM call model
2. 3GPP TS 23.228: IP Multimedia Subsystem (IMS); Stage 2
3. 3GPP TS 24.229: IP Multimedia Call Control Protocol based on SIP and SDP; Stage 3
4. 3GPP TS 29.xxx: Media Gateway Controller Function (MGCF) – IM-Media Gateway (MGW) interface; Stage 3
5. 3GPP TS 29.162: Interworking between the IM CN subsystem and IP networks
6. 3GPP TS 29.163: Interworking between the IM CN subsystem and CS networks
7. 3GPP TS 29.228: IP Multimedia (IM) Subsystem Cx Interface; Signalling flows and message contents
8. 3GPP TS 29.229: Cx Interface based on the Diameter protocol; Protocol details
9. 3GPP TS 29.328: IP Multimedia Subsystem (IMS) Sh Interface; Signalling flows and message contents
10. 3GPP TS 29.329: Sh interface based on the Diameter protocol; Protocol details

TS 23.228 is intended to be re-structured for Rel6 so that the GPRS-specific pieces of specification from all across the TS would be moved to a separate clause. Possible need for changes in access-related terminology used in the IMS level clauses of the TS will be addressed on a per-need basis within the context of the re-organization work.

The CR in [\[3\]](#) describes a draft of such a re-organization on TS 23.228 v6.0.1. The CR will be maintained and updated until it reaches a mature state and can be presented for approval.

Annex <A>:
<Annex title>

A.1 Heading levels in an annex

Heading levels within an annex are used as in the main document, but for Heading level selection, the "A.", "B.", etc. are ignored. e.g. **A.1.2** is formatted using *Heading 2* style.

Annex <X>:
Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New