3GPP TS 24.166 V11.0.0 (2012-09)

Technical Specification

3rd Generation Partnership Project;
Technical Specification Group Core Network and Terminals;
3GPP IP Multimedia Subsystem (IMS) conferencing
Management Object (MO)
(Release 11)





Specifications and reports for implementation of the 3GPP TM system should be obtained via the 3GPP Organizational Partners' Publications Offices.

Keywords

LTE, UMTS, IMS, SIP, Multimedia, Management,
GSM

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis Valbonne - FRANCE Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

http://www.3gpp.org

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© 2012, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TTA, TTC).
All rights reserved.

UMTSTM is a Trade Mark of ETSI registered for the benefit of its members $3GPP^{TM}$ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners LTETM is a Trade Mark of ETSI currently being registered for the benefit of its Members and of the 3GPP Organizational Partners GSM® and the GSM logo are registered and owned by the GSM Association

Contents

Fore	word						
1	Scope						
	-						
2	References						
3	Definitions and abbreviations						
3.1							
3.2	Definitions						
4	IMS conferencing management object						
5		parameters					
5.1	General	outunio toto	6				
5.2	Node: /< <i>X</i> >		6				
5.3	/< <i>X</i> >/Name		6				
5.4	/ <x>/Conf_Factory_URI</x>						
5.5	/ <x>/Ext</x>						
Ann	ex A (informative):	Management object DDF	8				
Ann	ex B (informative):	Change history					

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

This document defines the IMS conferencing management object. The management object is compatible with OMA Device Management protocol specifications, version 1.2 and upwards, and is defined using the OMA DM Device Description Framework as described in the Enabler Release Definition OMA-ERELD_DM-V1_2 [3].

The IMS conferencing management object consists of relevant parameters that can be managed for IMS conferencing capabilities.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document.
- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 24.147: "Conferencing using the IP Multimedia (IM) Core Network (CN) subsystem; Stage 3".
- [3] OMA-ERELD-DM-V1_2-20070209-A: "Enabler Release Definition for OMA Device Management, Version 1.2".
- [4] IETF RFC 4579 (August 2006): "Session Initiation Protocol Call Control Conferencing for User Agents".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] apply.

The following terms and definitions given in in IETF RFC 4579 [4] apply:

Conference Factory URI

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CN Core Network

DDF Device Description Framework

DM Device Management

IMS IP Multimedia core network Subsystem

IP Internet Protocol
MO Management Object
OMA Open Mobile Alliance
SIP Session Initiation Protocol

UE User Equipment

4 IMS conferencing management object

The IMS conferencing management object is used to manage configuration settings of the UE for IMS conferencing. The management object covers parameters for IMS conferencing related capabilities. The management object enables the management of the settings on behalf of the end user.

The Management Object Identifier is: urn:o ma:mo:ext-3gpp-conf:1.0.

Protocol compatibility: This MO is compatible with OMA DM 1.2.




Figure 1: The 3GPP Conferencing Management Object

5 Management object parameters

5.1 General

This clause describes the parameters for the IMS conferencing management object.

5.2 Node: /<X>

This interior node acts as a placeholder for one or more accounts for a fixed node.

- Occurrence: OneOrMore

- Format: node

Access Types: Get

- Values: N/A

The interior node is mandatory if the UE supports one or more IMS conferencing capabilities. Support for a UE is defined by the related roles as defined by the related IMS conferencing service.

NOTE: One node is normally used.

5.3 /<X>/Name

The Name leaf is a name for the conferencing settings.

- Occurrence: ZeroOrOne

Format: chr

- Access Types: Get

- Values: <User displayable name>

5.4 /<X>/Conf_Factory_URI

The Conf_Factory_URI leaf defines a Conference Factory URI as defined by IETF RFC 4579 [4] that is supported by a subscriber's network as described in 3GPP TS 24.147 [2].

- Occurrence: ZeroOrOne

Format: chr

- Access Types: Get, Replace

- Values: <A Conference Factory URI>

5.5 /<X>/Ext

The Ext is an interior node for where the vendor specific information about the IMS conferencing management is being placed (vendor meaning application vendor, device vendor etc.). Usually the vendor extension is identified by vendor specific name under the ext node. The tree structure under the vendor identified is not defined and can therefore include one or more un-standardized sub-trees.

- Occurrence: ZeroOrOne

- Format: node

- Access Types: Get

- Values: N/A

Annex A (informative): Management object DDF

This DDF is the standardized minimal set. A vendor can define its own DDF for the complete device. This DDF can include more features than this minimal standardized version.

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE MgmtTree PUBLIC "-//OMA//DTD-DM-DDF 1.2//EN"</pre>
             "http://www.openmobilealliance.org/tech/DTD/DM_DDF-V1_2.dtd">
   <VerDTD>1.2</VerDTD>
   <Man>--The device manufacturer--</Man>
   <Mod>--The device model--</Mod>
       <NodeName> IMS conferencing </NodeName>
       <DFProperties>
            <AccessType>
               <Get/>
            </AccessType>
            <Description>IMS conferencing configuration parameters/Description>
            </DFFormat>
            <Occurrence>
                <OneOrMore/>
            </Occurrence>
            <Scope>
                <Permanent/>
            </Scope>
            <DFTitle>The IMS conferencing Management Object.
            <DFType>
                <DDFName/>
           </DFType>
        </DFProperties>
            <NodeName>Conference Factory URI</NodeName>
            <DFProperties>
                <AccessType>
                    <Get/>
                   <Replace/>
                </AccessType>
                <DFFormat>
                    <chr/>
                </DFFormat>
                <Occurrence>
                    <ZeroOrOne/>
                </Occurrence>
                <Scope>
                    <Dynamic/>
                </Scope>
                <DFTitle>The Confernece Factory URI.
                <DFType>
                    <MIME>text/plain</MIME>
                </DFType>
            </DFProperties>
        </Node>
            <NodeName>Ext</NodeName>
            <!-- The Extension node starts here. -->
            <DFProperties>
                <AccessType>
                   <Get/>
                   <Replace/>
                </AccessType>
                <DFFormat>
                   <node/>
                </DFFormat>
                <Occurrence>
                    <ZeroOrOne/>
                </Occurrence>
                <Scope>
                    <Dvnamic/>
                </Scope>
```

Annex B (informative): Change history

Change history										
Date	TSG#	TSG Doc.	CR	Rev	Subject/Comment	Old	New	WG doc		
2009-10					Version 0.0.0: First proposal		0.0.0			
2009-10					Version 0.0.1 due to comments in CT1#61	0.0.0	0.0.2			
2009-11					Author proposes to use urn:oma:mo:ext-3gpp-conf:1.0	0.0.1	0.0.2			
2009-11					Comments received on proposal for urn:oma:mo:ext-3gpp- conf:1.0. This needs to be documented as an EN	0.0.2	0.0.3			
2009-11	CP-46	CP- 090888			Version 1.0.0 created by MCC for presentation to CT-46 for information and approval	0.0.3	1.0.0			
2009-12	CP-46	CP- 091044			Formal number added	1.0.0	1.0.1			
2009-12	CP-46				Version 9.0.0 created by MCC after approval at CT-46	1.0.1	9.0.0			
2010-03	CP-47	CP- 100135	0001		Missing "Ext" interior node	9.0.0	9.1.0	C1-100451		
2011-03	CP-51	CP- 110174	0002		MO identifier registered by OMNA	9.1.0	9.2.0	C1-110074		
2011-03	CP-51				Upgrade to Rel-10	9.2.0	10.0.0			
2012-09	CP-57				Upgrade to Rel-11	10.0.0	11.0.0			