# 3GPP TS 28.402 V0.2.0 (2013-06)

**Technical Specification** 

3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; Performance Management (PM); Performance measurements for Evolved Packet Core (EPC) and non-3GPP access Interworking System (Release 12)





The present document has been developed within the 3<sup>rd</sup> Generation Partnership Project (3GPP <sup>TM</sup>) and may be further elaborated for the purposes of 3GPP.. The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification. Specifications and Reports for implementation of the 3GPP <sup>TM</sup> system should be obtained via the 3GPP Organizational Partners' Publications Offices. Keywords EPC, WLAN interworking, Performance

3GPP

Postal address

3GPP support office address 650 Route des Lucioles - Sophia Antipolis Valbonne - FRANCE Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

http://www.3gpp.org

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© 2013, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TTA, TTC). All rights reserved.

UMTS<sup>TM</sup> is a Trade Mark of ETSI registered for the benefit of its members 3GPP<sup>TM</sup> is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners LTE<sup>TM</sup> is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners GSM® and the GSM logo are registered and owned by the GSM Association

# Contents

Forev	vord	.4		
Introduction				
1	Scope	.6		
2	References	.6		
3	Definitions and abbreviations			
3.1	Definitions	.6		
3.2	Abbreviations	.7		
4	Measurements related to ePDG	.7		
4.1	Tunnel Establishment Measurements	7		
4.1.1	Attempted Tunnel Establishment Successful Tunnel Establishment	7		
4.1.2	Successful Tunnel Establishment	.7		
4.1.3	Failed Tunnel Establishment	.7		
Annex A: Use cases for performance measurements definition				
A.1	Use case for tunnel establishment measurements	.9		
Anne	x B: Change history1	.0		

3

## Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

4

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

#### Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

32.401	Performance Management (PM); Concept and requirements
52.402	Performance Management (PM); Performance measurements - GSM
32.404	Performance Management (PM); Performance measurements - Definitions and template
32.405	Performance Management (PM); Performance measurements Universal Terrestrial Radio Access Network (UTRAN)
32.406	Performance Management (PM); Performance measurements Core Network (CN) Packet Switched (PS) do main
32.407	Performance Management (PM); Performance measurements Core Network (CN) Circuit Switched (CS) domain
32.408	Performance Management (PM); Performance measurements Teleservice
32.409	Performance Management (PM); Performance measurements IP Multimedia Subsystem (IMS)
32.425	Telecommunication management; Performance Management (PM); Performance measurements Evolved Universal Terrestrial Radio Access Network (E-UTRAN)
32.426	Telecommunication management; Performance Management (PM); Performance measurements Evolved Packet Core (EPC) network
32.452	Performance Management (PM); Performance measurements Home Node B Subsystem (HNS)
32.453	Performance Management (PM); Performance measurements Home enhanced Node B Subsystem (HeNS)
28.401	Performance Management (PM); Performance measurements for Core Network (CN) and non- 3GPP access Interworking System
28.402	Performance Management (PM); Performance measurements for Evolved Packet Core (EPC) and non-3 GPP access Interworking System

The present document is part of a set of specifications, which describe the requirements and information model necessary for the standardised Operation, Administration and Maintenance (OA&M) of the Evolved Packet Core (EPC) and Wireless Local Area Network (WLAN) Interworking System.

During the lifetime of interworking network, its logical and physical configuration will undergo changes of varying degrees and frequencies in order to optimise the utilisation of the network resources. These changes will be executed through network configuration management activities and/or network engineering, see 3GPP TS 32.600 [1].

Many of the activities involved in the daily operation and future network planning of interworking require data on which to base decisions. This data refers to the load carried by the network and the grade of service offered. In order to produce this data performance measurements are executed in the NEs, which comprise the network. The data can then be transferred to an external system, e.g. an Operations System (OS) in TMN terminology, for further evaluation.

Annex B of TS 32.404 [2] helps in the definition of new performance measurements that can be submitted to 3GPP for potential adoption and inclusion in the present document. Annex B of TS 32.404 discusses a top-down performance measurement definition methodology that focuses on how the end-user of performance measurements can use the measurements.

## 1 Scope

The present document describes the measurements for EPC and non-3GPP interworking system.

TS 32.401 [3] describes Performance Management concepts and requirements.

The present document is valid for all measurement types provided by an implementation of a interworking system. Only measurement types that are specific to interworking system are defined within the present documents. Vendor specific measurement types used in interworking system are not covered. Instead, these could be applied according to manufacturer's documentation.

Measurements related to "external" technologies (such as ATM or IP) as described by "external" standards bodies (e.g. ITU-T or IETF) shall only be referenced within this specification, wherever there is a need identified for the existence of such a reference.

The definition of the standard measurements is intended to result in comparability of measurement data produced in a multi-vendor network, for those measurement types that can be standardised across all vendors' implementations.

The structure of the present document is as follows:

- Header 1: Network Element (e.g. measurements related to ePDG);
- Header 2: Measurement function (e.g. FFS);
- Header 3: Measurements.

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
- [2] 3GPP TS 32.404: "Performance Management (PM); Performance measurements Definitions and template".
- [3] 3GPP TS 32.401: "Telecommunication management; Performance Management (PM); Concept and requirements".
- [4] 3GPP TS 23.402: "Architecture enhancements for non-3GPP accesses".

## 3 Definitions and abbreviations

#### 3.1 Definitions

The measurement names defined in the present document are all beginning with a prefix containing the measurement family name. This family name identifies all measurements which relate to a given functionality and it may be used for measurement administration (see TS 32.401 [3]).

6

The list of families currently used in the present document is as follows:

- TUN (measurements related to Tunnel Establishment Management)

#### 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ePDG Evolved Packet Data Gateway

## 4 Measurements related to ePDG

#### 4.1 Tunnel Establishment Measurements

The measurements types defined in subclauses 6.x are subject to the "2 out of 3 approach".

#### 4.1.1 Attempted Tunnel Establishment

- a) This measurement provides the number of attempted tunnel establishment
- b) CC
- c) Receipt of tunnel establishment request message from UE to ePDG
- d) A single integer value
- e) TUN.TunEst Att
- f) EPDGFunction
- g) Valid for packet switched traffic.
- h) EPS

#### 4.1.2 Successful Tunnel Establishment

- a) This measurement provides the number of successful tunnel establishment
- b) CC.
- c) Transmission of tunnel establishment response message from ePDG to UE
- d) A single integer value.
- e) TUN.TunEstSucc
- f) EPDGFunction
- g) Valid for packet switched traffic.
- h) EPS

#### 4.1.3 Failed Tunnel Establishment

- a) This measurement provides the number of failed tunnel establishment
- b) CC
- c) Transmission of tunnel establishment reject message from ePDG to UE

- d) A single integer value.
- e) TUN.TunEstFail
- f) EPDGFunction
- g) Valid for packet switched traffic.
- h) EPS

# Annex A: Use cases for performance measurements definition

The present annex provides the concrete use cases for the interworking system performance measurements defined in clause 4.

## A.1 Use case for tunnel establishment measurements

It's required to setup secure tunnels between WLAN UE and remote tunnel endpoint once UE attaches to interworking system. The tunnel shall reside between the WLAN UE and ePDG. In order to guarantee the user experiences, the tunnel should be established before the data is transmitted. During the period of tunnel establishment, ePDG may reject the tunnel establishment due to WLAN QoS profile request or policy enforcement in AAA servers. Those rejections would impact subsequent traffic transmission and user experiences. It's desirable to operators to get the indications before massive rejection happened.

9

# Annex B: Change history

Change history										
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New			
Apr 2013					Initial version for TS skeleton	0.0.0	0.0.1			
May 2013					Update the draftw ith the comments at the meeting and email approval	0.0.1	0.1.0			
Jun 2013					Add performance measurement to TUN	0.1.0	0.2.0			