

3GPP TS 28.625 V11.0.0 (2012-12)

Technical Specification

**3rd Generation Partnership Project;
Technical Specification Group Services and System Aspects;
Telecommunication management;
State Management Data Definition
Integration Reference Point (IRP);
Information Service (IS)
(Release 11)**



The present document has been developed within the 3rd Generation Partnership Project (3GPPTM) and may be further elaborated for the purposes of 3GPP. The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification. Specifications and reports for implementation of the 3GPPTM system should be obtained via the 3GPP Organizational Partners' Publications Offices.

Keywords

NRM, IRP, Converged Management, State

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2012, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TTA, TTC).
All rights reserved.

UMTS™ is a Trade Mark of ETSI registered for the benefit of its members
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners
LTE™ is a Trade Mark of ETSI currently being registered for the benefit of its Members and of the 3GPP Organizational Partners
GSM® and the GSM logo are registered and owned by the GSM Association

Contents

Foreword	4
Introduction	4
1 Scope	5
2 References.....	5
3 Definitions and abbreviations	6
3.1 Definitions	6
3.2 Abbreviations.....	6
4 Model.....	6
4.1 Information entities imported and local labels	6
4.2 Class diagram.....	6
4.2.1 Relationships.....	6
4.2.2 Inheritance	6
4.3 Class definitions.....	7
4.3.1 StateManagementEntity	7
4.3.1.1 Definition	7
4.3.1.2 Attributes.....	7
4.3.1.3 Attribute constraints	7
4.4 Attribute definitions	7
4.4.1 Attribute properties.....	7
Annex A (informative): Change history	10

Foreword

This Technical Specification (TS) has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Ready for Converged Management

This specification is part of a set that has been developed for converged management solutions.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

- 28.624 State Management Data Definition Integration Reference Point (IRP); Requirements
- 28.625 State Management Data Definition Integration Reference Point (IRP); Information Service (IS)**
- 28.626 State Management Data Definition Integration Reference Point (IRP); Solution Set (SS) definitions

1 Scope

The present document specifies the State Management Data Definition IRP Information Service that can be communicated between an IRP Agent and an IRP Manager for telecommunication network management purposes, including management of converged networks.

The present document specifies the semantics and behaviour of information object class attributes and relations visible across the reference point in a protocol and technology neutral way. It does not define their syntax and encoding.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] 3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects".
- [4] 3GPP TS 32.302: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP): Information Service (IS)".
- [5] 3GPP TS 32.312: "Telecommunication management; Generic Integration Reference Point (IRP) management; Information Service (IS)".
- [6] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
- [7] ITU-T Recommendation X.731: "Information technology - Open Systems Interconnection - Systems Management: State management function".
- [8] ITU-T Recommendation X.733: "Information technology - Open Systems Interconnection - Systems Management: Alarm reporting function".
- [9] 3GPP TS 32.111-2: "Telecommunication management; Fault Management; Part 2: Alarm Integration Reference Point (IRP): Information Service (IS)".
- [10] 3GPP TS 32.662: "Telecommunication management; Configuration Management (CM); Kernel CM Information Service (IS)".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TS 32.101 [1], 3GPP TS 32.102 [2] and 3GPP TS 32.600 [6] apply.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CM	Configuration Management
EM	Element Manager
IOC	Information Object Class
IRP	Integration Reference Point
IS	Information Service (see 3GPP TS 32.101 [1])
M	Mandatory
NE	Network Element
NM	Network Manager
NR	Network Resource
O	Optional
OMG	Object Management Group
OS	Operations System
QoS	Quality of Service
UML	Unified Modelling Language (OMG)

4 Model

4.1 Information entities imported and local labels

Label reference	Local label

4.2 Class diagram

4.2.1 Relationships

There is no relationship.

4.2.2 Inheritance

There are no inheritance relationships.

4.3 Class definitions

4.3.1 StateManagementEntity

4.3.1.1 Definition

StateManagementEntity is a Archetype, that may represent any IOC defined in the Network Resource Models, e.g. Generic Network Resource Model, Core Network Resource Model, UTRAN Network Resource Model or GERAN Network Resource Model.

The attributes defined for this Archetype can be imported and used in any IOC of the Network Resource Models, where such attributes are needed. These attributes shall be used in the same way as defined in the ITU-T Recommendation X.731 [7] and ITU-T Recommendation X.733 [8], unless otherwise stated. That document gives also examples of state diagrams, defining possible state transitions when one or more of the state attributes defined here are used in a class.

4.3.1.2 Attributes

The following attributes are defined for this Archetype.

Attribute Name
operationalState
usageState
administrativeState
alarmStatus
proceduralStatus
availabilityStatus
controlStatus
standbyStatus
unknownStatus

4.3.1.3 Attribute constraints

None.

4.4 Attribute definitions

4.4.1 Attribute properties

The following table gives the definition and legal values for each attribute.

Attribute Name	Documentation and Allowed Values	Properties
operationalState	It indicates the operational state of the object instance. "It describes whether or not the resource is physically installed and working." [7] This attribute is READ-ONLY. The meaning of these values is as defined in ITU-T Recommendation X.731 [7]. allowedValues: "Enabled", "Disabled"	type: String multiplicity: 1 isOrdered: N/A isUnique: N/A defaultValue: None isNullable: False
usageState	It indicates the usage state of the object instance. "It describes whether or not the resource is actively in use at a specific instant, and if so, whether or not it has spare capacity for additional users at that instant." [7] This attribute is READ-ONLY. The meaning of these values is as defined in ITU-T Recommendation X.731 [7]. allowedValues: "Idle", "Active", "Busy"	type: String multiplicity: 1 isOrdered: N/A isUnique: N/A defaultValue: None isNullable: False
administrativeState	It indicates the administrative state of the object instance. "It describes the permission to use or prohibition against using the resource, imposed through the management services." [7] The meaning of these values is as defined in ITU-T Recommendation X.731 [7]. allowedValues: "Locked", "Shutting down", "Unlocked"	type: String multiplicity: 1 isOrdered: N/A isUnique: N/A defaultValue: None isNullable: False
alarmStatus	It indicates the alarm status of the object instance. This is mapped to the perceived severity of the most severe active alarm associated to the object instance. The meaning of these values is as defined for the attribute perceived severity in ITU-T Recommendation X.733 [8]. allowedValues: "Cleared", "Indeterminate", "Warning", "Minor", "Major", "Critical",	type: String multiplicity: 1 isOrdered: N/A isUnique: N/A defaultValue: None isNullable: False
proceduralStatus	It indicates the procedural status of the object instance. The meaning of these values is as defined in ITU-T Recommendation X.731 [7]. allowedValues: "Initialisation required", "Not initialised", "Initialising", "Reporting", "Terminating".	type: String multiplicity: 1..* isOrdered: False isUnique: True defaultValue: None isNullable: True
availabilityStatus	It indicates the availability status of the object instance. The meaning of these values is as defined in ITU-T Recommendation X.731 [7]. allowedValues: "In test", "Failed", "Power off", "Off line", "Off duty", "Dependency", "Degraded", "Not installed", "Log full"	type: String multiplicity: 1..* isOrdered: False isUnique: True defaultValue: None isNullable: True
controlStatus	It indicates the control status of the object instance. The meaning of these values is as defined in ITU-T Recommendation X.731 [7]. allowedValues: "Subject to test", "Part of services locked", "Reserved for test", "Suspended"	type: String multiplicity: 1..* isOrdered: False isUnique: True defaultValue: None isNullable: True
standbyStatus	It indicates the standby status of the object instance. The meaning of these values is as defined in ITU-T Recommendation X.731 [7]. allowedValues: "Hot standby", "Cold standby", "Providing service",	type: String multiplicity: 1 isOrdered: N/A isUnique: N/A defaultValue: None isNullable: False

Attribute Name	Documentation and Allowed Values	Properties
UnknownStatus	It indicates whether the state of the resource represented by the managed object is unknown. "True" (state is unknown, the values of the state attributes may not reflect the actual state of the resource); "False" (state is known, the values of the state attributes reflect the actual state of the resource). allowedValues: "True", "False".	type: String multiplicity: 1 isOrdered: N/A isUnique: N/A defaultValue: None isNullable: False

Annex A (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2012-10					First Draft		0.1.0
2012-12					Draft sent for Information and Approval	0.1.0	1.0.0
2012-12					New version after approval	1.0.0	11.0.0