## 3GPP TS 29.199-12 V9.0.0 (2009-12)

Technical Specification

3rd Generation Partnership Project;
Technical Specification Group Core Network and Terminals;
Open Service Access (OSA);
Parlay X Web Services;
Part 12: Multimedia conference
(Release 9)





The present document has been developed within the 3<sup>rd</sup> Generation Partnership Project (3GPP <sup>TM</sup>) and may be further elaborated for the purposes of 3GPP. The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented.

This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification. Specifications and reports for implementation of the 3GPP TM system should be obtained via the 3GPP Organizational Partners' Publications Offices.

Keywords
UMTS, network, API, OSA

#### 3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis Valbonne - FRANCE Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

http://www.3gpp.org

#### Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

©2009, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TTA, TTC). All rights reserved.

 $UMTS^{TM}$  is a Trade Mark of ETSI registered for the benefit of its members  $3GPP^{TM}$  is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners  $LTE^{TM}$  is a Trade Mark of ETSI currently being registered for the benefit of its Members and of the 3GPP Organizational Partners GSM and the GSM logo are registered and owned by the GSM Association

## Contents

Forew	vord	5
Introd	luction	5
1	Scope	e
2	References	e
3	Definitions and abbreviations	
3.1	Definitions	
3.2	Abbreviations	
4	Detailed service description	
5	Namespaces	9
6	Sequence diagrams	10
6.1	Setting up a conference	10
6.2	Void	
6.3	Conference owner disconnects	11
6.4	All participants disconnect	12
6.5	Conference ended by application	
7	XML Schema data type definition	14
7.1	ConferenceStatus enumeration	
7.2	ConferenceInfo structure	
7.3	Partic ipantInfo structure	
7.4	ParticipantStatus enumeration	
7.5	Void	
7.6	Void	
7.7	Vo id	14
8	Web Service interface definition	15
8.1	Interface: Multimedia Conference	
8.1.1	Operation: createConference	
8.1.1.1	•	
8.1.1.2		
8.1.1.3		
8.1.2	Operation: get ConferenceInfo	
8.1.2.1		
8.1.2.2		
8.1.2.3		
8.1.3	Operation: end Conference	17
8.1.3.1	Input message: endConferenceRequest	17
8.1.3.2	2 Output message: endConferenceResponse	17
8.1.3.3	Referenced faults	17
8.1.4	Operation: inviteParticipant	18
8.1.4.1	Input message: inviteParticipantRequest	18
8.1.4.2	2 Output message: inviteParticipantResponse	18
8.1.4.3		
8.1.5	Operation: disconnectParticipant	
8.1.5.1		
8.1.5.2		
8.1.5.3		
8.1.6	Operation: getParticipantInfo	
8.1.6.1		
8.1.6.2		
8.1.6.3		
8.1.7	Operation: getParticipants	
8.1.7.1	I Input message: getParticipantsRequest	20

Output message: getParticipantsResponse	20
Referenced faults	20
Void	20
Void	20
Fault definitions	21
PolicyException	21
<b>7</b> 1	
Void	
POL0242: Maximum duration exceeded	21
Service Exception	21
Vo id	21
Void	21
Service policies	21
x A (normative): WSDL for Multimedia conference	22
	23
Specific Exceptions	23
Clause 2: References	
Clause 3: Definitions and abbreviations	23
Clause 4: Detailed service description	23
Clause 5: Namespaces	23
Clause 6: Sequence diagrams	24
Clause 7: XML Schema data type definition	
Clause 8: Web Service interface definition	24
Clause 9: Fault definitions	
	24
Clause 10: Service policies	24 24
Clause 10: Service policies	24 24
	Void

#### **Foreword**

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

3GPP acknowledges the contribution of the Parlay X Web Services specifications from The Parlay Group. The Parlay Group is pleased to see 3GPP acknowledge and publish the present document, and the Parlay Group looks forward to working with the 3GPP community to improve future versions of the present document.

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

#### where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

#### Introduction

The present document is part 12 of a multi-part deliverable covering the 3<sup>rd</sup> Generation Partnership Project; Technical Specification Group Core Network and Terminals; Open Service Access (OSA); Parlay X Web Services, as identified below:

Part 1:	"Common"
Part 2:	"Third party call"
Part 3:	"Call Notification"
Part 4:	"Short Messaging"
Part 5:	"Multimedia Messaging"
Part 6:	"Payment"
Part 7:	"Account management"
Part 8:	"Terminal Status"
Part 9:	"Terminal location"
Part 10:	"Call handling"
Part 11:	"Audio call"
<b>Part 12:</b>	"Mul time di a conference"
Part 13:	"Address list management"
Part 14:	"Presence"
Part 15:	"Message Broadcast"
Part 16:	"Geocoding"
Part 17:	"Application driven Quality of Service (QoS)"
Part 18:	"Device Capabilities and Configuration"
Part 19:	"Multimedia streaming control"
Part 20:	"Multimedia multicast session management"
Part 21:	"Content management"
Part 22:	"Policy"

## 1 Scope

The present document is Part 12 of the Stage 3 Parlay X Web Services specification for Open Service Access (OSA).

The OSA specifications define an architecture that enables application developers to make use of network functionality through an open standardized interface, i.e. the OSA APIs. The concepts and the functional architecture for the OSA are contained in 3GPP TS 23.198 [3]. The requirements for OSA are contained in 3GPP TS 22.127 [2].

The present document specifies the Multimedia Conference Web Service aspects of the interface. All aspects of the Multimedia Conference Web Service are defined here, these being:

- Name spaces.
- Sequence diagrams.
- Data definitions.
- Interface specification plus detailed method descriptions.
- Fault definitions.
- Service policies.
- WSDL Description of the interfaces.

The present document has been defined jointly between 3GPP TSG CT WG5, ETSI TISPAN and The Parlay Group.

Maintenance of up to 3GPP Rel-8 and new OSA Stage 1, 2 and 3 work beyond Rel-9 was moved to OMA in June 2008.

### 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document.
- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 22.127: "Service Requirement for the Open Services Access (OSA); Stage 1".
- [3] 3GPP TS 23.198: "Open Service Access (OSA); Stage 2".
- [4] 3GPP TS 22.101: "Service aspects; Service principles".
- [5] W3C Recommendation (2 May 2001): "XML Schema Part 2: Datatypes".

NOTE: Available at <a href="http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/">http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/</a>.

[6] 3GPP TS 29.199-1: "Open Service Access (OSA); Parlay X Web Services; Part 1: Common".

## 3 Definitions and abbreviations

## 3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TS 29.199-1 [6] apply.

#### 3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TS 29.199-1 [6] apply.

## 4 Detailed service description

The Multimedia Conferencing is a simple Web Service that allows the creation of a multimedia conference and the dynamic management of the participants involved.

The underlying model of the service is based on the following entities:

- Conference: a "context" (uniquely identified) to which participants can be added/removed.
- **Partici pant:** each of the parties involved in the conference. There may exist a participant that is also the "owner" of the conference, i.e. the user who can end the call and/or be the reference user for billing purposes.
- **Media:** the conference can utilize multiple media streams to support the participants' communication. In particular both audio and video streams are available, including the specific stream direction (i.e. in, out, bidirectional).

NOTE: A call session allows the application to avail of other web service features that can add value to the created call session. For example the Audio Call web service can provide multimedia message delivery to call participants in the call session (playXXXMessage operation) and furthermore control of the media streams for the call participants thus enabling conversational multimedia communication including voice, video, chat, and data. Media can be added/removed for participants using the operations addMediaForParticipants and deleteMediaForParticipants in Audio Call

An application setting up a multimedia conference must initially invoke the **create Conference** operation. The result of such invocation is the creation of a "context" that represents a "virtual" room where users can "meet". A unique identifier, a callSessionIdentifier is assigned to the just-created conference. At this stage no participant is connected yet.

Subsequently the application may wish to add participants to the conference. In order to do so the operation **inviteParticipant** can be used. The result of such operation is to alert the user of the incoming connection request (e.g. the user's terminal rings).

If the application wishes to check whether the user has accepted the invitation (i.e. is connected) it can invoke (at a later time) the **getPartici pantInfo** operation.

#### Note that:

- As soon as the first participant connects, the conference becomes "active". The duration of the conference is then measured starting from the moment the conference has became active.
- The initial media set utilized by the participant will depend on the conference type and the media actually supported by the participant's terminal.

During the conference session the application is able to:

- Add (or remove) a specific media stream to a single participant: e.g. adding a video bidirectional stream to a participant that has an audio connection to the conference. This can be obtained by invoking the media control (addMediaForParticipants and the delete MediaForParticipants) operations of the Audio Call web service.
- Disconnect a participant from the conference, by invoking the **disconnectParticipant** operation.
- Retrieve information related to the conference and its status, by invoking **getConferenceInfo** and **getParticipants**.

There are different conditions that can determine the end of the conference:

- 1) The application may invoke the operation **endConference**, that "forces" the termination of the conference and the disconnection of all participants.
- 2) The owner of the conference (if defined) leaves the conference. If the owner is not defined this condition will apply when all the participants have left the conference (disconnected).
- 3) The conference duration exceeds a maximum value (specified during the conference creation step).

## 5 Namespaces

The Multimedia Conference interface uses the namespace:

 $http://www.csapi.org/wsdl/parlay\,x/mu\,ltimedia\_conference/v4\_0$ 

The data types are defined in the namespace:

 $http://www.csapi.org/schema/parlay\,x/mu\,ltimed\,ia\_conference/v\,4\_0$ 


The 'xsd' names pace is used in the present document to refer to the XML Schema data types defined in XML Schema [5]. The use of the name 'xsd' is not semantically significant.

## 6 Sequence diagrams

The following sequence diagrams illustrate typical scenarios of interaction between an application and the Multimedia Conferencing Web Service.

## 6.1 Setting up a conference


Set up a multimedia conference call.



#### 6.2 Void


## 6.3 Conference owner disconnects

During a conference call, the conference owner disconnects.




## 6.4 All participants disconnect

End of conference call processing when all participants disconnect.



## 6.5 Conference ended by application

End of conference call processing when the conference is ended by the application.



## 7 XML Schema data type definition

## 7.1 ConferenceStatus enumeration

Element name	Description
Initial	The conference has been created but no participant is connected yet
Acti ve	The conference is active, i.e. at least one user has connected
Terminated	The conference was terminated

#### 7.2 ConferenceInfo structure

Name	Туре	Optional	Description
Status	ConferenceStatus	-	Status of the conference
StartTime	xsd:dateTime	No	The time at which the conference was created
ActiveTime	Xsd:dateTime	-	The time at which the conference was actived
Duration	xsd:int	No	The duration of the conference so far (in seconds)
Owner	xsd:anyURI	-	Conference owner
NumberOfParticipants	xsd:int		Current number of connected participants
Maximum Number Of Participants	xsd:int		Maximum number of participants
CallSessionIdentifier	xsd:string	No	CallSessionIdentifier for the conference
ConferenceDescription	xsd:string	No	Conference description

## 7.3 ParticipantInfo structure

Name	Туре	Optional	Description
Participant	xsd:anyURI	No	Participant identifier
MediaInfo	common: MediaInfo[1unbounded]	No	Media information currently used
StartTime	xsd:dateTime	No	Time this participant joined the conference
Status	ParticipantStatus	No	Status of participant

## 7.4 ParticipantStatus enumeration

Element name	Description
Invited	Participant invited but not connected yet
	Participant connected
Disconnected	Participant disconnected

- 7.5 Void
- 7.6 Void
- 7.7 Void

#### 8 Web Service interface definition

#### 8.1 Interface: MultimediaConference

The Multimedia Conference interface can be used by an application for creating a multimedia conference call and for dynamically managing the participants involved in the call.

#### 8.1.1 Operation: createConference

The invocation of **create Conference** requests to create a multi-media conference with initially no participants connected. The reference to the new multimedia conference is returned in the output parameter.

The conference termination can be driven either by a user action or by the expiring of a maximum duration. In particular, three possible situations are considered. In the first scenario, the concept of the "conference owner" is used. This user that has the control of the call and when the conference owner leaves the conference, all users are disconnected (such a user could be for instance the reference for the conference billing). In this scenario, the optional parameter **conferenceOwner** is present in the method call.

In the second scenario, the conference is terminated when the last participant abandons (in this case the parameter **conferenceOwner** is not present).

A third case is when the optional parameter **maximumDuration** is present: in this situation, when the maximum duration is reached, the conference is terminated.

The selection of the scenario depends on the presence of the optional parameters; if no optional parameter is present, the conference end condition is the disconnection of the last user in conference, if both are present, the conference is terminated when the duration expires (this case could happen if the information concerning the conference owner is needed for billing purposes).

The values **maximumDuration** and **maximumNumberOfParticipants** must not exceed the corresponding service policies otherwise a policy exception is raised.

#### 8.1.1.1 Input message: createConferenceRequest

Part name	Part type	Optional	Description
ConferenceType	ksd:string	Yes	Conference type, i.e. one of a list of operator- specific identifiers that indicates how the conference is rendered on the terminals
ConferenceDescription	xsd:string	No	A text describing the conference
Charging	common:ChargingInformation	Yes	If present, defines the charge per unit of time consumed on the conference call. If the service does not support charging, a PolicyException (POL0008) will be returned.
Ma xim um Duration	ksd:int	Yes	If present it represents the maximum duration of the multimedia conference in seconds. If this parameter is present, it represents the end condition of the conference.
Maximum Number Of Participants	xsd:int	No	Maximum number of participants allowed
ConferenceOwner	ksd:anyURI	Yes	It is the address of the multimedia conference owner. If this parameter is present, and the maximum Duration is not present, the conference is terminated when this user disconnects, else this information can be used for billing or other purpose

#### 8.1.1.2 Output message: createConferenceResponse

Part name Part type Optional			Description
result	xsd:string	No	Call session identifier, the identifier for the created Conference

#### 8.1.1.3 Referenced faults

Service Exception from 3GPP TS 29.199-1 [6]:

- SVC0001: Service error.
- SVC0002: Invalid input value.

PolicyException from 3GPP TS 29.199-1 [6]:

- POL0001: Policy error.
- POL0008: Charging not supported.
- POL0012 Too many description entries specified.
- POL0240: Too many participants.
- POL0242: Maximum duration exceeded.

## 8.1.2 Operation: getConferenceInfo

The invocation of **getConferenceInfo** requests the information concerning the current status of the multi-media conference call identified by **callSessionIdentifier**.

#### 8.1.2.1 Input message: getConferenceInfoRequest

Part name	Part type Opti	ional	Description
CallSessionIdentifier	xsd:stringNo	(	Call session identifier; the Conference identifier

#### 8.1.2.2 Output message: getConferenceInfoResponse

Part name	Part type	Optional	Description
result	ConferenceInfo	No	Status of the conference

#### 8.1.2.3 Referenced faults

Service Exception from 3GPP TS 29.199-1 [6]:

- SVC0001: Service error.
- SVC0002: Invalid input value.

PolicyException from 3GPP TS 29.199-1 [6]:

• POL0001: Policy error.

#### 8.1.3 Operation: endConference

The invocation of **endConference** requests to terminate the multi-media conference call identified by **callSessionIdentifier**.

#### 8.1.3.1 Input message: endConferenceRequest

Part name	Part type Optional	Description
CallSessionIdentifier	xsd:stringNo	Call session identifier; the Conference identifier

#### 8.1.3.2 Output message: endConferenceResponse

Part name	Part type	Optional	Description
None			

#### 8.1.3.3 Referenced faults

Service Exception from 3GPP TS 29.199-1 [6]:

- SVC0001: Service error.
- SVC0002: Invalid input value.

PolicyException from 3GPP TS 29.199-1 [6]:

• POL0001: Policy error.

#### 8.1.4 Operation: inviteParticipant

The invocation of **inviteParticipant** requests to add a new participant specified by **participant** to the multi-media conference call identified by **callSessionIdentifier**. The media used for the initial connection of the new participant depends on the conference type and the participant's supported media.

The operation will fail if the conference has already reached the maximum number of participants (as specified in the creation operation).

#### 8.1.4.1 Input message: inviteParticipantRequest

Part name	Part type	Optional	Description
CallSessionIdentifier	xsd:string	No	Call session identifier; the Conference identifier
Participant	xsd:anyUR	No	New participant invited

#### 8.1.4.2 Output message: inviteParticipantResponse

Part name	Part type	Optional	Description
None			

#### 8.1.4.3 Referenced faults

Service Exception from 3GPP TS 29.199-1 [6]:

• SVC0001: Service error.

• SVC0002: Invalid input value.

PolicyException from 3GPP TS 29.199-1 [6]:

• POL0001: Policy error.

• POL0240: Too many participants.

#### 8.1.5 Operation: disconnectParticipant

The invocation of **disconnectParticipant** requests to disconnect the participant specified by **participant** from the multi-media conference call identified by **callSessionIdentifier**.

#### 8.1.5.1 Input message: disconnectParticipantRequest

Part name	Part type	Optional	Description
CallSessionIdentifier	xsd:string	No	Call session identifier; the Conference identifier
Participant	xsd:anyURI	No	Participant

#### 8.1.5.2 Output message: disconnectParticipantResponse

Part name	Part type	Optional	Description
None			

#### 8.1.5.3 Referenced faults

Service Exception from 3GPP TS 29.199-1 [6]:

- SVC0001: Service error.
- SVC0002: Invalid input value.

PolicyException from 3GPP TS 29.199-1 [6]:

• POL0001: Policy error.

#### 8.1.6 Operation: getParticipantInfo

The invocation of **getPartici pantInfo** requests information concerning the current status of the participant specified by **partici pant**, in the multi-media conference call identified by **callSessionIdentifier**.

#### 8.1.6.1 Input message: getParticipantInfoRequest

Part name	Part type	Optional	Description
CalSessionIdentifier	xsd:string	No	Call session identifier; the Conference identifier
Participant	xsd:anyURI	No	Participant

#### 8.1.6.2 Output message: getParticipantInfoResponse

Part name	Part type	Optional	Description
result	ParticipantInfo	No	Status of the participant

#### 8.1.6.3 Referenced faults

Service Exception from 3GPP TS 29.199-1 [6]:

- SVC0001: Service error.
- SVC0002: Invalid input value.

PolicyException from 3GPP TS 29.199-1 [6]:

• POL0001: Policy error.

## 8.1.7 Operation: getParticipants

The invocation of **getPartici pants** requests information concerning the current status of each participant of the multimed is conference call identified by **callSessionIdentifier**. The output includes participants already disconnected from the conference (if any).

#### 8.1.7.1 Input message: getParticipantsRequest

Part name	Part type Optional	Description
CallSessionIdentifie	xsd:stringNo	Call session identifier; the Conference identifier

#### 8.1.7.2 Output message: getParticipantsResponse

Part name	Part type	Optional	Description
result	ParticipantInfo [0unbounded]	Yes	Array containing status information for each participant

#### 8.1.7.3 Referenced faults

Service Exception from 3GPP TS 29.199-1 [6]:

- SVC0001: Service error.
- SVC0002: Invalid input value.

PolicyException from 3GPP TS 29.199-1 [6]:

- POL0001: Policy error.
- 8.1.8 Void
- 8.1.9 Void

## 9 Fault definitions

## 9.1 PolicyException

## 9.1.1 POL0240: Too many participants

Too many participants.

Name	Description
Message Id	
	Too many participants
Variables	None

#### 9.1.2 Void

The fault code (POL0241) is reserved and shall not be used.

#### 9.1.3 POL0242: Maximum duration exceeded

Name	Description
Message Id	POL0242
Text	Maximum duration exceeded. Maximum allowed is %1 seconds.
Variables	%1 – maximum duration set by service policy

## 9.2 ServiceException

#### 9.2.1 Void

The fault code (SVC0210) is reserved and shall not be used.

#### 9.2.2 Void

The fault code (SVC0211) is reserved and shall not be used.

## 10 Service policies

Name	Туре	Description
Ma xim um Duration		Maximum duration for which a conference may be set up.
Maximum Participants	xsd:int	Maximum number of participants for which a conference may be set up.
ChargingSupported		Indicates whether charging is supported for the createConference operation
Ma xim um Des criptions	xsd:int	Maximum number of Descriptions that can be charged simultaneously

# Annex A (normative): WSDL for Multimedia conference

The document/literal WSDL representation of this interface specification is compliant to 3GPP TS 29.199-1 [6] and is contained in text files

- parlay x\_multimed ia\_conference\_interface\_4\_0.wsdl
- parlay x\_multimed ia\_conference\_service\_4\_0.wsdl
- parlay x\_multimedia\_conference\_types\_4\_0.xsd which accompanies the present document.

The WSDL files have been verified using the following files:

- 12\_wsdl2Java\_axis-1\_4.bat
- 12\_wsdl2Java\_axis2-1\_4\_1.bat which accompany the present document.

## Annex B (informative):

## Description of Parlay X Web Services Part 12: Multimedia conference for 3GPP2 cdma2000 networks

This annex is intended to define the OSA Parlay X Web Services Stage 3 interface definitions and it provides the complete OSA specifications. It is an extension of OSA Parlay X Web Services specifications capabilities to enable operation in cdma 2000 systems environment. They are in alignment with 3GPP2 Stage 1 requirements and Stage 2 architecture defined in:

- [1] 3GPP2 X.S0011-D: "cdma 2000 Wireless IP Network Standard", Version 1.1
- [2] 3GPP2 S.R0037-0: "IP Network Architecture Model for cd ma2000 Spread Spectrum Systems", Version 3.0
- [3] 3GPP2 X.S0013-A: "All-IP Core Network Multimedia Domain"

These requirements are expressed as additions to and/or exclusions from the 3GPP specification. The information given here is to be used by developers in 3GPP2 cd ma 2000 network architecture to interpret the 3GPP OSA specifications.

## B.1 General Exceptions

The terms 3GPP and UMTS are not applicable for the cdma 2000 family of standards. Nevertheless these terms are used (3GPP TR 21.905) mostly in the broader sense of "3G Wireless System". If not stated otherwise there are no additions or exclusions required.

CAMEL mappings are not applicable for cd ma 2000 systems.

## B.2 Specific Exceptions

### B.2.1 Clause 1: Scope

There are no additions or exclusions.

#### B.2.2 Clause 2: References

There are no additions or exclusions.

#### B.2.3 Clause 3: Definitions and abbreviations

There are no additions or exclusions.

## B.2.4 Clause 4: Detailed service description

There are no additions or exclusions.

## B.2.5 Clause 5: Namespaces

There are no additions or exclusions.

## B.2.6 Clause 6: Sequence diagrams

There are no additions or exclusions.

#### B.2.7 Clause 7: XML Schema data type definition

There are no additions or exclusions.

#### B.2.8 Clause 8: Web Service interface definition

There are no additions or exclusions.

#### B.2.9 Clause 9: Fault definitions

There are no additions or exclusions.

#### B.2.10 Clause 10: Service policies

There are no additions or exclusions.

## B.2.11 Annex A (normative): WSDL for Multimedia conference

There are no additions or exclusions.

# Annex C (informative): Change history

Change history								
Date	TSG#	TSG Doc.	CR	Rev	Subject/Comment	Cat	Old	New
Sep 2004	CN_25	NP-040360			Draft v100 submitted to TSG CN#25 for Approval.		1.0.0	6.0.0
Jun 2005	CT_28	CP-050221	0001		Optionals for Part 12	F	6.0.0	6.1.0
Dec 2005	CT_30	CP-050577	0002		Inconsistent part naming in PX response messages	F	6.1.0	6.2.0
Jun 2006	CT_32	CP-060195	0003		Change reference to OSA Stage 2 from 23.127 to 23.198	F	6.2.0	6.3.0
Dec 2006	CT_34	CP-060593	0004		Add missing ServiceExceptions to Multimedia Conference Web Service	F	6.3.0	6.4.0
Dec 2006	CT_34	CP-060593	0005		Correct the ParticipantInfo structure of Multimedia Conference Web Service	F	6.3.0	6.4.0
Mar 2007	CT_35	CP-070045	0006		Add OSA Parlay Web Services support for 3GPP2 networks	F	6.4.0	6.5.0
Mar 2007	CT_35	CP-070045	0007		Corrections to namespace version numbers	F	6.4.0	6.5.0
Mar 2007	CT_35	CP-070048	0008		Move support for add/delete media out of Multimedia conference	С	6.5.0	7.0.0
Mar 2007					Editorial: Aligned 5 Namespaces		7.0.0	7.0.1
Jun 2007					Renamed in Introduction Part 18: "Device management" to "Device		7.0.1	7.0.2
					Capabilities and Configuration"			
Sep 2007	CT_37	CP-070640	0010		Replace ConferenceIdentifier with CallSessionIdentifier	F	7.0.2	7.1.0
Dec 2007					Word file and code attachment provided by PTCC. The code change		7.1.0	7.1.1
					required a change to the namespace in the Word TS.			
Dec 2008	CT_42				Upgraded unchanged from Rel-7		7.1.1	8.0.0
Sep 2009	CT_45	CP-090600	0011		Completion of Parlay X Part 12 (Multimedia conference) for	F	8.0.0	8.1.0
					Release 8			
2009-12	-	-	-	-	Update to Rel-9 version (MCC)		8.1.0	9.0.0