

**3rd Generation Partnership Project;
Technical Specification Group Services and System Aspects;
Telecommunication management;
Configuration Management (CM);
Notification Integration Reference Point (IRP);
SOAP Solution Set (SS)
(Release 9)**



Keywords

UMTS, management, SOAP

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis

Valbonne - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2011, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TTA, TTC).
All rights reserved.

UMTSTM is a Trade Mark of ETSI registered for the benefit of its members

3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners

LTE™ is a Trade Mark of ETSI currently being registered for the benefit of its Members and of the 3GPP Organizational Partners

GSM® and the GSM logo are registered and owned by the GSM Association

Contents

Foreword	5
Introduction	5
1 Scope	7
2 References.....	7
3 Definitions and abbreviations	8
3.1 Definitions	8
3.2 Abbreviations.....	8
4 Architectural features.....	8
5 Mapping	10
5.1 Operation mapping	10
5.2 Filter language.....	10
5.3 Common datatype definition	10
5.3.1 NotificationCategorySetType	10
5.3.2 SubscriptionStateType	10
5.4 Operation parameter mapping	11
5.4.1 Operation subscribe	11
5.4.1.1 Input parameters.....	11
5.4.1.2 Output parameters.....	11
5.4.1.3 Fault definition	11
5.4.2 Operation unsubscribe	12
5.4.2.1 Input parameters.....	12
5.4.2.2 Output parameters.....	12
5.4.2.3 Fault definition	12
5.4.3 Operation getSubscriptionIds.....	13
5.4.3.1 Input parameters.....	13
5.4.3.2 Output parameters.....	13
5.4.3.3 Fault definition	13
5.4.4 Operation getSubscriptionStatus	14
5.4.4.1 Input parameters.....	14
5.4.4.2 Output parameters.....	14
5.4.4.3 Fault definition	14
5.4.5 Operation changeSubscriptionFilter	15
5.4.5.1 Input parameters.....	15
5.4.5.2 Output parameters.....	15
5.4.5.3 Fault definition	15
5.4.6 Operation suspendSubscription	15
5.4.6.1 Input parameters.....	15
5.4.6.2 Output parameters.....	16
5.4.6.3 Fault definition	16
5.4.7 Operation resumeSubscription	16
5.4.7.1 Input parameters.....	16
5.4.7.2 Output parameters.....	16
5.4.7.3 Fault definition	17
5.4.8 Operation getNotificationCategories	17
5.4.8.1 Input parameters.....	17
5.4.8.2 Output parameters.....	17
5.4.8.3 Fault definition	17
5.5 Parameter mapping	17
5.6 NotificationIRPNotification Interface definition	18
5.6.1 Input parameters	18
5.6.2 Output parameters	18
6 IRPAgent's Behaviour	18
6.1 Subscription.....	18

Annex A (normative):	WSDL specifications.....	19
Annex B (normative):	Notification WSDL specifications	27
Annex C (informative):	Void.....	28
Annex D (informative):	Change history.....	29

Foreword

This Technical Specification (TS) has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

- 32.301: Configuration Management (CM); Notification Integration Reference Point (IRP); Requirements
- 32.302: Configuration Management (CM); Notification Integration Reference Point (IRP); Information Service (IS)
- 32.303: Configuration Management (CM); Notification Integration Reference Point (IRP); Common Object Request Broker Architecture (CORBA) Solution Set (SS)
- 32.305: Configuration Management (CM); Notification Integration Reference Point (IRP); eXtensible Markup Language (XML) definition
- 32.307: Configuration Management (CM); Notification Integration Reference Point (IRP); SOAP Solution Set**

Configuration Management (CM), in general, provides the operator with the ability to assure correct and effective operation of the 3G network as it evolves. CM actions have the objective to control and monitor the actual configuration on the Network Elements (NEs) and Network Resources (NRs), and they may be initiated by the operator or by functions in the Operations Systems (OSs) or NEs.

CM actions may be requested as part of an implementation programme (e.g. additions and deletions), as part of an optimisation programme (e.g. modifications), and to maintain the overall Quality of Service (QoS). The CM actions are initiated either as a single action on a NE of the 3G network or as part of a complex procedure involving actions on many NEs.

The Ifc-N interface is built up by a number of Integration Reference Points (IRPs) and a related Name Convention, which realise the functional capabilities over this interface. The basic structure of the IRPs is defined in 3GPP TS 32.101 [6] and 3GPP TS 32.102 [7].

Network Elements (NEs) under management and element managers generate notifications of events about occurrences within the network. Different kinds of events carry different kinds of information. For instance a new alarm as specified in 3GPP TS 32.111-2 Alarm IRP: Information Service [5], is one possible kind of event, an object creation as specified in 3GPP TS 32.602 Basic CM IRP: Information Service [15] is another possible kind of event.

Information of an event is carried in notification. An IRP Agent (typically an EM or a NE) emits notifications. IRP Manager (typically a network management system) receives notifications. The purpose of Notification IRP is to define an interface through which an IRP Manager can subscribe to IRP Agents for receiving notifications.

This IRP bases its design on work captured in ITU-T Recommendation X.734 [2], The central design ideas are:

- Separation of notification Consumers (IRP Managers) from Producers (IRP Agents);
- Notifications are sent to IRP Managers without the need for IRP Managers to periodically check for new notifications.

Common characteristics related to notifications in all other IRPs are gathered in one IRP.

1 Scope

The present document specifies the SOAP Solution Set for the IRP whose semantics is specified in Notification IRP: Information Service (3GPP TS 32.302 [4]).

This Solution Set specification is related to 3GPP TS 32.302 V9.0.X.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] ITU-T Recommendation X.736: "Information technology - Open Systems Interconnection - Systems Management: Security alarm reporting function".
- [2] ITU-T Recommendation X.734 (1992): "Information technology - Open Systems Interconnection - Systems management: Event report management function".
- [3] 3GPP TS 32.312: "Telecommunication management; Generic Integration Reference Point (IRP) management; Information Service (IS)".
- [4] 3GPP TS 32.302: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP): Information Service (IS)".
- [5] 3GPP TS 32.111-2: "Telecommunication management; Fault Management; Part 2: Alarm Integration Reference Point (IRP): Information Service (IS)".
- [6] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [7] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [8] 3GPP TS 32.301: "Telecommunication Management; Configuration Management (CM); Notification Integration Reference Point (IRP): Requirements".
- [9] 3GPP TS 32.317: "Telecommunication management; Generic Integration Reference Point (IRP) management; SOAP solution set".
- [10] 3GPP TS 32.311: "Telecommunication management; Generic Integration Reference Point (IRP) management; Requirements".
- [11] 3GPP TS 32.172: "Telecommunication management; Subscription Management (SuM) Network Resource Model (NRM) Integration Reference Point (IRP): Information Service".
- [12] W3C SOAP 1.1 specification (<http://www.w3.org/TR/2000/NOTE-SOAP-20000508/>)
- [13] W3C XPath 1.0 specification (<http://www.w3.org/TR/1999/REC-xpath-19991116>)
- [14] W3C WSDL 1.1 specification (<http://www.w3.org/TR/2001/NOTE-wsdl-20010315>)
- [15] 3GPP TS 32.602: "Telecommunication management; Configuration Management (CM); Basic CM Integration Reference Point (IRP): Information Service (IS)".

- [16] 3GPP TS 32.305: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP): eXtensible Markup Language (XML) definition".
 - [17] WS-I Basic Profile Version 1.1 (<http://www.ws-i.org/Profiles/BasicProfile-1.1-2004-08-24.html>)
 - [18] W3C SOAP 1.2 specification (<http://www.w3.org/TR/soap12-part1/>)
-

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TS 32.101 [6], 3GPP TS 32.102 [7] and 3GPP TS 32.301 [8] and the following apply:

IRP document version number string (or "IRPVersion"): See 3GPP TS 32.311 [10].

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CM	Configuration Management
EM	Element Manager
IS	Information Service
NE	Network Element
NV	Name and Value pair
QoS	Quality of Service
SS	Solution Set
WSDL	Web Service Description Language
WS-I	Web Services Interoperability Organization

4 Architectural features

The overall architectural feature of Notification IRP is specified in 3GPP TS 32.302 [4]. This clause specifies features that are specific to the SOAP solution set.

The SOAP 1.1 specification [12] and WSDL 1.1 specification [14] are supported.

The SOAP 1.2 specification [18] is supported optionally.

This specification uses "document" style in WSDL file.

This specification uses "literal" encoding style in WSDL file.

The IRP Agent shall support the push interface model that means IRP Agent sends notifications to IRP Manager as soon as new events occur. IRP Manager does not need to check ("pull") for events.



The "Notification" definition is imported from Notification IRP XML Definition [16].

This specification uses a number of namespace prefixes throughout that are listed in Table 4.1.

Table 4.1: Prefixes and Namespaces used in this specification

PREFIX	NAMESPACE
http	http://schemas.xmlsoap.org/wsdl/http/
soap	http://schemas.xmlsoap.org/wsdl/soap/
SOAP-ENV	http://schemas.xmlsoap.org/soap/envelope/
SOAP-ENC or soapenc	http://schemas.xmlsoap.org/soap/encoding/
xs or xsd	http://www.w3.org/2001/XMLSchema
xsi	http://www.w3.org/2001/XMLSchema-instance
ntfIRPSystem	http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-810/NotificationIRPSystem
ntfIRPData	http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-810/NotificationIRPData
ntfIRPNtfSystem	http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-810/notification/NotificationIRPNtfSystem
ntfIRPNtfData	http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-810/notification/NotificationIRPNtfData
genericIRPSystem	http://www.3gpp.org/ftp/Specs/archive/32_series/32.317/schema/32317-810/GenericIRPSystem

The WSDL structure is like Figure 4.1:

**Figure 4.1: Notification IRP SOAP Solution Set WSDL structure****Figure 4.2: Notification IRP SOAP Solution Set Notification WSDL structure**

5 Mapping

5.1 Operation mapping

Notification IRP: IS (3GPP TS 32.302 [5]) defines semantics of operations visible across this IRP. These operations are the operations of the IOCs defined in 3GPP TS 32.302 [5].

Table 5.1 maps the operations defined in Notification IRP: IS (3GPP TS 32.302 [5]) to their equivalents (methods) in this Solution Set (SS). Specifically, the table 5.1 maps the operations of the IOCs defined in 3GPP TS 32.302 [5] to their equivalents in this SS. Since one of the IOCs, the `NotificationIRP` IOC, inherits from the `ManagedGenericIRP` IOC [4], the table 5.1 also maps the operations of `ManagedGenericIRP` IOC to their equivalents (methods) in this SS.

Table 5.1 also qualifies if a method is Mandatory (M) or Optional (O).

Table 5.1: Mapping from IS Operation to SS Equivalents

IS Operations in 3GPP TS 32.302 [5]	SS Operations	Qualifier
<code>subscribe</code>	<code>subscribe</code>	M
<code>unsubscribe</code>	<code>unsubscribe</code>	M
<code>getSubscriptionIds</code>	<code>getSubscriptionIds</code>	O
<code>getSubscriptionStatus</code>	<code>getSubscriptionStatus</code>	O
<code>changeSubscriptionFilter</code>	<code>changeSubscriptionFilter</code>	O
<code>suspendSubscription</code>	<code>suspendSubscription</code>	O
<code>resumeSubscription</code>	<code>resumeSubscription</code>	O
<code>getNotificationCategories</code>	<code>getNotificationCategories</code>	O
<code>getIRPVersion</code> (see note.)	<code>getIRPVersion</code>	M
<code>getOperationProfile</code> (see note.)	<code>getOperationProfile</code>	O
<code>getNotificationProfile</code> (see note.)	<code>getNotificationProfile</code>	O

NOTE: These 3 operations are operations of `ManagedGenericIRP` IOC specified in 3GPP TS 32.312 [4]. The `NotificationIRP` IOC of 3GPP TS 32.302 [5] inherits from it.

5.2 Filter language

The filter language used in the SS is the XPath Language (see W3C XPath 1.0 specification [13]). IRP Agents may throw a `FilterComplexityLimit` fault when a given filter is too complex.

5.3 Common datatype definition

5.3.1 NotificationCategorySetType

```
<complexType name="NotificationCategorySetType">
<complexContent>
<extension base="ntfIRPData:VersionNumberSetType">
  </extension>
</complexContent>
</complexType>
```

5.3.2 SubscriptionStateType

```
<simpleType name="SubscriptionStateType">
<restriction base="string">
  <enumeration value="Suspended"/>
  <enumeration value="NotSuspended"/>
</restriction>
</simpleType>
```

5.4 Operation parameter mapping

3GPP TS 32.302 [5] defines semantics of parameters carried in operations across the Notification IRP. The tables below show the mapping of these parameters, as per operation, to their equivalents defined in this SS.

5.4.1 Operation subscribe

5.4.1.1 Input parameters

Table 5.4.1.1: Mapping from IS subscribe input parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
managerReference	anyURI managerReference	M
timeTick	long timeTick	O
notificationCategories	ntfIRPData:NotificationCategorySetType notificationCategories	O
filter	string filter (see note 1)	O
	anyURI ntfTransServiceNS (see note 2)	M

NOTE1: The grammar of the filter string is XPath defined by W3C XPath 1.0 specification [12].

NOTE2: This parameter is used to specify the name space of the Web Notification Transmission Service that will be used for sending notification.
The "http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-810/notification" URI should be supported.

Here is the XML schema fragment of the subscribe request:

```
<!-- subscribe Request -->
<element name="subscribe">
<complexType>
<sequence>
<element name="managerReference" type="anyURI"/>
<element name="timeTick" type="long" minOccurs="0"/>
<element name="notificationCategories" type="ntfIRPData:NotificationCategorySetType"
minOccurs="0"/>
<element name="filter" type="string" minOccurs="0"/>
<element name="ntfTransServiceNS" type="anyURI"/>
</sequence>
</complexType>
</element>
```

5.4.1.2 Output parameters

Table 5.4.1.2: Mapping from IS subscribe output parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
subscriptionId	string subscriptionId	M
status	ntfIRPData:subscribeFault	M

Here is the XML schema fragment of the subscribe response:

```
<!-- subscribe Response -->
<element name="subscribeResponse">
<complexType>
<sequence>
<element name="subscriptionId" type="string"/>
</sequence>
</complexType>
</element>
```

5.4.1.3 Fault definition

```
<!-- subscribe Fault -->
<element name="subscribeFault">
<complexType>
```

```

<choice>
  <element name="AlreadySubscribedFault" type="string"/>
  <element name="AtLeastOneNotificationCategoryNotSupportedFault" type="string"/>
  <element name="subscribeFault" type="string"/>
  <element ref="ntfIRPData:InvalidParameterFault"/>
</choice>
</complexType>
</element>

```

5.4.2 Operation unsubscribe

5.4.2.1 Input parameters

Table 5.4.2.1: Mapping from IS unsubscribe input parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
managerReference	anyURI managerReference	M
subscriptionId	string subscriptionId	O

Here is the XML schema fragment of the unsubscribe request:

```

<!-- unsubscribe Request -->
<element name="unsubscribe">
<complexType>
<sequence>
  <element name="managerReference" type="anyURI"/>
  <element name="subscriptionId" type="string" minOccurs="0"/>
</sequence>
</complexType>
</element>

```

5.4.2.2 Output parameters

Table 5.4.2.2: Mapping from IS unsubscribe output parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
Status	ntfIRPData:unsubscribeFault	M

Here is the XML schema fragment of the unsubscribe response:

```

<!-- unsubscribe Response -->
<element name="unsubscribeResponse">
</element>

```

5.4.2.3 Fault definition

```

<!-- unsubscribe Fault -->
<element name="unsubscribeFault">
<complexType>
<choice>
  <element name="unsubscribeFault" type="string"/>
  <element ref="ntfIRPData:InvalidParameterFault"/>
</choice>
</complexType>
</element>

```

5.4.3 Operation getSubscriptionIds

5.4.3.1 Input parameters

Table 5.4.3.1: Mapping from IS getSubscriptionIds input parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
managerReference	anyURI managerReference	M

Here is the XML schema fragment of the getSubscriptionIds request:

```
<!-- getSubscriptionIds Request -->
<element name="getSubscriptionIds">
<complexType>
<sequence>
<element name="managerReference" type="anyURI"/>
</sequence>
</complexType>
</element>
```

5.4.3.2 Output parameters

Table 5.4.3.2: Mapping from IS getSubscriptionIds output parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
subscriptionIdSet	sequence of string subscriptionIdSet	M
status	ntfIRPData:getSubscriptionIdsFault	M

Here is the XML schema fragment of the getSubscriptionIds response:

```
<!-- getSubscriptionIds Response -->
<element name="getSubscriptionIdsResponse">
<complexType>
<sequence>
<element name="subscriptionIdSet">
<complexType>
<sequence>
<element name="subscriptionId" type="string" maxOccurs="unbounded"/>
</sequence>
</complexType>
</element>
</sequence>
</complexType>
</element>
```

5.4.3.3 Fault definition

```
<!-- getSubscriptionIds Fault -->
<element name="getSubscriptionIdsFault">
<complexType>
<choice>
<element name="getSubscriptionIdsFault" type="string"/>
<element ref="ntfIRPData:OperationNotSupportedFault"/>
<element ref="ntfIRPData:InvalidParameterFault"/>
</choice>
</complexType>
</element>
```

5.4.4 Operation getSubscriptionStatus

5.4.4.1 Input parameters

Table 5.4.4.1: Mapping from IS getSubscriptionStatus input parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
subscriptionId	string subscriptionId	M

Here is the XML schema fragment of the getSubscriptionStatus request:

```
<!-- getSubscriptionStatus Request -->
<element name="getSubscriptionStatus">
  <complexType>
    <sequence>
      <element name="subscriptionId" type="string"/>
    </sequence>
  </complexType>
</element>
```

5.4.4.2 Output parameters

Table 5.4.4.2: Mapping from IS getSubscriptionStatus output parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
notificationCategories	ntfIRPData:NotificationCategorySetType notificationCategories	C
filterInEffect	string filterInEffect (see note)	O
SubscriptionState	ntfIRPData:SubscriptionStateType SubscriptionState	O
timeTick	long timeTick	O
status	ntfIRPData:getSubscriptionStatusFault	M

NOTE: The grammar of the filter string is XPath defined by W3C XPath 1.0 specification [12].

Here is the XML schema fragment of the getSubscriptionStatus response:

```
<!-- getSubscriptionStatus Response -->
<element name="getSubscriptionStatusResponse">
  <complexType>
    <sequence>
      <element name="notificationCategories" type="ntfIRPData:NotificationCategorySetType"
minOccurs="0"/>
      <element name="filterInEffect" type="string" minOccurs="0"/>
      <element name="SubscriptionState" type="ntfIRPData:SubscriptionStateType"
minOccurs="0"/>
      <element name="timeTick" type="long" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
```

5.4.4.3 Fault definition

```
<!-- getSubscriptionStatus Fault -->
<element name="getSubscriptionStatusFault">
  <complexType>
    <choice>
      <element name="getSubscriptionStatusFault" type="string"/>
      <element ref="ntfIRPData:OperationNotSupportedFault"/>
      <element ref="ntfIRPData:InvalidParameterFault"/>
    </choice>
  </complexType>
</element>
```

5.4.5 Operation changeSubscriptionFilter

5.4.5.1 Input parameters

Table 5.4.5.1: Mapping from IS changeSubscriptionFilter input parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
subscriptionId	string subscriptionId	M
filter	string filter (see note)	O

NOTE: The grammar of the filter string is XPath defined by W3C XPath 1.0 specification [12].

Here is the XML schema fragment of the changeSubscriptionFilter request:

```
<!-- changeSubscriptionFilter Request -->
<element name="changeSubscriptionFilter">
<complexType>
<sequence>
    <element name="subscriptionId" type="string"/>
    <element name="filter" type="string" minOccurs="0"/>
</sequence>
</complexType>
</element>
```

5.4.5.2 Output parameters

Table 5.4.5.2: Mapping from IS changeSubscriptionFilter output parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
status	ntfIRPData:changeSubscriptionFilterFault	M

Here is the XML schema fragment of the changeSubscriptionFilter response:

```
<!-- changeSubscriptionFilter Response -->
<element name="changeSubscriptionFilterResponse">
</element>
```

5.4.5.3 Fault definition

```
<!-- changeSubscriptionFilter Fault -->
<element name="changeSubscriptionFilterFault">
<complexType>
<choice>
    <element name="changeSubscriptionFilterFault" type="string"/>
    <element ref="ntfIRPData:OperationNotSupportedFault"/>
    <element ref="ntfIRPData:InvalidParameterFault"/>
</choice>
</complexType>
</element>
```

5.4.6 Operation suspendSubscription

5.4.6.1 Input parameters

Table 5.4.6.1: Mapping from IS suspendSubscription input parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
subscriptionId	string subscriptionId	M

Here is the XML schema fragment of the suspendSubscription request:

```
<!-- suspendSubscription Request -->
<element name="suspendSubscription">
```

```

<complexType>
  <sequence>
    <element name="subscriptionId" type="string"/>
  </sequence>
</complexType>
</element>

```

5.4.6.2 Output parameters

Table 5.4.6.2: Mapping from IS suspendSubscription output parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
status	ntfIRPData:suspendSubscriptionFault	M

Here is the XML schema fragment of the suspendSubscription response:

```

<!-- suspendSubscription Response -->
<element name="suspendSubscriptionResponse">
</element>

```

5.4.6.3 Fault definition

```

<!-- suspendSubscription Fault -->
<element name="suspendSubscriptionFault">
  <complexType>
    <choice>
      <element name="suspendSubscriptionFault" type="string"/>
      <element ref="ntfIRPData:OperationNotSupportedFault"/>
      <element ref="ntfIRPData:InvalidParameterFault"/>
    </choice>
  </complexType>
</element>

```

5.4.7 Operation resumeSubscription

5.4.7.1 Input parameters

Table 5.4.7.1: Mapping from IS resumeSubscription input parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
subscriptionId	string subscriptionId	M

Here is the XML schema fragment of the resumeSubscription request:

```

<!-- resumeSubscription Request -->
<element name="resumeSubscription">
  <complexType>
    <sequence>
      <element name="subscriptionId" type="string"/>
    </sequence>
  </complexType>
</element>

```

5.4.7.2 Output parameters

Table 5.4.7.2: Mapping from IS resumeSubscription output parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
status	ntfIRPData:resumeSubscriptionFault	M

Here is the XML schema fragment of the resumeSubscription response:

```

<!-- resumeSubscription Response -->

```

```
<element name="resumeSubscriptionResponse">
</element>
```

5.4.7.3 Fault definition

```
<!-- resumeSubscription Fault -->
<element name="resumeSubscriptionFault">
  <complexType>
    <choice>
      <element name="resumeSubscriptionFault" type="string"/>
      <element ref="ntfIRPData:OperationNotSupportedFault"/>
      <element ref="ntfIRPData:InvalidParameterFault"/>
    </choice>
  </complexType>
</element>
```

5.4.8 Operation getNotificationCategories

5.4.8.1 Input parameters

None.

Here is the XML schema fragment of the getNotificationCategories request:

```
<!-- getNotificationCategories Request -->
<element name="getNotificationCategories">
</element>
```

5.4.8.2 Output parameters

Table 5.4.8.2: Mapping from IS getNotificationCategories output parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
NotificationCategoryList	ntfIRPData:NotificationCategorySetType	M
status	ntfIRPData:getNotificationCategories Fault	M

Here is the XML schema fragment of the getNotificationCategories response:

```
<!-- getNotificationCategories Response -->
<element name="getNotificationCategoriesResponse">
  <complexType>
    <sequence>
      <element name="NotificationCategoryList" type="ntfIRPData:NotificationCategorySetType"/>
    </sequence>
  </complexType>
</element>
```

5.4.8.3 Fault definition

```
<!-- getNotificationCategories Fault -->
<element name="getNotificationCategoriesFault">
  <complexType>
    <choice>
      <element name="getNotificationCategoriesFault" type="string"/>
      <element ref="ntfIRPData:OperationNotSupportedFault"/>
    </choice>
  </complexType>
</element>
```

5.5 Parameter mapping

Notification IRP: IS (3GPP TS 32.302 [5]) defines the semantics of common attributes carried in notifications. This SS does not provide the mapping of these attributes to their SOAP SS equivalents. Other IRPs such as Alarm IRP:

IS (3GPP TS 32.111-2 [6]) identify and qualify these common attributes for use in their environment. Their corresponding SS documents define the mapping of these attributes to their SS equivalents.

5.6 NotificationIRPNotification Interface definition

The operation name is defined as “notify”.

5.6.1 Input parameters

Table 5.6.1: notify input parameters

IS Operation parameter	SS Method parameter	Qualifier
-	xe:Notification notification	M

The notifications of the various IRPs extend the input parameter above.

Here is the XML schema fragment of the notify request:

```
<!-- notify Request -->
<element name="notify">
  <complexType>
    <sequence>
      <element name="notificationHeaderAndBody"
type="ntfIRPntfData:AnySequenceType"/>
    </sequence>
  </complexType>
</element>
<complexType name="AnySequenceType">
  <sequence>
    <any namespace="##any" processContents="lax" maxOccurs="unbounded"/>
  </sequence>
</complexType>
```

5.6.2 Output parameters

None.

6 IRP Agent's Behaviour

This clause describes some IRP Agent's behaviour not captured by WSDL.

6.1 Subscription

IRPManager can invoke multiple subscribe operation using different managerReference(s). As far as IRP Agent is concerned, the IRP Agent will emit notifications to multiple "places" with their independent filter requirements. IRP Agent will not know if the notifications are going to the same IRPManager.

If IRPManager invokes multiple subscribe using the same managerReference and with an already subscribed notificationCategory, IRP Agent shall raise AlreadySubscribedFault fault to all invocations except one.

IRPManager can invoke multiple subscribe using the same managerReference and with one or more not-yet-subscribed notificationCategories. In this case, if IRP Agent supports all the notification categories requested, IRP Agent shall accept the invocation; otherwise, it raises AtLeastOneNotificationCategoryNotSupportedFault fault.

Annex A (normative): WSDL specifications

```

<?xml version="1.0" encoding="UTF-8"?>
<definitions xmlns="http://schemas.xmlsoap.org/wsdl/"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
  xmlns:http="http://schemas.xmlsoap.org/wsdl/http/" xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:genericIRPSys="http://www.3gpp.org/ftp/Specs/archive/32_series/32.317/schema/32317-
  810/GenericIRPSys"
  xmlns:ntfIRPSys="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-
  810/NotificationIRPSys"
  xmlns:ntfIRPData="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-
  810/NotificationIRPData"
  targetNamespace="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-
  810/NotificationIRPSys">
  <import namespace="http://www.3gpp.org/ftp/Specs/archive/32_series/32.317/schema/32317-
  810/GenericIRPSys" location="http://www.3gpp.org/ftp/Specs/archive/32_series/32.317/schema/32317-
  810-wsdl.zip"/>
  <types>
    <schema
      targetNamespace="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-
  810/NotificationIRPData" xmlns="http://www.w3.org/2001/XMLSchema">
        <!-- subscribe Request -->
        <element name="subscribe">
          <complexType>
            <sequence>
              <element name="managerReference" type="anyURI"/>
              <element name="timeTick" type="long" minOccurs="0"/>
              <element name="notificationCategories"
type="ntfIRPData:NotificationCategorySetType" minOccurs="0"/>
              <element name="filter" type="string" minOccurs="0"/>
              <element name="ntfTransServiceNS" type="anyURI"/>
            </sequence>
          </complexType>
        </element>
        <!-- subscribe Response -->
        <element name="subscribeResponse">
          <complexType>
            <sequence>
              <element name="subscriptionId" type="string"/>
            </sequence>
          </complexType>
        </element>
        <complexType name="NotificationCategorySetType">
          <complexContent>
            <extension base="ntfIRPData:VersionNumberSetType">
            </extension>
          </complexContent>
        </complexType>
        <!-- subscribe Fault -->
        <element name="subscribeFault">
          <complexType>
            <choice>
              <element name="AlreadySubscribedFault" type="string"/>
              <element name="AtLeastOneNotificationCategoryNotSupportedFault"
type="string"/>
              <element name="subscribeFault" type="string"/>
              <element ref="ntfIRPData:InvalidParameterFault"/>
            </choice>
          </complexType>
        </element>
        <!-- unsubscribe Request -->
        <element name="unsubscribe">
          <complexType>
            <sequence>
              <element name="managerReference" type="anyURI"/>
              <element name="subscriptionId" type="string" minOccurs="0"/>
            </sequence>
          </complexType>
        </element>
        <!-- unsubscribe Response -->
        <element name="unsubscribeResponse">
        </element>
    </schema>
  </import>
</definitions>

```

```
<!-- unsubscribe Fault -->
<element name="unsubscribeFault">
    <complexType>
        <choice>
            <element name="unsubscribeFault" type="string"/>
            <element ref="ntfIRPData:InvalidParameterFault"/>
        </choice>
    </complexType>
</element>
<!-- getSubscriptionIds Request -->
<element name="getSubscriptionIds">
    <complexType>
        <sequence>
            <element name="managerReference" type="anyURI"/>
        </sequence>
    </complexType>
</element>
<!-- getSubscriptionIds Response -->
<element name="getSubscriptionIdsResponse">
    <complexType>
        <sequence>
            <element name="subscriptionIdSet">
                <complexType>
                    <sequence>
                        <element name="subscriptionId" type="string"
maxOccurs="unbounded" />
                    </sequence>
                </complexType>
            </element>
        </sequence>
    </complexType>
</element>
<!-- getSubscriptionIds Fault -->
<element name="getSubscriptionIdsFault">
    <complexType>
        <choice>
            <element name="getSubscriptionIdsFault" type="string"/>
            <element ref="ntfIRPData:OperationNotSupportedFault"/>
            <element ref="ntfIRPData:InvalidParameterFault"/>
        </choice>
    </complexType>
</element>
<!-- getSubscriptionStatus Request -->
<element name="getSubscriptionStatus">
    <complexType>
        <sequence>
            <element name="subscriptionId" type="string"/>
        </sequence>
    </complexType>
</element>
<!-- getSubscriptionStatus Response -->
<element name="getSubscriptionStatusResponse">
    <complexType>
        <sequence>
            <element name="notificationCategories"
type="ntfIRPData:NotificationCategorySetType" minOccurs="0"/>
            <element name="filterInEffect" type="string" minOccurs="0"/>
            <element name="SubscriptionState" type="ntfIRPData:SubscriptionStateType"
minOccurs="0"/>
            <element name="timeTick" type="long" minOccurs="0"/>
        </sequence>
    </complexType>
</element>
<simpleType name="SubscriptionStateType">
    <restriction base="string">
        <enumeration value="Suspended"/>
        <enumeration value="NotSuspended"/>
    </restriction>
</simpleType>
<!-- getSubscriptionStatus Fault -->
<element name="getSubscriptionStatusFault">
    <complexType>
        <choice>
            <element name="getSubscriptionStatusFault" type="string"/>
            <element ref="ntfIRPData:OperationNotSupportedFault"/>
            <element ref="ntfIRPData:InvalidParameterFault"/>
        </choice>
    </complexType>
</element>
```

```
</element>
<!-- changeSubscriptionFilter Request -->
<element name="changeSubscriptionFilter">
    <complexType>
        <sequence>
            <element name="subscriptionId" type="string"/>
            <element name="filter" type="string" minOccurs="0"/>
        </sequence>
    </complexType>
</element>
<!-- changeSubscriptionFilter Response -->
<element name="changeSubscriptionFilterResponse">
</element>
<!-- changeSubscriptionFilter Fault -->
<element name="changeSubscriptionFilterFault">
    <complexType>
        <choice>
            <element name="changeSubscriptionFilterFault" type="string"/>
            <element ref="ntfIRPData:OperationNotSupportedFault"/>
            <element ref="ntfIRPData:InvalidParameterFault"/>
        </choice>
    </complexType>
</element>
<!-- suspendSubscription Request -->
<element name="suspendSubscription">
    <complexType>
        <sequence>
            <element name="subscriptionId" type="string"/>
        </sequence>
    </complexType>
</element>
<!-- suspendSubscription Response -->
<element name="suspendSubscriptionResponse">
</element>
<!-- suspendSubscription Fault -->
<element name="suspendSubscriptionFault">
    <complexType>
        <choice>
            <element name="suspendSubscriptionFault" type="string"/>
            <element ref="ntfIRPData:OperationNotSupportedFault"/>
            <element ref="ntfIRPData:InvalidParameterFault"/>
        </choice>
    </complexType>
</element>
<!-- resumeSubscription Request -->
<element name="resumeSubscription">
    <complexType>
        <sequence>
            <element name="subscriptionId" type="string"/>
        </sequence>
    </complexType>
</element>
<!-- resumeSubscription Response -->
<element name="resumeSubscriptionResponse">
</element>
<!-- resumeSubscription Fault -->
<element name="resumeSubscriptionFault">
    <complexType>
        <choice>
            <element name="resumeSubscriptionFault" type="string"/>
            <element ref="ntfIRPData:OperationNotSupportedFault"/>
            <element ref="ntfIRPData:InvalidParameterFault"/>
        </choice>
    </complexType>
</element>
<!-- getNotificationCategories Request -->
<element name="getNotificationCategories">
</element>
<!-- getNotificationCategories Response -->
<element name="getNotificationCategoriesResponse">
    <complexType>
        <sequence>
            <element name="NotificationCategoryList"
type="ntfIRPData:NotificationCategorySetType"/>
        </sequence>
    </complexType>
</element>
<!-- getNotificationCategories Fault -->
```

```

<element name="getNotificationCategoriesFault">
    <complexType>
        <choice>
            <element name="getNotificationCategoriesFault" type="string"/>
            <element ref="ntfIRPData:OperationNotSupportedFault"/>
        </choice>
    </complexType>
</element>

<element name="OperationNotSupportedFault" type="string"/>
<element name="InvalidParameterFault" type="string"/>
<simpleType name="VersionNumberType">
    <restriction base="string"/>
</simpleType>
<complexType name="VersionNumberSetType">
    <sequence>
        <element name="versionNumber" type="ntfIRPData:VersionNumberType"
maxOccurs="unbounded"/>
    </sequence>
</complexType>
<complexType name="ParameterSetType">
    <sequence>
        <element name="parameterName" type="string" maxOccurs="unbounded"/>
    </sequence>
</complexType>
<complexType name="OperationType">
    <sequence>
        <element name="operationName" type="string"/>
        <element name="parameterSet" type="ntfIRPData:ParameterSetType"/>
    </sequence>
</complexType>
<complexType name="OperationSetType">
    <sequence>
        <element name="operation" type="ntfIRPData:OperationType"
maxOccurs="unbounded"/>
    </sequence>
</complexType>
<complexType name="NotificationType">
    <sequence>
        <element name="notificationName" type="string"/>
        <element name="parameterSet" type="ntfIRPData:ParameterSetType"/>
    </sequence>
</complexType>
<complexType name="NotificationSetType">
    <sequence>
        <element name="notification" type="ntfIRPData:NotificationType"
maxOccurs="unbounded"/>
    </sequence>
</complexType>
</schema>
</types>
<message name="subscribeRequest">
    <part name="parameter" element="ntfIRPData:subscribe"/>
</message>
<message name="subscribeResponse">
    <part name="parameter" element="ntfIRPData:subscribeResponse"/>
</message>
<message name="subscribeFault">
    <part name="parameter" element="ntfIRPData:subscribeFault"/>
</message>
<message name="unsubscribeRequest">
    <part name="parameter" element="ntfIRPData:unsubscribe"/>
</message>
<message name="unsubscribeResponse">
    <part name="parameter" element="ntfIRPData:unsubscribeResponse"/>
</message>
<message name="unsubscribeFault">
    <part name="parameter" element="ntfIRPData:unsubscribeFault"/>
</message>
<message name="getSubscriptionIdsRequest">
    <part name="parameter" element="ntfIRPData:getSubscriptionIds"/>
</message>
<message name="getSubscriptionIdsResponse">
    <part name="parameter" element="ntfIRPData:getSubscriptionIdsResponse"/>
</message>
<message name="getSubscriptionIdsFault">
    <part name="parameter" element="ntfIRPData:getSubscriptionIdsFault"/>

```

```

</message>
<message name="getSubscriptionStatusRequest">
    <part name="parameter" element="ntfIRPData:getSubscriptionStatus"/>
</message>
<message name="getSubscriptionStatusResponse">
    <part name="parameter" element="ntfIRPData:getSubscriptionStatusResponse"/>
</message>
<message name="getSubscriptionStatusFault">
    <part name="parameter" element="ntfIRPData:getSubscriptionStatusFault"/>
</message>
<message name="changeSubscriptionFilterRequest">
    <part name="parameter" element="ntfIRPData:changeSubscriptionFilter"/>
</message>
<message name="changeSubscriptionFilterResponse">
    <part name="parameter" element="ntfIRPData:changeSubscriptionFilterResponse"/>
</message>
<message name="changeSubscriptionFilterFault">
    <part name="parameter" element="ntfIRPData:changeSubscriptionFilterFault"/>
</message>
<message name="suspendSubscriptionRequest">
    <part name="parameter" element="ntfIRPData:suspendSubscription"/>
</message>
<message name="suspendSubscriptionResponse">
    <part name="parameter" element="ntfIRPData:suspendSubscriptionResponse"/>
</message>
<message name="suspendSubscriptionFault">
    <part name="parameter" element="ntfIRPData:suspendSubscriptionFault"/>
</message>
<message name="resumeSubscriptionRequest">
    <part name="parameter" element="ntfIRPData:resumeSubscription"/>
</message>
<message name="resumeSubscriptionResponse">
    <part name="parameter" element="ntfIRPData:resumeSubscriptionResponse"/>
</message>
<message name="resumeSubscriptionFault">
    <part name="parameter" element="ntfIRPData:resumeSubscriptionFault"/>
</message>
<message name="getNotificationCategoriesRequest">
    <part name="parameter" element="ntfIRPData:getNotificationCategories"/>
</message>
<message name="getNotificationCategoriesResponse">
    <part name="parameter" element="ntfIRPData:getNotificationCategoriesResponse"/>
</message>
<message name="getNotificationCategoriesFault">
    <part name="parameter" element="ntfIRPData:getNotificationCategoriesFault"/>
</message>

<portType name="NotificationIRP">
    <operation name="getIRPVersion">
        <input message="genericIRPSystem:getIRPVersionRequest"/>
        <output message="genericIRPSystem:getIRPVersionResponse"/>
        <fault name="getIRPVersionFault" message="genericIRPSystem:getIRPVersionFault"/>
    </operation>
    <operation name="getOperationProfile">
        <input message="genericIRPSystem:getOperationProfileRequest"/>
        <output message="genericIRPSystem:getOperationProfileResponse"/>
        <fault name="getOperationProfileFault" message="genericIRPSystem:getOperationProfileFault"/>
    </operation>
    <operation name="getNotificationProfile">
        <input message="genericIRPSystem:getNotificationProfileRequest"/>
        <output message="genericIRPSystem:getNotificationProfileResponse"/>
        <fault name="getNotificationProfileFault" message="genericIRPSystem:getNotificationProfileFault"/>
    </operation>
    <operation name="subscribe">
        <input message="ntfIRPSystem:subscribeRequest"/>
        <output message="ntfIRPSystem:subscribeResponse"/>
        <fault name="subscribeFault" message="ntfIRPSystem:subscribeFault"/>
    </operation>
    <operation name="unsubscribe">
        <input message="ntfIRPSystem:unsubscribeRequest"/>
        <output message="ntfIRPSystem:unsubscribeResponse"/>
        <fault name="unsubscribeFault" message="ntfIRPSystem:unsubscribeFault"/>
    </operation>
    <operation name="getSubscriptionIds">
        <input message="ntfIRPSystem:getSubscriptionIdsRequest"/>
        <output message="ntfIRPSystem:getSubscriptionIdsResponse"/>
    </operation>

```

```
<fault name="getSubscriptionIdsFault" message="ntfIRPSystem:getSubscriptionIdsFault"/>
</operation>
<operation name="getSubscriptionStatus">
    <input message="ntfIRPSystem:getSubscriptionStatusRequest"/>
    <output message="ntfIRPSystem:getSubscriptionStatusResponse"/>
    <fault name="getSubscriptionStatusFault"
message="ntfIRPSystem:getSubscriptionStatusFault"/>
</operation>
<operation name="changeSubscriptionFilter">
    <input message="ntfIRPSystem:changeSubscriptionFilterRequest"/>
    <output message="ntfIRPSystem:changeSubscriptionFilterResponse"/>
    <fault name="changeSubscriptionFilterFault"
message="ntfIRPSystem:changeSubscriptionFilterFault"/>
</operation>
<operation name="suspendSubscription">
    <input message="ntfIRPSystem:suspendSubscriptionRequest"/>
    <output message="ntfIRPSystem:suspendSubscriptionResponse"/>
    <fault name="suspendSubscriptionFault" message="ntfIRPSystem:suspendSubscriptionFault"/>
</operation>
<operation name="resumeSubscription">
    <input message="ntfIRPSystem:resumeSubscriptionRequest"/>
    <output message="ntfIRPSystem:resumeSubscriptionResponse"/>
    <fault name="resumeSubscriptionFault" message="ntfIRPSystem:resumeSubscriptionFault"/>
</operation>
<operation name="getNotificationCategories">
    <input message="ntfIRPSystem:getNotificationCategoriesRequest"/>
    <output message="ntfIRPSystem:getNotificationCategoriesResponse"/>
    <fault name="getNotificationCategoriesFault"
message="ntfIRPSystem:getNotificationCategoriesFault"/>
</operation>

</portType>
<binding name="NotificationIRP" type="ntfIRPSystem:NotificationIRP">
    <soap:binding style="document" transport="http://schemas.xmlsoap.org/soap/http"/>
    <operation name="getIRPVersion">
        <soap:operation
soapAction="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-810/getIRPVersion"/>
        <input>
            <soap:body use="literal"/>
        </input>
        <output>
            <soap:body use="literal"/>
        </output>
        <fault name="getIRPVersionFault">
            <soap:fault name="getIRPVersionFault" use="literal"/>
        </fault>
    </operation>
    <operation name="getOperationProfile">
        <soap:operation
soapAction="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-810/getOperationProfile"/>
        <input>
            <soap:body use="literal"/>
        </input>
        <output>
            <soap:body use="literal"/>
        </output>
        <fault name="getOperationProfileFault">
            <soap:fault name="getOperationProfileFault" use="literal"/>
        </fault>
    </operation>
    <operation name="getNotificationProfile">
        <soap:operation
soapAction="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-810/getNotificationProfile"/>
        <input>
            <soap:body use="literal"/>
        </input>
        <output>
            <soap:body use="literal"/>
        </output>
        <fault name="getNotificationProfileFault">
            <soap:fault name="getNotificationProfileFault" use="literal"/>
        </fault>
    </operation>
    <operation name="subscribe">
```

```
<soap:operation
soapAction="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-810/subscribe"/>
<input>
    <soap:body use="literal"/>
</input>
<output>
    <soap:body use="literal"/>
</output>
<fault name="subscribeFault">
    <soap:fault name="subscribeFault" use="literal"/>
</fault>
</operation>
<operation name="unsubscribe">
<soap:operation
soapAction="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-810/unsubscribe"/>
<input>
    <soap:body use="literal"/>
</input>
<output>
    <soap:body use="literal"/>
</output>
<fault name="unsubscribeFault">
    <soap:fault name="unsubscribeFault" use="literal"/>
</fault>
</operation>
<operation name="getSubscriptionIds">
<soap:operation
soapAction="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-810/getSubscriptionIds"/>
<input>
    <soap:body use="literal"/>
</input>
<output>
    <soap:body use="literal"/>
</output>
<fault name="getSubscriptionIdsFault">
    <soap:fault name="getSubscriptionIdsFault" use="literal"/>
</fault>
</operation>
<operation name="getSubscriptionStatus">
<soap:operation
soapAction="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-810/getSubscriptionStatus"/>
<input>
    <soap:body use="literal"/>
</input>
<output>
    <soap:body use="literal"/>
</output>
<fault name="getSubscriptionStatusFault">
    <soap:fault name="getSubscriptionStatusFault" use="literal"/>
</fault>
</operation>
<operation name="changeSubscriptionFilter">
<soap:operation
soapAction="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-810/changeSubscriptionFilter"/>
<input>
    <soap:body use="literal"/>
</input>
<output>
    <soap:body use="literal"/>
</output>
<fault name="changeSubscriptionFilterFault">
    <soap:fault name="changeSubscriptionFilterFault" use="literal"/>
</fault>
</operation>
<operation name="suspendSubscription">
<soap:operation
soapAction="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-810/suspendSubscription"/>
<input>
    <soap:body use="literal"/>
</input>
<output>
    <soap:body use="literal"/>
</output>
```

```
<fault name="suspendSubscriptionFault">
    <soap:fault name="suspendSubscriptionFault" use="literal"/>
</fault>
</operation>
<operation name="resumeSubscription">
    <soap:operation
soapAction="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-
810/resumeSubscription"/>
    <input>
        <soap:body use="literal"/>
    </input>
    <output>
        <soap:body use="literal"/>
    </output>
    <fault name="resumeSubscriptionFault">
        <soap:fault name="resumeSubscriptionFault" use="literal"/>
    </fault>
</operation>
<operation name="getNotificationCategories">
    <soap:operation
soapAction="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-
810/getNotificationCategories"/>
    <input>
        <soap:body use="literal"/>
    </input>
    <output>
        <soap:body use="literal"/>
    </output>
    <fault name="getNotificationCategoriesFault">
        <soap:fault name="getNotificationCategoriesFault" use="literal"/>
    </fault>
</operation>
</binding>
<service name="NotificationIRP">
    <port name="NotificationIRP" binding="ntfIRPSystem:NotificationIRP">
        <soap:address location="To be defined."/>
    </port>
</service>
</definitions>
```

Annex B (normative): Notification WSDL specifications

```
<?xml version="1.0" encoding="UTF-8"?>
<definitions xmlns="http://schemas.xmlsoap.org/wsdl/"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
  xmlns:http="http://schemas.xmlsoap.org/wsdl/http" xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:ntfIRPntfSystem="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-
  810/notification/NotificationIRPntfSystem"
  xmlns:ntfIRPntfData="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-
  810/notification/NotificationIRPntfData"
  targetNamespace="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-
  810/notification/NotificationIRPntfSystem">
  <types>
    <schema
      targetNamespace="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-
      810/notification/NotificationIRPntfData" xmlns="http://www.w3.org/2001/XMLSchema">
      <!-- notify Request -->
      <element name="notify">
        <complexType>
          <sequence>
            <element name="notificationHeaderAndBody"
              type="ntfIRPntfData:AnySequenceType"/>
          </sequence>
        </complexType>
      </element>
      <complexType name="AnySequenceType">
        <sequence>
          <any namespace="#any" processContents="lax" maxOccurs="unbounded"/>
        </sequence>
      </complexType>
    </schema>
  </types>
  <message name="notifyRequest">
    <part name="parameter" element="ntfIRPntfData:notify" />
  </message>
  <portType name="NotificationIRPntf">
    <operation name="notify">
      <input message="ntfIRPntfSystem:notifyRequest" />
    </operation>
  </portType>
  <binding name="NotificationIRPntf" type="ntfIRPntfSystem:NotificationIRPntf">
    <soap:binding style="document" transport="http://schemas.xmlsoap.org/soap/http"/>
    <operation name="notify">
      <soap:operation
        soapAction="http://www.3gpp.org/ftp/Specs/archive/32_series/32.307/schema/32307-
        810/notification/notify"/>
      <input>
        <soap:body use="literal"/>
      </input>
    </operation>
  </binding>
  <service name="NotificationIRPntf">
    <port name="NotificationIRPntf" binding="ntfIRPntfSystem:NotificationIRPntf">
      <soap:address location="To be defined." />
    </port>
  </service>
</definitions>
```

Annex C (informative):
Void

Annex D (informative): Change history

Change history								
Date	TSG #	TSG Doc.	CR	R	Subject/Comment	Cat	Old	New
Mar 2006	SA_31	SP-060096	--	--	Submitted to TSG SA#31 for Information	--	1.0.0	
Dec 2006	SA_34	SP-060740	--	--	Submitted to TSG SA#34 for Approval	--	2.0.0	7.0.0
Mar 2007	--	--	--	--	Delete reference to the 32.304 CMIP SS. Reason: SA#35 endorsed the SA5 decision to not propagate the CMIP Solution Sets to Rel-7 (TS 32.3x4, TS 32.4x4, TS 32.6x4)	--	7.0.0	7.0.1
Jun 2007	--	--	--	--	Changed TS Title. Reason: SOAP does not stand anymore for "Simple Object Access Protocol"	--	7.0.1	7.0.2
Dec 2008	SA_42	SP-080845	0001	-	Incorrect URI specified in TS 32.307 (both word document and corresponding wsdl file)	F	7.0.2	7.1.0
Dec 2008	SA_42	--	--	--	Upgrade to Release 8	--	7.1.0	8.0.0
Mar 2009	SA_43	SP-090207	0002	--	Correction of notify	F	8.0.0	8.1.0
Dec 2009	SA_46	SP-090719	0003	--	Discontinuation of the maintenance of WSDL/XML schema folders	C	8.1.0	9.0.0
Mar 2010	SA_47	SP-100034	0005	--	Incorrect direction for message notifyRequest	A	9.0.0	9.1.0
Sep 2011	SA_53	SP-110524	0007	--	Change direction of notifications in SOAP solution	A	9.1.0	9.2.0