

# 3GPP TS 32.354 V6.0.0 (2004-12)

---

*Technical Specification*

**3rd Generation Partnership Project;  
Technical Specification Group Services and System Aspects;  
Telecommunication management;  
Communication Surveillance Integration Reference Point (IRP);  
Common Management Information Protocol (CMIP)  
Solution Set (SS)  
(Release 6)**

---



The present document has been developed within the 3<sup>rd</sup> Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP.

The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification. Specifications and reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organizational Partners' Publications Offices.

---

Keywords

---

UMTS, management, IRP, CMIP

**3GPP**

Postal address

---

3GPP support office address

---

650 Route des Lucioles - Sophia Antipolis  
Valbonne - FRANCE  
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

---

<http://www.3gpp.org>

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© 2004, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TTA, TTC).  
All rights reserved.

# Contents

Foreword .....	4
Introduction .....	4
1 Scope .....	5
2 References.....	5
3 Definitions and abbreviations .....	6
3.1 Definitions .....	6
3.2 Abbreviations.....	6
4 Basic aspects .....	6
4.1 General .....	6
4.2 Mapping.....	6
4.2.1 Mapping of Information Object Classes (IOCs).....	6
4.2.2 Mapping of Attributes .....	7
4.2.2.1 Attribute Mapping of the IOC <i>CSIRP</i> .....	7
4.2.3 Mapping of operations .....	7
4.2.4 Mapping of Operation Parameters .....	7
4.2.4.1 Parameter Mapping of the Operation <i>getHeartbeatPeriod</i> .....	8
4.2.4.2 Parameter Mapping of the Operation <i>triggerHeartbeat</i> .....	8
4.2.4.3 Parameter Mapping of the Operation <i>setHeartbeatPeriod</i> .....	8
4.2.4.4 Parameter mapping of the Operation <i>getIRPVersion</i> .....	8
4.2.4.5 Parameter mapping of the Operation <i>getOperationProfile</i> .....	8
4.2.4.6 Parameter mapping of the Operation <i>getNotificationProfile</i> .....	9
4.2.5 Mapping of Notifications.....	9
4.2.6 Mapping of Notification Parameters .....	9
4.2.6.1 Parameter Mapping of the Notification <i>notifyHeartbeat</i> .....	9
--5 GDMO Definitions .....	10
--5.1.1 <i>csIRP</i> .....	10
--5.2 Packages .....	10
--5.2.1 <i>csIRPBasicPackage</i> .....	10
--5.3 Parameters .....	10
--5.4 Name Bindings.....	10
--5.5 Attributes.....	10
--5.5.1 <i>heartBeatPeriod</i> .....	10
--5.6 Actions.....	11
--5.6.1 <i>triggerHeartbeat</i> .....	11
--5.7 Notifications .....	11
--5.7.1 <i>notifyHeartbeat</i> .....	11
6 ASN.1 Definitions .....	12
<b>Annex A (informative): List of assigned Object Identifiers.....</b>	<b>14</b>
<b>Annex B (informative): Change history.....</b>	<b>15</b>

---

## Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following for mal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

## Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

- 32.351: "Communication Surveillance Integration Reference Point (IRP); Requirements";
- 32.352: "Communication Surveillance Integration Reference Point (IRP): Information Service (IS)";
- 32.353: "Communication Surveillance Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)";
- 32.354: "Communication Surveillance Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS)".**

A 3G telecommunication network is composed of a multitude of different Network Elements (NE). For a successful operation of the network the operator must be provided with mechanisms allowing him to manage the network. These management activities can be grouped into several areas: configuration management, fault management, performance management, accounting management and security management.

A management function assisting in different high level management areas such as fault management and performance management is the function to log notification. The purpose of notification logging is to keep the content of the notification stored and safe for later access.

The present document is part of a TS-family defining the Telecommunication Management (TM) of 3G systems. The TM principles are described in 3GPP TS 32.101 [1]. The TM architecture is described in 3GPP TS 32.102 [2]. The other specifications define the interface (Itf-N) between the managing system (manager), which is in general the Network Manager (NM) and the managed system (agent), which is either an Element Manager (EM) or the managed NE itself. The Itf-N is composed of a number of Integration Reference Points (IRPs) defining the information in the agent that is visible for the manager, the operations that the manager may perform on this information and the notifications that are sent from the agent to the manager. One of these IRPs is the Communication Surveillance IRP.

Each IRP is specified by the requirements part, the Information Service part, the CORBA SS and the CMIP SS.

---

# 1 Scope

The present document specifies the CMIP SS for the Communication Surveillance IRP IS defined in 3GPP TS 32.352 [8]. In detail:

- Clause 4 provides the basic architectural concept of the CMIP SS and the mapping between the IOCs, operations and notifications defined in 3GPP TS 32.352 [8] to the corresponding CMIP SS equivalents.
- Clause 5 contains the GDMO definitions for the Communication Surveillance IRP over the CMIP interfaces.
- Clause 6 contains the ASN.1 definitions supporting the GDMO definitions provided in clause 5.

This Solution Set specification is related to 3GPP TS 32.352 (V6.0.X).

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] 3GPP TS 32.302: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP): Information Service".
- [4] 3GPP TS 32.314: "Telecommunication management; Generic Integration Reference Point (IRP) management; Common Management Information Protocol (CMIP) Solution Set (SS)".
- [5] 3GPP TS 32.304: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS)".
- [6] 3GPP TS 32.312: "Telecommunication management; Generic Integration Reference Point (IRP) management; Information Service (IS)".
- [7] 3GPP TS 32.351: "Telecommunication management; Communication Surveillance Integration Reference Point (IRP): Requirements".
- [8] 3GPP TS 32.352: "Telecommunication management; Communication Surveillance Integration Reference Point (IRP): Information Service (IS)".
- [9] ITU-T Recommendation X.735: "Information Technology - Open Systems Interconnection – Log Control Function".
- [10] ITU-T Recommendation X.710: "Information Technology – Open Systems Interconnection – Common Management Information Service"
- [11] ITU-T Recommendation X.721: "Information Technology - Open Systems Interconnection - Structure of Management Information: Definition of Management Information"
- [12] ITU-T Recommendation X.734: "Information Technology - Open Systems Interconnection - Systems Management: Event Report Management Function".

---

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TS 32.101 [1], 3GPP TS 32.102 [2] and 3GPP TS 32.351 [7] apply.

### 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ASN.1	Abstract Syntax Notation One
CMISE	Common Management Information Service
CMIP	Common Management Information Protocol
CORBA	Common Object Request Broker Architecture
CS	Communication Surveillance
EM	Element Manager
GDMO	Guidelines for the Definition of Managed Objects
IOC	Information Object Class
IRP	Integration Reference Point
IS	Information Service
MOC	Managed Object Class
NE	Network Element
NM	Network Manager
SS	Solution Set
TM	Telecommunication Management

---

## 4 Basic aspects

### 4.1 General

The present document provides all the GDMO definitions necessary to implement the Communication Surveillance IRP Information Service (3GPP TS 32.352 [8]) for the CMIP interface.

### 4.2 Mapping

The semantics of the Communication Surveillance IRP are defined in 3GPP TS 32.352 [8]. The definitions of the management information defined there are independent of any implementation technology and protocol. This clause maps these protocol independent definitions onto their equivalents of the CMIP SS of the Communication Surveillance IRP.

#### 4.2.1 Mapping of Information Object Classes (IOCs)

The following table maps the IOCs defined in 3GPP TS 32.352 [8] to the corresponding Managed Object Classes (MOCs) defined in this CMIP SS. The MOCs are qualified either as Mandatory (M) or Optional (O).

**Mapping of IOCs**

IS IOC	MOC of the CMIP SS	Qualifier
CSIRP	csIRP	M

## 4.2.2 Mapping of Attributes

This clause depicts the mapping of the attributes defined in 3GPP TS 32.352 [8] and 3GPP TS 32.312 [6] on the corresponding attributes of the CMIP Solution Set.

### 4.2.2.1 Attribute Mapping of the IOC CSIRP

#### Attribute mapping of the IOC CSIRP

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
iRPId	irpId	M	M	-
heartBeatPeriod	heartBeatPeriod	M	M	-
countDownTimer	-(TS 32.352: invisible attribute)	M	-	-

## 4.2.3 Mapping of operations

The following two tables map the operations defined in 3GPP TS 32.352 [8] and 3GPP TS 32.312 [6] to corresponding GDMO actions and CMISE services. The operations are qualified either as Mandatory (M) or Optional (O).

The CMISE services are defined in ITU-T Recommendation X.710 [10].

#### Mapping of operations of the Communication Surveillance IRP: IS

Interface	Qualifier	IS Operation	GDMO Action or CMISE of CMIP SS	Qualifier
CSIRPOperations_1	M	getHeartbeatPeriod	M-GET to MOC csIRP	M
		triggerHeartbeat	triggerHeartbeat	M
CSIRPOperations_2	O	setHeartbeatPeriod	M-SET to MOC csIRP	M

#### Mapping of operations inherited from the Generic IRP Management: IS

Interface	Operation	GDMO Action or CMISE of CMIP SS	Qualifier
GenericRPVersionsOperations	getRPVersion	getRPVersion	M
GenericRPPProfileOperations	getOperationProfile	getOperationProfile	O
	getNotificationProfile	getNotificationProfile	O

## 4.2.4 Mapping of Operation Parameters

The tables in the following subclauses list the parameters of each operation defined in 3GPP TS 32.322 [8] and their equivalents in the CMIP SS.

#### 4.2.4.1 Parameter Mapping of the Operation *getHeartbeatPeriod*

The operation *getHeartbeatPeriod* is mapped to a CMISE M-GET service of an the csIRP MOC.

##### Parameter mapping of the operation 'getHeartbeatPeriod'

IS Parameter Name	IN/OUT	Qualifier	CMIP SS Equivalent	Qualifier
-	IN	M	M-GET request parameters 'base object class' and 'base object instance', 'scope' and 'filter' shall identify the csIRP instance	M
heartBeatPeriod	OUT	M	M-GET request parameter 'Attribute list': attribute identifier and value for the 'heartBeatPeriod' attribute	M
status	OUT	M	status = OperationSucceeded The semantics of this status are conveyed by the emission of an M-GET success confirmation.  status = OperationFailed The semantics of this status are conveyed by the emission of an M-GET failure confirmation.	M

#### 4.2.4.2 Parameter Mapping of the Operation *triggerHeartbeat*

The operation *triggerHeartbeat* is mapped to a CMISE M-ACTION of the csIRP MOC.

##### Parameter mapping of the operation 'triggerHeartbeat'

IS Parameter Name	IN/OUT	Qualifier	CMIP SS Equivalent	Qualifier
-	IN	M	M-ACTION request parameters 'base object class' and 'base object instance', 'scope' and 'filter' shall identify the csIRP instance	
managerIdentifier	IN	M	M-ACTION parameter 'Action information': TriggerHeartBeatInfo): managerIdentifier	M
status	OUT	M	M-ACTION parameter 'Action reply': (TriggerHeartBeatReply): status	M

#### 4.2.4.3 Parameter Mapping of the Operation *setHeartbeatPeriod*

The operation *setHeartbeatPeriod* is mapped to a CMISE M-SET service of an the csIRP MOC.

##### Parameter mapping of the operation 'setHeartbeatPeriod'

IS Parameter Name	IN/OUT	Qualifier	CMIP SS Equivalent	Qualifier
-	IN	M	M-SET request parameters 'base object class' and 'base object instance', 'scope' and 'filter' shall identify the csIRP instance	M
heartBeatPeriod	IN	M	M-SET request parameter Modification List' contains attribute identifier and value and modifyOperator for the attribute heartBeatPeriod	M
status	OUT	M	status = OperationSucceeded The semantics of this status are conveyed by the emission of an M-SET success confirmation.  status = OperationFailed The semantics of this status are conveyed by the emission of an M-SET failure confirmation.	M

#### 4.2.4.4 Parameter mapping of the Operation *getIRPVersion*

See TS 32.314 [4].

#### 4.2.4.5 Parameter mapping of the Operation *getOperationProfile*

See TS 32.314 [4].



#### 4.2.4.6 Parameter mapping of the Operation getNotificationProfile

See TS 32.314 [4].

### 4.2.5 Mapping of Notifications

#### Mapping of notifications of the Communication Surveillance IRP: IS

Interface	Qualifier	IS Notification	GDMO Action or CMISE of CMIP SS	Qualifier
CsIRPNotifications	M	notifyHeartbeat	notifyHeartbeat	M

### 4.2.6 Mapping of Notification Parameters

The table in the following subclause shows the parameters of each notification defined in 3GPP TS 32.352 [8] and their equivalents in the CMIP Solution Set.

#### 4.2.6.1 Parameter Mapping of the Notification *notifyHeartbeat*

##### Parameter mapping of the notification 'notifyHeartbeat'

IS Parameter	CMIP SS Equivalent	Qualifier
objectClass	M-EVENT REPORT parameter 'Managed object class'	M
objectInstance	M-EVENT REPORT parameter 'Managed object instance'	M
eventTime	M-EVENT-REPORT parameter 'Event time'	M
notificationId	M-EVENT-REPORT parameter 'Event information' (NotifyHeartBeatInfo): notificationIdentifier	O
systemDN	This parameter is conditional and not used in the CMIP SS.	--
notificationType	M-EVENT REPORT parameter 'Event type'	M
heartBeatPeriod	M-EVENT-REPORT parameter 'Event information' (NotifyHeartBeatInfo): heartBeatPeriod	M
locator	Not applicable for CMIP SS	M
triggerFlag	M-EVENT-REPORT parameter 'Event information' (NotifyHeartBeatInfo): triggerFlag	M
managerIdentifier	M-EVENT-REPORT parameter 'Event information' (NotifyHeartBeatInfo): managerIdentifier	M

NOTE: 3GPP TS 32.352 [8] allows to choose to send this notification - in case it has been triggered by operation *triggerHeartBeat* - to:

- a) one notification to the invoking IRPManager; or
- b) one notification to each of the subscribed IRPManagers,

depending on system performance considerations.

An appropriate *EventForwardingDiscriminator* has to be chosen in the framework of the CMIP SS.

---

## --5 GDMO Definitions

--Please do not remove the "--" in front of the headline numbering, as it is the CMIP code  
 --for a comment. This way the whole chapter can be put directly into a compiler.

### --5.1 Managed Object Classes

#### --5.1.1 csIRP

```
csIRP MANAGED OBJECT CLASS
  DERIVED FROM
    "3GPP TS 32.314":managedGenericIRP;
  CHARACTERIZED BY
    csIRPBasicPackage;
  REGISTERED AS {ts32-354ComSurvObjectClass 10600};
```

### --5.2 Packages

#### --5.2.1 csIRPBasicPackage

```
csIRPBasicPackage PACKAGE
  BEHAVIOUR
    csIRPBasicPackageBehaviour;
  ATTRIBUTES
    heartBeatPeriod;
  NOTIFICATIONS
    notifyHeartbeat;
  ACTIONS
    triggerHeartbeat;
  REGISTERED AS {ts32-354ComSurvPackage 10600};

csIRPBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "This package provides all mandatory items of MOC csIRP.";
```

### --5.3 Parameters

--None.

### --5.4 Name Bindings

--None.

### --5.5 Attributes

#### --5.5.1 heartBeatPeriod

```
heartBeatPeriod ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-354ComSurvTypeModule.HeartBeatPeriod;
  BEHAVIOUR
    heartBeatPeriodBehaviour;
  REGISTERED AS {ts32-354ComSurvAttribute 10600};

heartBeatPeriodBehaviour BEHAVIOUR
DEFINED AS
  "This attribute specifies the time between two emissions of heartbeat notifications. A value of zero
  implies there is no heartbeat emission. The unit is minute.";
```

## --5.6 Actions

### --5.6.1 triggerHeartbeat

triggerHeartbeat **ACTION**

**BEHAVIOUR**

triggerHeartbeatBehaviour;

**MODE**

CONFIRMED;

**WITH INFORMATION SYNTAX**

TS32-354ComSurvTypeModule.TriggerHeartbeatInfo;

**WITH REPLY SYNTAX**

TS32-354ComSurvTypeModule.TriggerHeartbeatReply;

**REGISTERED AS** {ts32-354comSurvAction 10600};

triggerHeartbeatBehaviour **BEHAVIOUR**

**DEFINED AS**

"The IRPManager invokes this operation to solicit a notifyHeartbeat notification. After the successful completion of the operation, the IRPAgent shall emit the notifyHeartbeat notification immediately. One notification shall be emitted as follows:

- a) one notification to the invoking IRPManager; or
- b) one notification to each of the subscribed IRPManagers.

If the operation fails the notification shall not be emitted.

One of the two options above shall be chosen depending on system performance considerations.

Before invoking this operation, the invoking IRPManager should make sure it has subscribed the notifyHeartbeat notification.

The behaviour of this functionality is defined within 32.322 - below provides an overview and CMI P specific semantics.

The M-ACTION request parameter 'Action information' contains the managerIdentifier of the invoking IRPManager.

The M-ACTION response parameter 'Action reply' is composed of the following data:

+ status

The parameter *status* contains the results of the Manager action.

Possible values:

noError (0),

error (the value indicates the reason of the error).

";

## --5.7 Notifications

### --5.7.1 notifyHeartbeat

notifyHeartbeat **NOTIFICATION**

**BEHAVIOUR**

notifyHeartbeatBehaviour;

**WITH INFORMATION SYNTAX**

TS32-354ComSurvTypeModule.NotifyHeartbeatInfo;

**REGISTERED AS** {ts32-354comSurvNotification 10600};

notifyHeartbeatBehaviour **BEHAVIOUR**

**DEFINED AS**

"This notification is used to notify the subscribed IRPManager instances that the resources supporting the communication path between the Notification IRPAgent and the notification receiving IRPManager are working.";

## 6 ASN.1 Definitions

```

TS32-354comSurvTypeModule {
    itu-t (0)
    identified-organization(4)
    etsi(0)
    mobileDomain(0)
    umts-Operation-Maintenance(3)
    ts32-354 (354)
    informationModel(0)
    asn1Module (2)
    version10600(10600)
}

DEFINITIONS IMPLICIT TAGS ::=
BEGIN
--EXPORTS everything

IMPORTS
NotificationIdentifier
    FROM Attribute-ASN1Module {joint-iso-ccitt ms(9) smi(3) part2(2) asn1Module(2) 1}; --X.721

-- 3GPP TS 32.354 related Object Identifiers

baseNodeUMTS                OBJECT IDENTIFIER ::= {itu-t(0) identified-organization(4)
                                etsi(0) mobileDomain(0)
                                umts-Operation-Maintenance(3)}
ts32-354comSurvPrefix        OBJECT IDENTIFIER ::= {baseNodeUMTS
                                ts32-354
                                (354)}
ts32-354comSurvInfoModel    OBJECT IDENTIFIER ::= {ts32-354comSurvPrefix
                                informationModel
                                ( 0)}
ts32-354comSurvObjectClass  OBJECT IDENTIFIER ::= {ts32-354comSurvInfoModel
                                managedObjectClass
                                ( 3)}
ts32-354comSurvPackage      OBJECT IDENTIFIER ::= {ts32-354comSurvInfoModel
                                package
                                ( 4)}
ts32-354comSurvParameter    OBJECT IDENTIFIER ::= {ts32-354comSurvInfoModel
                                parameter
                                ( 5)}
ts32-354comSurvNameBinding  OBJECT IDENTIFIER ::= {ts32-354comSurvInfoModel
                                nameBinding
                                ( 6)}
ts32-354comSurvAttribute    OBJECT IDENTIFIER ::= {ts32-354comSurvInfoModel
                                attribute
                                ( 7)}
ts32-354comSurvAction       OBJECT IDENTIFIER ::= {ts32-354comSurvInfoModel
                                action
                                ( 9)}
ts32-354comSurvNotification OBJECT IDENTIFIER ::= {ts32-354comSurvInfoModel
                                notification
                                ( 10)}

-- Start of 3GPP SA5 own definitions

ErrorCauses ::= ENUMERATED
{
    noError                (0),          -- operation / notification successfully performed
    unspecifiedErrorReason (255)        -- operation failed, specific error unknown
}

HeartBeatPeriod ::= INTEGER (0..60)

ManagerIdentifier ::= GraphicString

NotifyHeartbeatInfo ::= SEQUENCE
{
    notificationIdentifier NotificationIdentifier,
    heartBeatPeriod        HeartBeatPeriod,
    managerIdentifier       ManagerIdentifier,
    triggerFlag            TriggerFlag
}

TriggerFlag ::= ENUMERATED {
    irpManager (0),
    irpAgent   (1)
}

TriggerHeartbeatInfo ::= SEQUENCE
{

```

```
managerIdentifier  ManagerIdentifier,  
status            ErrorCauses  
}
```

```
TriggerHeartbeatReply ::= ErrorCauses
```

```
END -- of module TS32-354ComSurvTypeModule
```

## Annex A (informative): List of assigned Object Identifiers

This annex provides a list with all object identifiers that have been assigned in TS 32.354. These object identifiers shall not be assigned to new objects (also not in new versions of this document).

Basic Name	Name and OID of the current TS Version	Name and OIDs of previous TS Versions
<b>Managed Object Classes</b>		
csIRP	Name: csIRP OID: ts32-354comSurvObjectClass 10600	--
--		
<b>Packages</b>		
csIRPBasicPackage	Name: csIRPBasicPackage OID: ts32-354comSurvPackage 10600	--
--		
<b>Parameters</b>		
--		
<b>Name Bindings</b>		
--		
<b>Attributes</b>		
heartBeatPeriod	Name: heartBeatPeriod OID: ts32-354comSurvAttribute 10600	
--		
<b>Actions</b>		
triggerHeartbeat	Name: triggerHeartbeat OID : ts32-354comSurvAction 10600	
--		
<b>Notifications</b>		
notifyHeartbeat	Name: notifyHeartbeat OID : ts32-354comSurvNotification 10600	
--		
<b>Type Module</b>		
TS32-354comSurvTypeModule	Name: TS32-354comSurvTypeModule OID: { itu-t(0) identified-organization(4) etsi(0) mobileDomain(0) umts-Operation-Maintenance(3) ts32-354(354) informationModel(0) asn1Module(2) Version10600(106000) }	
--		

---

## Annex B (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
Dec 2004	S_26	SP-040803	--	--	Submitted to SA#26 for Approval	1.0.0	6.0.0