

3GPP TS 32.395 V9.1.0 (2011-12)

Technical Specification

**3rd Generation Partnership Project;
Technical Specification Group Services and System Aspects;
Telecommunication management;
Delta Synchronisation Integration Reference Point (IRP):
eXtensible Markup Language (XML) file format definition
(Release 9)**



The present document has been developed within the 3rd Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP. The present document has not been subject to any approval process by the 3GPP Organisational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organisational Partners accept no liability for any use of this Specification. Specifications and reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organisational Partners' Publications Offices.

Keywords

Management, CORBA

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2011, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TTA, TTC).
All rights reserved.

UMTS™ is a Trade Mark of ETSI registered for the benefit of its members
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners
LTE™ is a Trade Mark of ETSI currently being registered for the benefit of its Members and of the 3GPP Organizational Partners
GSM® and the GSM logo are registered and owned by the GSM Association

Contents

Foreword	4
Introduction	4
1 Scope	5
2 References.....	5
3 Definitions and abbreviations	6
3.1 Definitions	6
3.2 Abbreviations.....	7
4 Structure and content of configuration data XML files	7
4.1 Global structure.....	7
4.2 XML elements fileHeader and fileFooter	8
4.2.1 XML elements fileHeaderForDeltaSynchForCM/AlarmData	8
4.2.2 XML element fileFooter	9
4.3 Delta synchronisation IRP specific XML elements.....	10
4.4 Delta synchronisation IRP XML File Name Conventions	10
Annex A (normative): Delta synchronization specific data file XML schemas.....	11
A.1 Delta synchronization specific data file XML schemas Generic Part (file name "deltaSynchGeneric.xsd").....	11
A.2 Delta synchronization specific data file XML schemas for CM data (file name "deltaSynchForCMDData.xsd").....	13
A.3 Delta synchronization specific data file XML schemas for alarm data (file name "deltaSynchForAlarms.xsd").....	15
Annex B (informative): Void.....	17
Annex C (informative): Change history.....	18

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

- 32.391: Delta Synchronisation Integration Reference Point (IRP); Requirements
- 32.392: Delta Synchronisation Integration Reference Point (IRP); Information Service (IS)
- 32.393: Delta Synchronisation Integration Reference Point (IRP); Common Object Request Broker Architecture (CORBA) Solution Set
- 32.395: Delta Synchronization Integration Reference Point (IRP); eXtensible Markup Language (XML) file format definition**

The Itf-N interface is built up by a number of IRPs and a related Name Convention, which realise the functional capabilities over this interface. The basic structure of the IRPs is defined in TS 32.101 [1] and TS 32.102 [2].

IRPManagers (typically Network Management Systems) and IRPAgents (typically EMs or NEs) synchronize their data concerning alarms or configuration data. In certain scenarios this synchronization is lost or not done. This IRP provides functionality to significantly reduce the amount of data which needs to be transferred in order to re-establish synchronisation.

1 Scope

The purpose of Delta Synchronisation IRP is to define an interface through which an IRPManager can request only those data which changed (i.e. changed, were created or deleted) from a synchronisation point onwards.

The present document is the eXtensible Markup Language (XML) file format definition of Delta Synchronisation IRP for the IRP whose semantics is specified in Delta Synchronisation IRP: Information Service (3GPP TS 32.392 [11]).

This XML Definitions specification defines the XML syntax of the Delta Synchronisation IRP XML Data File.

This XML Definitions specification is related to 3GPP TS 32.392 V9.0.X.

2 References

The following documents contain provisions that, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document.

- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] 3GPP TS 32.342: "Telecommunication management; File Transfer (FT) Integration Reference Point (IRP): Information Service (IS)".
- [4] W3C REC-xml-20001006: "Extensible Markup Language (XML) 1.0 (Second Edition)".
- [5] W3C REC-xmlschema-0-20010502: "XML Schema Part 0: Primer".
- [6] W3C REC-xmlschema-1-20010502: "XML Schema Part 1: Structures".
- [7] W3C REC-xmlschema-2-20010502: "XML Schema Part 2: Datatypes".
- [8] W3C REC-xml-names-19990114: "Namespaces in XML".
- [10] 3GPP TS 32.391: "Configuration Management (CM); Delta Synchronisation Integration Reference Point (IRP): Requirements".
- [11] 3GPP TS 32.392: "Configuration Management (CM); Delta Synchronisation Integration Reference Point (IRP): Information Service (IS)".
- [12] 3GPP TS 32.305: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP): eXtensible Markup Language (XML) definitions".
- [13] 3GPP TS 32.111-5: "Telecommunication management; Fault Management; Part 5: Alarm Integration Reference Point (IRP): eXtensible Markup Language (XML) definitions".
- [14] 3GPP TS 32.615: "Telecommunication management; Configuration Management (CM); Bulk CM Integration Reference Point (IRP): eXtensible Markup Language (XML) definitions".
- [15] 3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

Changed alarm: See 3GPP TS 32.391 [10].

Changed instance: See 3GPP TS 32.391 [10].

Delta Synchronisation: See 3GPP TS 32.391 [10].

Delta Synchronisation Point: See 3GPP TS 32.391 [10].

Full Synchronisation: See 3GPP TS 32.391 [10].

IRP: See 3GPP TS 32.101 [1].

IRP Agent: See 3GPP TS 32.102 [2].

IRP Manager: See 3GPP TS 32.102 [2].

XML file: file containing an XML document

XML document: composed of the succession of an optional XML declaration followed by a root XML element [4].

XML declaration: it specifies the version of XML being used, see [4].

XML element: has a type, is identified by a name, may have a set of XML attribute specifications and is either composed of the succession of an XML start-tag followed by the XML content of the XML element followed by an XML end-tag, or composed simply of an XML empty-element tag; each XML element may contain other XML elements, see [4].

empty XML element: having an empty XML content; an empty XML element still possibly has a set of XML attribute specifications; an empty XML element is either composed of the succession of an XML start-tag directly followed by an XML end-tag, or composed simply of an XML empty-element tag, see [4].

XML content (of an XML element): empty if the XML element is simply composed of an XML empty-element tag; otherwise the part, possibly empty, of the XML element between its XML start-tag and its XML end-tag, see [4].

XML start-tag: the beginning of a non-empty XML element is marked by an XML start-tag containing the name and the set of XML attribute specifications of the XML element, see [4].

XML end-tag: the end of a non-empty XML element is marked by an XML end-tag containing the name of the XML element, see [4].

XML empty-element tag: composed simply of an empty-element tag containing the name and the set of XML attribute specifications of the XML element, see [4].

XML attribute specification: has a name and a value, see [4].

DTD: defines structure and content constraints to be respected by an XML document to be valid with regard to this DTD, see [4].

XML schema: more powerful than a DTD, an XML schema defines structure and content constraints to be respected by an XML document to conform with this XML schema; through the use of XML namespaces several XML schemas can be used together by a single XML document; an XML schema is itself also an XML document that shall conform with the XML schema for XML schemas, see [5], [6] and [7].

XML namespace: enables qualifying element and attribute names used in XML documents by associating them with namespaces identified by different XML schemas, see [5], [6] and [7].

XML complex type: defined in an XML schema; cannot be directly used in an XML document; can be the concrete type or the derivation base type for an XML element type or for another XML complex type; ultimately defines constraints for an XML element on its XML attribute specifications and/or its XML content, see [5], [6] and [7].

XML element type: declared by an XML schema; can be directly used in an XML document; as the concrete type of an XML element, directly or indirectly defines constraints on its XML attribute specifications and/or its XML content; can also be the concrete type or the derivation base type for another XML element type, see [5], [6] and [7].

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

EM	Element Manager
IRP	Integration Reference Point
IS	Information Service (see 3GPP TS 32.101 [1])
Itf-N	Interface N
NE	Network Element
XML	eXtensible Mark-up Language

4 Structure and content of configuration data XML files

Annex A of the present document defines the delta synchronization-specific XML schema and element types in `deltaSynchForCMDData.xsd`/`deltaSynchForAlarms.xsd` which shall be used for the files of which the locations can be supplied as an option in output of operation `triggerDeltaSynchOfCMDData` or `triggerDeltaSynchOfAlarms` defined in 3GPP TS 32.392 [11].

The present schema re-uses the structure and content of 3GPP TS 32.615 [14] for delta synchronization for CM data and those of 3GPP TS 32.111-5 [13] for delta synchronization for alarm data. The differences or additions are listed here:

For delta synchronization for CM data:

The modifier XML attribute specification shall be used as follows:

- Create for all created NRM instances
- Update for all modified NRM instances
- Delete for all deleted NRM instances

For delta synchronization for alarm data:

- Created alarms shall be indicated by content XML elements of `type="xa:NotifyNewAlarm"`
- Changed alarms shall be indicated by content XML elements of `type="xa:NotifyChangedAlarm"` or of `type="xa:NotifyClearedAlarm"` or of `type="xa:NotifyComments"`
- Deleted alarms shall be indicated by content XML elements of `type="xa:NotifyAckStateChanged"`

4.1 Global structure

See 3GPP TS 32.615 [14]

The following XML namespaces are potentially used in delta synchronisation XML files:

- delta synchronisation for CM data files are associated with XML schema `deltaSynchForCMDData.xsd` (see Annex A.1);
- delta synchronisation for alarm data files are associated with XML schema `deltaSynchForAlarmData.xsd` (see Annex A.2);

4.2 XML elements fileHeader and fileFooter

4.2.1 XML elements fileHeaderForDeltaSynchForCM/AlarmData

See 3GPP TS 32.615 [14]

The file header defined there is extended as follows (new parts marked by underlining>):
For delta synchronization of CM data:

```

<element name="fileHeaderDeltaSynchForCMData">
  <complexType>
    <attribute name="fileFormatVersion" type="string" use="required"/>
    <attribute name="senderName" type="string" use="optional"/>
    <attribute name="vendorName" type="string" use="optional"/>
    <!-- The content of the following element is a copy of the original
         request/response parameters -->
    <element name="inAndOutputParameter" minOccurs="0" maxOccurs="1">
      <complexType>
        <sequence>
          <attribute name="managerReference" type="string" use="optional"/>
          <attribute name="dataRequested" type="dsa:AlarmDataRequested" use="required"/>
          <attribute name="startSynchronizationPoint" type="dateTime" use="required"/>
          <attribute name="newSynchronizationPoint" type="dateTime" use="required"/>
        </sequence>
      </complexType>
    </element>
  </complexType>
</element>
<element name="fileHeaderDeltaSynchForCMData">
  <complexType>
    <sequence>
      <element name="fileHeader">
        <complexType>
          <attribute name="fileFormatVersion" type="string" use="required"/>
          <attribute name="senderName" type="string" use="optional"/>
          <attribute name="vendorName" type="string" use="optional"/>
        </complexType>
      </element>
      <!-- The content of the following element is a copy of the original
           request/response parameters -->
      <element name="inAndOutputParameter" minOccurs="0" maxOccurs="1">
        <complexType>
          <attribute name="dataRequested" type="dsc:CMDDataRequested" use="required"/>
          <attribute name="startSynchronizationPoint" type="dateTime" use="required"/>
          <attribute name="newSynchronizationPoint" type="dateTime" use="required"/>
          <attribute name="managerReference" type="string" use="optional"/>
        </complexType>
      </element>
      <element name="scope" type="nk:ScopeType" minOccurs="0"/>
    </sequence>
  </complexType>
</element>

```

For delta synchronization of alarm data:

```

<element name="fileHeaderDeltaSynchForCMData">
  <complexType>
    <attribute name="fileFormatVersion" type="string" use="required"/>
    <attribute name="senderName" type="string" use="optional"/>
    <attribute name="vendorName" type="string" use="optional"/>
    <!-- The content of the following element is a copy of the original
         request/response parameters -->
    <element name="inAndOutputParameter" minOccurs="0" maxOccurs="1">
      <complexType>
        <sequence>
          <attribute name="managerReference" type="string" use="optional"/>
          <attribute name="dataRequested" type="dsa:AlarmDataRequested" use="required"/>
          <attribute name="startSynchronizationPoint" type="dateTime" use="required"/>
          <attribute name="newSynchronizationPoint" type="dateTime" use="required"/>
        </sequence>
      </complexType>
    </element>
  </complexType>
</element>
<element name="fileHeaderDeltaSynchForAlarms">
  <complexType>
    <sequence>

```

```
<element name="fileHeader">
  <complexType>
    <attribute name="fileFormatVersion" type="string" use="required"/>
    <attribute name="senderName" type="string" use="optional"/>
    <attribute name="vendorName" type="string" use="optional"/>
  </complexType>
</element>
<!-- The content of the following element is a copy of the original
      request/response parameters -->
<element name="inAndOutputParameter" minOccurs="0" maxOccurs="1">
  <complexType>
    <attribute name="dataRequested" type="dsa:AlarmDataRequested" use="required"/>
    <attribute name="startSynchronizationPoint" type="dateTime" use="required"/>
    <attribute name="newSynchronizationPoint" type="dateTime" use="required"/>
    <attribute name="managerReference" type="string" use="optional"/>
  </complexType>
</element>
<element name="scope" type="nk:ScopeType" minOccurs="0"/>
</sequence>
</complexType>
</element>
```

4.2.2 XML element fileFooter

See 3GPP TS 32.615 [14]

4.3 Delta synchronisation IRP specific XML elements

For delta synchronization of CM data: Currently none, except those in clause 4.2 .

For delta synchronization of alarm data:

```
<element name="deltaAlarm" type="dsa:DeltaAlarm maxOccurs="unbounded"/>
```

of type

```
<complexType name="DeltaAlarm">  
  <choice>  
    <element ref="xa:NotifyNewAlarm"/>  
    <element ref="xa:NotifyChangedAlarm"/>  
    <element ref="xa:NotifyClearedAlarm"/>  
    <element ref="xa:NotifyComments"/>  
    <element ref="xa:NotifyAckStateChanged"/>  
  </choice>  
</complexType>
```

4.4 Delta synchronisation IRP XML File Name Conventions

For NL IRP XML File Name Conventions the generic file name definitions as specified by the FT IRP apply (see [3]).

Annex A (normative): Delta synchronization specific data file XML schemas

A.1 Delta synchronization specific data file XML schemas Generic Part (file name "deltaSynchGeneric.xsd")

```

<?xml version="1.0" encoding="UTF-8"?>

<!--
 3GPP TS 32.695 Delta Synchronisation IRP
 Delta synchronization specific data file XML schemas
 deltaSynchGeneric.xsd
-->

<schema
  targetNamespace=
"http://www.3gpp.org/ftp/specs/archive/32_series/32.395#deltaSynchGeneric"

  elementFormDefault="qualified"

  xmlns="http://www.w3.org/2001/XMLSchema"

  xmlns:dsg=
"http://www.3gpp.org/ftp/specs/archive/32_series/32.395#deltaSynchGeneric"

  xmlns:xe=
"http://www.3gpp.org/ftp/specs/archive/32_series/32.305#notification"
>

  <import
    namespace=
"http://www.3gpp.org/ftp/specs/archive/32_series/32.305#notification"
  />

  <!-- XML types specific for delta synchronization generic part -->

<simpleType name="DeltaSynchStatus">
  <restriction base="string">
    <enumeration value="Activated"/>
    <enumeration value="Deactivated"/>
  </restriction>
</simpleType>

<complexType name="NotifyStatusOfDeltaSynchChanged">
  <complexContent>
    <extension base="xe:Notification">
      <sequence>
        <element name="body">
          <complexType>
            <sequence>
              <element name="ManagerReference" type="string"/>
              <element name="DeltaSynchStatusForCMDData" type="dsg:DeltaSynchStatus"/>
              <element name="DeltaSynchStatusForAlarmData" type="dsg:DeltaSynchStatus"/>
            </sequence>
          </complexType>
        </element>
      </sequence>
    </extension>
  </complexContent>
</complexType>

<element name="NotifyStatusOfDeltaSynchChanged" type="dsg:NotifyStatusOfDeltaSynchChanged"/>

<simpleType name="DeltaSynchPointType">
  <restriction base="string">
    <enumeration value="DeltaSynchPointForAlarm"/>
    <enumeration value="DeltaSynchPointForCMDData"/>
  </restriction>

```

```
</restriction>
</simpleType>

<simpleType name="TriggeredByAgentOrManager">
  <restriction base="string">
    <enumeration value="IRPAgent"/>
    <enumeration value="IRPManager"/>
  </restriction>
</simpleType>

<complexType name="NotifyNewDeltaSynchPoint">
  <complexContent>
    <extension base="xe:Notification">
      <sequence>
        <element name="body">
          <complexType>
            <sequence>
              <element name="NewSynchPoint" type="dateTime"/>
              <element name="RequestedSynchPoint" type="dateTime"/>
              <element name="DeltaSynchPointType" type="dsg:DeltaSynchPointType"/>
              <element name="TriggeredByAgentOrManager" type="dsg:TriggeredByAgentOrManager"/>
              <element name="AgentOrManagerReference" type="string"/>
            </sequence>
          </complexType>
        </element>
      </sequence>
    </extension>
  </complexContent>
</complexType>

<element name="NotifyNewDeltaSynchPoint" type="dsg:NotifyNewDeltaSynchPoint"/>

</schema>
```

A.2 Delta synchronization specific data file XML schemas for CM data (file name "deltaSynchForCMDData.xsd")

```

<?xml version="1.0" encoding="UTF-8"?>

<!--
  3GPP TS 32.395 Delta Synchronisation IRP
  Delta synchronization specific data file XML schemas for CM data XML schema
  deltaSynchForCMDData.xsd
-->

<schema
  targetNamespace=
    "http://www.3gpp.org/ftp/specs/archive/32_series/32.395#deltaSynchForCMDData"

  elementFormDefault="qualified"

  xmlns="http://www.w3.org/2001/XMLSchema"

  xmlns:dsc=
    "http://www.3gpp.org/ftp/specs/archive/32_series/32.395#deltaSynchForCMDData"

  xmlns:xn=
    "http://www.3gpp.org/ftp/specs/archive/32_series/32.625#genericNrm"

  xmlns:nk=
    "http://www.3gpp.org/ftp/specs/archive/32_series/32.665#kernelNtf"
>

  <import
    namespace=
    "http://www.3gpp.org/ftp/specs/archive/32_series/32.625#genericNrm"
  />

  <import
    namespace=
    "http://www.3gpp.org/ftp/specs/archive/32_series/32.665#kernelNtf"
  />

  <!-- XML types specific for delta synchronization of CM data -->

  <simpleType name="CMDDataRequested">
    <restriction base="string">
      <enumeration value="DNsOnly"/>
      <enumeration value="CompleteDataSet"/>
    </restriction>
  </simpleType>

  <!--Delta synchronization for CM data file root XML element -->

  <element name="deltaSynchForCMDDataFile">
    <complexType>
      <sequence>

        <element name="fileHeaderDeltaSynchForCMDData">
          <complexType>
            <sequence>
              <element name="fileHeader">
                <complexType>
                  <attribute name="fileFormatVersion" type="string" use="required"/>
                  <attribute name="senderName" type="string" use="optional"/>
                  <attribute name="vendorName" type="string" use="optional"/>
                </complexType>
              </element>
              <!-- The content of the following element is a copy of the original
                request/response parameters -->
              <element name="inAndOutputParameter" minOccurs="0" maxOccurs="1">
                <complexType>

```

```
        <attribute name="dataRequested" type="dsc:CMDDataRequested" use="required"/>
        <attribute name="startSynchronizationPoint" type="dateTime" use="required"/>
        <attribute name="newSynchronizationPoint" type="dateTime" use="required"/>
        <attribute name="managerReference" type="string" use="optional"/>
      </complexType>
    </element>
    <element name="scope" type="nk:ScopeType" minOccurs="0"/>
  </sequence>
</complexType>
</element>

<element name="configData" maxOccurs="unbounded">
  <complexType>
    <choice>
      <element ref="xn:SubNetwork"/>
      <element ref="xn:MeContext"/>
      <element ref="xn:ManagedElement"/>
    </choice>
    <attribute name="dnPrefix" type="string" use="optional"/>
  </complexType>
</element>
<element name="fileFooter">
  <complexType>
    <attribute name="dateTime" type="dateTime" use="required"/>
  </complexType>
</element>
</sequence>
</complexType>
</element>
</schema>
```

A.3 Delta synchronization specific data file XML schemas for alarm data (file name "deltaSynchForAlarms.xsd")

```

<?xml version="1.0" encoding="UTF-8"?>

<!--
  3GPP TS 32.395 Delta Synchronisation IRP
  Delta synchronization specific data file XML schemas for alarm data XML schema
  deltaSynchForAlarmData.xsd
-->

<schema
  targetNamespace=
"http://www.3gpp.org/ftp/specs/archive/32_series/32.395#deltaSynchForAlarms"

  elementFormDefault="qualified"

  xmlns="http://www.w3.org/2001/XMLSchema"

  xmlns:dsa=
"http://www.3gpp.org/ftp/specs/archive/32_series/32.395#deltaSynchForAlarms"

  xmlns:nk=
"http://www.3gpp.org/ftp/specs/archive/32_series/32.665#kernelNtf"

  xmlns:xa=
"http://www.3gpp.org/ftp/specs/archive/32_series/32.111-5#alarmIRPNotif"
>

  <import
    namespace=
"http://www.3gpp.org/ftp/specs/archive/32_series/32.111-5#alarmIRPNotif"
  />

  <import
    namespace=
"http://www.3gpp.org/ftp/specs/archive/32_series/32.665#kernelNtf"
  />

  <!-- XML types specific for delta synchronization of alarm data -->

  <simpleType name="AlarmDataRequested">
    <restriction base="string">
      <enumeration value="AlarmIdsOnly"/>
      <enumeration value="CompleteAlarmInformation"/>
    </restriction>
  </simpleType>

  <complexType name="DeltaAlarm">
    <choice>
      <element ref="xa:NotifyNewAlarm"/>
      <element ref="xa:NotifyChangedAlarm"/>
      <element ref="xa:NotifyClearedAlarm"/>
      <element ref="xa:NotifyComments"/>
      <element ref="xa:NotifyAckStateChanged"/>
    </choice>
  </complexType>

  <!--Delta synchronization for alarm data file root XML element -->

  <element name="deltaSynchForAlarmDataFile">
    <complexType>
      <sequence>

        <element name="fileHeaderDeltaSynchForAlarms">
          <complexType>
            <sequence>
              <element name="fileHeader">

```

```
<complexType>
  <attribute name="fileFormatVersion" type="string" use="required"/>
  <attribute name="senderName" type="string" use="optional"/>
  <attribute name="vendorName" type="string" use="optional"/>
</complexType>
</element>
<!-- The content of the following element is a copy of the original
      request/response parameters -->
<element name="inAndOutputParameter" minOccurs="0" maxOccurs="1">
  <complexType>
    <attribute name="dataRequested" type="dsa:AlarmDataRequested" use="required"/>
    <attribute name="startSynchronizationPoint" type="dateTime" use="required"/>
    <attribute name="newSynchronizationPoint" type="dateTime" use="required"/>
    <attribute name="managerReference" type="string" use="optional"/>
  </complexType>
</element>
<element name="scope" type="nk:ScopeType" minOccurs="0"/>
</sequence>
</complexType>
</element>
<element name="deltaAlarm" type="dsa:DeltaAlarm" maxOccurs="unbounded"/>
<element name="fileFooter">
  <complexType>
    <attribute name="dateTime" type="dateTime" use="required"/>
  </complexType>
</element>
</sequence>
</complexType>
</element>
</schema>
```

Annex B (informative):
Void

Annex C (informative): Change history

Change history								
Date	TSG #	TSG Doc.	CR	R	Subject/Comment	Cat	Old	New
Jun 2007	SA_36	SP-070286	--	--	Submitted to SA#36 for Approval	--	1.0.0	7.0.0
Dec 2007	SA_38	SP-070732	0001	--	R7 CR 32.395-700 correction of compilation errors in XML schema	F	7.0.0	7.1.0
Dec 2007	SA_38	SP-070732	0002	--	Correct the Delta synchronization specific data file XML schema	F	7.0.0	7.1.0
Dec 2008	SA_42	--	--	--	Upgrade to Release 8	--	7.1.0	8.0.0
Dec 2009	SA_46	SP-090719	0003		Discontinue from Rel-9 onwards the XML schema extraction and storage	F	8.0.0	9.0.0
Dec 2011	SA_54	SP-110703	0006	--	Correct syntax errors in XML schemas	A	9.0.0	9.1.0