# 3GPP TS 32.603 V9.1.0 (2010-09)

Technical Specification

3rd Generation Partnership Project;
Technical Specification Group Services and System Aspects;
Telecommunication management;
Configuration Management (CM);
Basic CM Integration Reference Point (IRP);
Common Object Request Broker Architecture (CORBA)
Solution Set (SS)
(Release 9)





This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification. Specifications and reports for implementation of the 3GPP TM system should be obtained via the 3GPP Organizational Partners' Publications Offices.

Keywords

UMTS, management, CORBA, architecture

#### 3GPP

Postal address

3GPP support office address
650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

http://www.3gpp.org

#### Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© 2010, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TTA, TTC). All rights reserved.

UMTS<sup>TM</sup> is a Trade Mark of ETSI registered for the benefit of its members  $3GPP^{TM}$  is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners LTE<sup>TM</sup> is a Trade Mark of ETSI currently being registered for the benefit of its Members and of the 3GPP Organizational Partners GSM® and the GSM logo are registered and owned by the GSM Association

# Contents

Forev	vord	4
Introd	luction	4
1	Scope	5
2	References	5
3 3.1	Definitions and abbreviations	
3.2	Abbreviations	
4	IRP document version number string	6
5 5.1 5.2	Architectural features  Filter language  Syntax for Distinguished Names and Versions	6
6 6.1 6.2 6.3	Mapping  General mappings  Operation mapping  Operation parameter mapping	7 7
7	Void	.10
Anne	x A (normative): CORBA IDL, Access Protocol	.11
A.1	IDL specification (file name "BasicCMIRPConstDefs.idl")	.11
A.2	IDL specification (file name "BasicCMIRPSystem.idl")	.14
Anne	x B (informative): Change history	.20

#### **Foreword**

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

#### Introduction

The present document is part of a TS-family covering the 3<sup>rd</sup> Generation Partnership Project: Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

32.601:	"Configuration Management (CM); Basic CM Integration Reference Point (IRP); Requirements"
32.602:	"Configuration Management (CM); Basic CM Integration Reference Point (IRP); Information Service (IS)"
32.603:	"Configuration Management (CM); Basic CM Integration Reference Point (IRP); Common Object Request Broker Architecture (CORBA) Solution Set (SS)"

Configuration Management (CM), in general, provides the operator with the ability to assure correct and effective operation of the 3G network as it evolves. CM actions have the objective to control and monitor the actual configuration on the Network Elements (NEs) and Network Resources (NRs), and they may be initiated by the operator or by functions in the Operations Systems (OSs) or NEs.

CM actions may be requested as part of an implementation programme (e.g. additions and deletions), as part of an optimisation programme (e.g. modifications), and to maintain the overall Quality of Service (QoS). The CM actions are initiated either as single actions on single NEs of the 3G network, or as part of a complex procedure involving actions on many resources/objects in one or several NEs.

# 1 Scope

The purpose of this *Basic Configuration Management (CM) IRP: CORBA Solution Set* is to define the mapping of the Basic CM IRP: IS (see 3GPP TS 32.602 [4]) to the protocol specific details necessary for implementation of this IRP in a CORBA/IDL environment.

This document defines NRM independent data types and methods.

This Solution Set specification is related to 3G TS 32.602 V8.1.X.

#### 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document.
- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
- [4] 3GPP TS 32.602: "Telecommunication management; Configuration Management (CM); Basic CM Integration Reference Point (IRP) Information Service (IS)".
- [5] 3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects".
- [6] OMG Notification Service, Version 1.0.
- [7] OMG CORBA services: Common Object Services Specification, Update: November 22, 1996.
- [8] The Common Object Request Broker: Architecture and Specification (for specification of valid version, see [1]).
- [9] 3GPP TS 32.303: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP); Common Object Request Broker Architecture (CORBA) Solution Set (SS)".
- [10] 3GPP TS 32.312: "Telecommunication management; Generic Integration Reference Point (IRP) management; Information Service (IS)".
- [11] 3GPP TS 32.663: "Telecommunication management; Configuration Management (CM); Kernel CM Integration Reference Point (IRP); Common Object Request Broker Architecture (CORBA) Solution Set (SS)".

#### 3 Definitions and abbreviations

#### 3.1 Definitions

For terms and definitions please refer to 3GPP TS 32.101 [1], 3GPP TS 32.102 [2], 3GPP TS 32.600 [3] and 3GPP TS 32.602 [4].

#### 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CORBA Common Object Request Broker Architecture

DN Distinguished Name IS Information Service

IDL Interface Definition Language (OMG)

IRP Integration Reference Point

MO Managed Object
MOC Managed Object Class
NRM Network Resource Model
OMG Object Management Group

SS Solution Set

# 4 IRP document version number string

The IRP document version number (sometimes called "IRPVersion" or "SS version number") string is used to identify this specification. The string is derived using a rule described in 3GPP TS 32.312: [10].

This string (or sequence of strings, if more than one version is supported) is returned in getBasicCmIRPVersion method.

#### 5 Architectural features

The overall architectural feature of Basic Configuration Management IRP is specified in 3GPP TS 32.602 [4]. This clause specifies features that are specific to the CORBA SS.

## 5.1 Filter language

The filter language used in the SS is the Extended Trader Constraint Language (see OMG Notification Service [6]). IRPAgents may throw a FilterComplexityLimit exception when a given filter is too complex. However, for 3GPP Release 99 an "empty filter" shall be used i.e. a filter that satisfies all MOs of a scoped search (this does not affect the filter for notifications as defined in the Notification IRP – see 3GPP TS 32.303 [9]).

# 5.2 Syntax for Distinguished Names and Versions

The format of a Distinguished Name is defined in 3GPP TS 32.300 [5].

The version of this IRP is represented as a string (see also clause 4).

# 6 Mapping

#### 6.1 General mappings

The IS parameter name managedObjectInstance is mapped into DN.

Attributes modelling associations as defined in the NRM (here also called "reference attributes") are in this SS mapped to attributes. The names of the reference attributes in the NRM are mapped to the corresponding attribute names in the MOC. When the cardinality for an association is 0..1 or 1..1 the datatype for the reference attribute is defined as an MORe ference. The value of an MO reference contains the distinguished name of the associated MO. When the cardinality for an association allows more than one referred MO, the reference attribute will be of type MORe ferenceSet, which contains a sequence of MO references.

If a reference attribute is changed, an Attribute Value Change notification (see TS 32.663 [11]) is emitted.

#### 6.2 Operation mapping

The Basic CM IRP: IS (see 3GPP TS 32.602 [4]) defines semantics of operation visible across the Basic Configuration Management IRP. Table 1 indicates mapping of these operations to their equivalents defined in this SS.

SS Method Qualifier **IS Operation** (3GPP TS 32.602 [4]) BasicCmIrpOperations::find\_managed\_objects getMoAttributes M BasicCmInformationIterator::next\_basic\_cm\_informations getContainment BasicCmIrpOperations::find\_managed\_objects 0 BasicCmInformationIterator::next\_basic\_cm\_informations cancelOperation BasicCmInformationIterator::destroy 0 createMo BasicCmIrpOperations::create managed object 0 deleteMo BasicCmIrpOperations::delete\_managed\_objects 0 DeleteResultIterator::next\_basic\_cm\_informations DeleteResultIterator::next delete errors setMoAttributes BasicCmIrpOperations::modify\_managed\_objects 0 ModifyResultIterator::next\_basic\_cm\_informations ModifyResultIterator::next\_modification\_errors

Table 1: Mapping from IS Operation to SS equivalents

## 6.3 Operation parameter mapping

The Basic CM IRP: IS (see 3GPP TS 32.602 [4]) defines semantics of parameters carried in operations across the Basic Configuration Management IRP. Tables 2 through 8 indicate the mapping of these parameters, as per operation, to their equivalents defined in this SS.

The SS operation find\_managed\_objects is equivalent to the IS operation getMoAttributes when called with ResultContents set to NAMES\_AND\_ATTRIBUTES. Iterating the BasicCmInformationIterator is used to fetch the result.

Table 2: Mapping from IS getMoAttributes parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
invokeldentifier	- (No equivalence)	-
invokeldentifierOut	Return value of type BasicCmInformationIterator	М
baseObjectInstance	GenericIRPManagementConstDefs::DN base_object	М
scope	SearchControl search_control (SearchControl.type and SearchControl.level)	M
filter	SearchControl search_control (SearchControl.filter)	М
attributeListIn	AttributeNameSet requested_attributes	M
managedObjectClass managedObjectInstance attributeListOut	Return value of type BasicCmInformationIterator - parameter out ResultSet fetched_elements of method next_basic_cm_informations	M
status	Exceptions: FindManagedObjects, GenericIRPManagementSystem::InvalidParameter, UndefinedMOException, IllegalDNFomatException, UndefinedScopeException, IllegalScopeTypeException, IllegalScopeLevelException, IllegalFilterFomatException, FilterComplexityLimit	М

The SS operation find\_managed\_objects is equivalent to the IS operation getContainment when called with ResultContents set to NAMES. Iterating the BasicCmInformationIterator is used to fetch the result.

Table 3: Mapping from IS getContainment parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
invokeldentifier	- (No equivalence)	-
invokeldentifierOut	Return value of type BasicCmInformationIterator	М
baseObjectInstance	GenericIRPManagementConstDefs::DN base_object	M
scope	SearchControl search_control (SearchControl.type and SearchControl.level)	0
Not specified in IS	SearchControl search_control (SearchControl.filter)	М
containment	Return value of type BasicCmInformationIterator - parameter out ResultSet fetched_elements of method next_basic_cm_informations	М
status	Exceptions: FindManagedObjects, GenericIRPManagementSystem::OperationNotSupported, GenericIRPManagementSystem::ParameterNotSupported, GenericIRPManagementSystem::InvalidParameter, GenericIRPManagementSystem::ValueNotSupported, UndefinedMOException, IllegalDNFomatException, UndefinedScopeException, IllegalScopeTypeException, IllegalScopeLeveIException, IllegalFilterFomatException, FilterComplexityLimit	M

Table 4: Void

Table 5: Mapping from IS cancelOperation parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
invokeldentifier	- (Not applicable, the BasicCmInformationIterator instance identifies the ongoing	M
	operation)	
status	Exceptions:	M
	GenericIRPManagementSystem::OperationNotSupported,	
	DestroyException	

Table 6: Mapping from IS createMo parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
managedObjectClass managedObjectInstance	GenericIRPManagementConstDefs::DN object_name	M
referenceObjectInstance	GenericIRPManagementConstDefs::DN reference_object	0
attributeListIn attributeListOut	GenericIRPManagementConstDefs::MoAttributeSet attributes	M
status	AttributeErrorSeq attribute_errors Exceptions: CreateManagedObject, GenericIRPManagementSystem::OperationNotSupported, GenericIRPManagementSystem::ParameterNotSupported, GenericIRPManagementSystem::InvalidParameter, UndefinedMOException, IllegalDNFormatException, DuplicateMO, CreateNotAllowed, ObjectClassMismatch, NoSuchObjectClass, ParentObjectDoesNotExist	M

Table 7: Mapping from IS deleteMo parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
baseObjectInstance	GenericIRPManagementConstDefs::DN base_object	M
scope	SearchControl search_control (SearchControl.type and SearchControl.level)	M
filter	SearchControl search_control (SearchControl.filter)	M
deletionList	Return value of type DeleteResultIterator - parameter out ResultSet fetched_elements of method next_basic_cm_informations	M
status	Return value of type DeleteResultIterator - parameter out DeleteErrorSeq fetched_delete_errors of method next_delete_errors  Exceptions: DeleteManagedObjects, GenericIRPManagementSystem::OperationNotSupported, GenericIRPManagementSystem::InvalidParameter, UndefinedMoException, IllegalDNFormatException, UndefinedScopeException, IllegalScopeTypeException, IllegalScopeLeveIException, IllegalFilterFormatException, FilterComplexityLimit	М

Table 8: Mapping from IS setMoAttributes parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
baseObjectInstance	GenericIRPManagementConstDefs::DN base_object	M
scope	SearchControl search_control (SearchControl.type and SearchControl.level)	M
filter	SearchControl search_control (SearchControl.filter)	M
modificationList	AttributeModificationSet modifications	M
modificationListOut	Return value of type ModifyResultIterator - parameter out ResultSet fetched_elements of method next_basic_cm_informations	М
status	Return value of type ModifyResultIterator - parameter out ModifyAttributeErrors Seq fetched_modify_errors of method next_modify_errors Exceptions: ModifyManagedObjects, GenericIRPManagementSystem::OperationNotSupported, GenericIRPManagementSystem::InvalidParameter, UndefinedMoException, IllegalDNFomatException, UndefinedScopeException, IllegalScopeTypeException, IllegalScopeLeveIException, IllegalFilterFomatException, FilterComplexityLimit	M

Table 9: Void

Table 10: Void

7 Void

# Annex A (normative): CORBA IDL, Access Protocol

#### A.1 IDL specification (file name "BasicCMIRPConstDefs.idl")

```
//File: BasicCMIRPConstDefs.idl
#ifndef _BASIC_CM_IRP_CONST_DEFS_IDL_
#define _BASIC_CM_IRP_CONST_DEFS_IDL_
#include <GenericIRPManagementConstDefs.idl>
// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"
/* ## Module: BasicCMIRPConstDefs
This module contains commonly used definitions for BasicCMIRP.
module BasicCMIRPConstDefs
    * Defines the name of a Managed Object Class
   typedef string MOClass;
   /**
    ^{\star} In this version the only allowed filter value is "TRUE" i.e. a filter that
    * matches everything.
   typedef string Filter;
    * ResultContents is used to tell how much information to get back
    * from the find managed objects operation.
    * NAMES: Used to get only Distinguished Name
              for MOs.
             The name contains both the MO class
             and the names of all superior objects in the naming
             tree.
    * NAMES AND ATTRIBUTES: Used to get both NAMES plus
        MO attributes (all or selected).
   enum ResultContents
   {
      NAMES_AND_ATTRIBUTES
   } :
    * ScopeType defines the kind of scope to use in a search
    ^{\star} together with SearchControl.level, in a SearchControl value.
    * SearchControl.level is always >= 0. If a level is bigger than the
    * depth of the tree there will be no exceptions thrown.
   enum ScopeType
      BASE ONLY,
      BASE NTH LEVEL,
      BASE_SUBTREE,
      BASE ALL
   };
    ^{\star} SearchControl controls the find_managed_object search,
    * the type of scope ("type" field),
    * the level of scope ("level" field), level 0 means the "baseObject",
         level 1 means baseobject including its sub-ordinates etc..
```

```
* the filter ("filter" field),
 * the result type ("contents" field).
 * The type, level and contents fields are all mandatory.
 * The filter field contains the filter expression.

* The string "TRUE" indicates "no filter",
 * i.e. a filter that matches everything.
 */
struct SearchControl
   ScopeType type;
   unsigned long level;
   Filter filter;
   ResultContents contents;
};
struct Result
   GenericIRPManagementConstDefs::DN mo;
   GenericIRPManagementConstDefs::MOAttributeSet attributes;
typedef sequence <Result> ResultSet;
^{\star} AttributeErrorCategory defines the categories of errors, related to
* attributes, that can occur during creation or modification of MOs.
 ^{\star} NO_SUCH_ATTRIBUTE: The specified attribute does not exist.
 * INVALID_ATTRIBUTE_VALUE: The specified attribute value is not valid.
* MISSING_ATTRIBUTE_VALUE: An attribute value is required but none was * provided and no default value is defined for the attribute.
 * INVALID MODIFY OPERATOR: The specified modify operator is not valid
    (e.g. operator ADD_VALUES applied to a non multi-valued attribute
    or operator SET TO DEFAULT applied where no default value is defined).
 * MODIFY NOT ALLOWED: The modification of the attribute is not allowed.
 * MODIFY FAILED: The modification failed because of an unspecified reason.
enum AttributeErrorCategory
{
   NO SUCH ATTRIBUTE,
   INVALID ATTRIBUTE VALUE,
   MISSING ATTRIBUTE VALUE,
   INVALID MODIFY OPERATOR,
   MODIFY NOT ALLOWED,
  MODIFY FAILED
} :
* DeleteErrorCategory defines the categories of errors that can occur
^{\star} during deletion of MOs.
* SUBORDINATE OBJECT: The MO cannot be deleted due to subordinate MOs.
* DELETE NOT ALLOWED: The deletion of the MO is not allowed.
 ^{\star} DELETE FAILED: The deletion failed because of an unspecified reason.
*/
enum DeleteErrorCategory
   SUBORDINATE_OBJECT, DELETE NOT ALLOWED,
   DELETE FAILED
};
^{\star} AttributeError represents an error, related to an attribute, that occured
* during creation or modification of MOs.
* It contains:
 * - the name of the indicted attribute ("name" field),
 * - the category of the error ("error" field),
 * - optionally, the indicted attribute value ("value" field),
 * - optionally, additional details on the error ("reason" field).
 */
struct AttributeError
   GenericIRPManagementConstDefs::MOAttributeName name;
   AttributeErrorCategory error;
   GenericIRPManagementConstDefs::MOAttributeValue value;
   string reason;
```

};

```
};
  typedef sequence <AttributeError> AttributeErrorSeq;
   * DeleteError represents an error that occured during deletion of MOs.
   * It contains:
   * - the distinguished name of the indicted MO ("object name" field),
   * - the category of the error ("error" field),
   * - optionally, additional details on the error ("reason" field).
   */
  struct DeleteError
     GenericIRPManagementConstDefs::DN object name;
     DeleteErrorCategory error;
     string reason;
  typedef sequence <DeleteError> DeleteErrorSeq;
   ^{\star} ModifyAttributeErrors represents errors that occured during
   * modification of attributes of a MO.
   * It contains:
   * - the distinguished name of the indicted MO ("object name" field),
   * - a sequence containing the attribute errors ("errors" field).
   */
  struct ModifyAttributeErrors
      GenericIRPManagementConstDefs::DN object name;
      AttributeErrorSeq errors;
  typedef sequence <ModifyAttributeErrors> ModifyAttributeErrorsSeq;
  typedef sequence < GenericIRPManagementConstDefs::MOAttributeName> AttributeNameSet;
   \mbox{\ensuremath{^{\star}}} ModifyOperator defines the way in which an attribute value is to be
   ^{\star} applied to an attribute in a modification of MO attributes.
   * REPLACE: replace the current value with the provided value
   ^{\star} ADD_VALUES: for a multi-valued attribute, add the provided values to the
       current list of values
   * REMOVE VALUES: for a multi-valued attribute, remove the provided values
        from the current list of values
    * SET TO DEFAULT: set the attribute to its default value
   */
  enum ModifyOperator
  {
     REPLACE.
     ADD VALUES,
     REMOVE_VALUES,
SET TO DEFAULT
  };
   ^{\star} AttributeModification defines an attribute value and the way it is to
   * be applied to an attribute in a modification of MO attributes.
    * It contains:
   \star - the name of the attribute to modify ("name" field),
   * - the value to apply to this attribute ("value" field),
   \star - the way the attribute value is to be applied to the attribute
        ("operator" field).
   */
  struct AttributeModification
      GenericIRPManagementConstDefs::MOAttributeName name;
     {\tt GenericIRPManagementConstDefs::} {\tt MOAttributeValue} \ \ {\tt value;}
     ModifyOperator operator;
  typedef sequence <AttributeModification> AttributeModificationSet;
#endif // _BASIC_CM_IRP_CONST_DEFS_IDL_
```

# A.2 IDL specification (file name "BasicCMIRPSystem.idl")

```
//File: BasicCMIRPSystem.idl
#ifndef _BASIC_CM_IRP_SYSTEM_IDL_
#define _BASIC_CM_IRP_SYSTEM_IDL_
#include <GenericIRPManagementSystem.idl>
#include <GenericIRPManagementConstDefs.idl>
#include <BasicCMIRPConstDefs.idl>
// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"
module BasicCmIRPSystem
   exception IllegalFilterFormatException {
      string reason;
   exception IllegalDNFormatException {
     string reason;
   };
   exception IllegalScopeTypeException {
     string reason;
   exception IllegalScopeLevelException {
      string reason;
   exception UndefinedMOException {
      string reason;
   exception UndefinedScopeException {
     string reason;
   exception FilterComplexityLimit {
      string reason;
   exception DuplicateMO {};
   exception CreateNotAllowed {};
   exception ObjectClassMismatch {};
   exception NoSuchObjectClass {
      BasicCMIRPConstDefs::MOClass objectClass;
   exception ParentObjectDoesNotExist {};
    ^{\star} System otherwise fails to complete the operation. System can provide
    \star reason to qualify the exception. The semantics carried in reason
    * is outside the scope of this IRP.
   exception NextBasicCmInformations { string reason; };
   exception NextDeleteErrors { string reason; };
   exception NextModifyErrors { string reason; };
   exception DestroyException { string reason; };
   exception GetBasicCmIRPVersion { string reason; };
   exception GetBasicCmIRPOperationProfile { string reason; };
   exception GetBasicCmIRPNotificationProfile { string reason; };
   exception FindManagedObjects { string reason; };
   exception CreateManagedObject { string reason; };
   exception DeleteManagedObjects { string reason; };
   exception ModifyManagedObjects { string reason; };
   The BasicCmInformationIterator is used to iterate through a snapshot of
   Managed Object Information when IRPManager invokes find managed objects.
   IRPManager uses it to pace the return of Managed Object Information.
   IRPAgent controls the life-cycle of the iterator. However, a destroy
   operation is provided to handle the case where IRPManager wants to stop
   the iteration procedure before reaching the last iteration.
```

```
interface BasicCmInformationIterator
{
   This method returns between 1 and "how many" Managed Object information.
   The IRPAgent may return less than "how many" items even if there are
   more items to return. "how many" must be non-zero. Return TRUE if there
   may be more Managed Object information to return. Return FALSE if there
   are no more Managed Object information to be returned.
   If FALSE is returned, the IRPAgent will automatically destroy the
   iterator.
   @parm how many how many elements to return in the "fetched elements" out
   parameter.
   @parm fetched elements the elements.
   @returns A boolean indicating if any elements are returned.
  "fetched_elements" is empty when the BasicCmInformationIterator is
    emptv.
   boolean next_basic_cm_informations (
      in unsigned short how many,
      out BasicCMIRPConstDefs::ResultSet fetched elements
   raises (
      NextBasicCmInformations,
      GenericIRPManagementSystem::InvalidParameter,
      GenericIRPManagementSystem::OperationNotSupported);
   This method destroys the iterator.
   void destroy ()
   raises (
      DestroyException,
      GenericIRPManagementSystem::OperationNotSupported);
}; // end of BasicCmInformationIterator
The DeleteResultIterator is used to iterate through the list of deleted MOs
when IRPManager invokes method "delete managed objects".
IRPManager uses it to pace the return of Managed Object Information.
IRPAgent controls the life-cycle of the iterator. However, a destroy
operation is provided to handle the case where IRPManager wants to stop
the iteration procedure before reaching the last iteration.
interface DeleteResultIterator : BasicCmInformationIterator
{
   Inherited method "next basic cm informations" has the same behaviour as
   for interface BasicCmInformationIterator, except that:
   - The Managed Object information returned in parameter
     "fetched elements" contains only the DNs of the deleted MOs
     (no attributes are returned).
   - If FALSE is returned, the IRPAgent will not automatically destroy the
     iterator.
   */
   This method returns between 0 and "how many" deletion errors. The
   IRPAgent may return less than "how_many" items even if there are more
   items to return. "how many" must be non-zero. Return TRUE if there are
   more deletion errors to return. Return FALSE if there are no more
   deletion errors to be returned.
   If FALSE is returned and last call to inherited method "next_basic_cm_informations" also returned FALSE (i.e. no more Managed
   Object information to be returned), the IRPAgent will automatically
   destroy the iterator.
   \ensuremath{\texttt{Qparm}} how_many: how many deletion errors to return in the
    "fetched delete errors" out parameter.
   @parm fetched delete errors: the deletion errors.
   @returns: a boolean indicating if any deletion errors are returned.
```

```
boolean next delete errors (
      in unsigned short how many,
      out BasicCMIRPConstDefs::DeleteErrorSeq fetched_delete_errors
   raises (
      NextDeleteErrors,
      GenericIRPManagementSystem::InvalidParameter);
}; // end of DeleteResultIterator
The ModifyResultIterator is used to iterate through the list of modified MOs when IRPManager invokes method "modify_managed_objects".
IRPManager uses it to pace the return of Managed Object Information.
IRPAgent controls the life-cycle of the iterator. However, a destroy
operation is provided to handle the case where IRPManager wants to stop
the iteration procedure before reaching the last iteration.
\verb|interface ModifyResultIterator : BasicCmInformationIterator|\\
   Inherited method "next basic cm informations" has the same behaviour as
   for interface BasicCmInformationIterator, except that:
   - The Managed Object information returned in parameter
     "fetched elements" contains DNs and attributes of the modified MOs.
   - If FALSE is returned, the IRPAgent will not automatically destroy the
     iterator.
   This method returns between 0 and "how_many" modification errors. The IRPAgent may return less than "how_many" items even if there are more
   items to return. "how many" must be non-zero. Return TRUE if there are
   more modification errors to return. Return FALSE if there are no more
   modification errors to be returned.
   If FALSE is returned and last call to inherited method \,
   "next basic cm informations" also returned FALSE (i.e. no more Managed
   Object information to be returned), the IRPAgent will automatically
   destroy the iterator.
   @parm how_many: how many modification errors to return in the
    "fetched modify errors" out parameter.
   @parm fetched modify errors: the modification errors.
   \mbox{\tt @returns:}\ \mbox{\tt a boolean indicating if any modification errors are returned.}
   boolean next modification errors (
      in unsigned short how_many,
      out BasicCMIRPConstDefs::ModifyAttributeErrorsSeq
         fetched modify errors
   raises (
      NextModifyErrors,
      GenericIRPManagementSystem::InvalidParameter);
}; // end of ModifyResultIterator
 * The BasicCmIrpOperations interface.
  * Supports a number of Resource Model versions.
interface BasicCmIrpOperations : GenericIRPManagementSystem::
    GenericIRPManagement
{
    * Performs a containment search, using a SearchControl to
    * control the search and the returned results.
    * All MOs in the scope constitute a set that the filter works on.
    * The result BasicCmInformationIterator contains all matched MOs,
    ^{\star} with the amount of detail specified in the SearchControl.
    * For the special case when no managed objects are matched in
```

```
* find managed objects, the BasicCmInformationIterator will be returned.
 * Executing the next basicCmInformations in the
 * BasicCmInformationIterator will return FALSE for
 * completion.
 * @parm base object The start MO in the containment tree.
  @parm search control the SearchControl to use.
  Oparm requested attributes defines which attributes to get.
     If this parameter is empty (""), all attributes shall
     be returned. In this version this is the only supported semantics.
     Note that this argument is only
     relevant if ResultContents in the search control is
     specifed to NAMES AND ATTRIBUTES.
 * @raises GenericIRPManagementSystem::ValueNotSupported if a valid but
 * unsupported parameter value is passed. E.g. the contents
 ^{\star} field in the searchcontrol parameter contains the value NAMES and
 * the optional getContainment IS operation is not supported.
 * @raises UndefinedMOException The MO does not exist.
 * @raises IllegalDNFormatException The dn syntax string is
 malformed.
 * @raises IllegalScopeTypeException The ScopeType in scope contains
 * an illegal value.
 * @raises IllegalScopeLevelException The scope level is negative
 * (<0).
 * @raises IllegalFilterFormatException The filter string is
 * malformed.
 * @raises FilterComplexityLimit if the filter syntax is correct,
    but the filter is too complex to be processed by the IRPAgent.
 * @see SearchControl
 * @see BasicCmInformationIterator
BasicCmInformationIterator find_managed_objects(
   in GenericIRPManagementConstDefs::DN base_object,
   in BasicCMIRPConstDefs::SearchControl search control,
   in BasicCMIRPConstDefs::AttributeNameSet requested attributes)
raises (
   FindManagedObjects,
   GenericIRPManagementSystem::ParameterNotSupported,
   GenericIRPManagementSystem::InvalidParameter,
   GenericIRPManagementSystem::ValueNotSupported,
   GenericIRPManagementSystem::OperationNotSupported,
   UndefinedMOException,
   Illegal DNFormatException,
   UndefinedScopeException,
   IllegalScopeTypeException,
   IllegalScopeLevelException,
   IllegalFilterFormatException,
   FilterComplexityLimit);
^{\star} Performs the creation of a MO instance in the MIB maintained
 * by the IRPAgent.
 ^{\star} @parm object name: the distinguished name of the MO to create.
 * @parm reference_object: the distinguished name of a reference MO.
 * @parm attributes: in input, initial attribute values for the MO to
    create; in output, actual attribute values of the created MO.
 * @parm attribute errors: errors, related to attributes, that caused the
     creation of the MO to fail.
 * @raises GenericIRPManagementSystem::OperationNotSupported: The operation
    is not supported.
 * @raises GenericIRPManagementSystem::ParameterNotSupported: An optional
    parameter is not supported.
 * @raises GenericIRPManagementSystem::InvalidParameter: An invalid
    parameter value has been provided.
 * @raises UndefinedMOException: The MO does not exist.
 ^{\star} @raises IllegalDNFormatException: The DN syntax string is malformed.
 * Graises DuplicateMO: A MO already exist with the same DN as the one
 * @raises CreateNotAllowed: The creation of the MO is not allowed.
 * @raises ObjectClassMismatch: The object class of the MO to create does
    not match with the object class of the provided reference MO.
 * @raises NoSuchObjectClass: The class of the object to create is not
    recognized.
 * @raises ParentObjectDoesNotExist: The parent MO instance of the
  ManagedEntity specified to be created does not exist.
```

```
void create managed object (
  in GenericIRPManagementConstDefs::DN object name,
   in GenericIRPManagementConstDefs::DN reference object,
   inout GenericIRPManagementConstDefs::MOAttributeSet attributes,
   out BasicCMIRPConstDefs::AttributeErrorSeq attribute errors
raises (
   CreateManagedObject,
   GenericIRPManagementSystem::OperationNotSupported,
   GenericIRPManagementSystem::ParameterNotSupported,
   GenericIRPManagementSystem::InvalidParameter,
   Undefined MOException.
   Illegal DN FormatException,
   DuplicateMO,
   CreateNotAllowed,
   ObjectClassMismatch,
   NoSuchObjectClass,
   ParentObjectDoesNotExist);
^{\star} Performs the deletion of one or more MO instances from the MIB
 * maintained by the IRPAgent, using a SearchControl to control the
 * instances to be deleted.
 ^{\star} All MOs in the scope constitute a set that the filter works on.
 * All matched MOs will be deleted by this operation.
 * The returned DeleteResultIterator is used to retrieve the DNs of the
 ^{\star} MOs deleted and the errors that may have occurred preventing deletion
 \star of some MOs.
 * For the special case when no managed objects are matched in
 * delete managed objects, the DeleteResultIterator will be returned.
 * Executing the next basicCmInformations in the DeleteResultIterator
 * will return FALSE for completion.
 * @parm base object: the start MO in the containment tree.
 * @parm search control: the SearchControl to use; field "contents" has no
    meaning here and shall be ignored.
 * @returns: a DeleteResultIterator (see above).
 * @raises GenericIRPManagementSystem::OperationNotSupported: The operation
    is not supported.
 * @raises GenericIRPManagementSystem::InvalidParameter: An invalid
    parameter value has been provided.
 * @raises UndefinedMOException: The MO does not exist.
 * @raises IllegalDNFormatException: The DN syntax string is malformed.
 * @raises IllegalScopeTypeException: The ScopeType in scope contains
     an illegal value.
 * @raises IllegalScopeLevelException: The scope level is negative (<0).
 * @raises IllegalFilterFormatException: The filter string is malformed.
 * @raises FilterComplexityLimit: The filter syntax is correct,
     but the filter is too complex to be processed by the IRPAgent.
* /
DeleteResultIterator delete managed objects (
  in GenericIRPManagementConstDefs::DN base object,
   in BasicCMIRPConstDefs::SearchControl search control
raises (
   DeleteManagedObjects,
   GenericIRPManagementSystem::OperationNotSupported,
  {\tt GenericIRPManagementSystem::InvalidParameter,}
   UndefinedMOException,
   Illegal DN FormatException,
   UndefinedScopeException,
   IllegalScopeTypeException,
   IllegalScopeLevelException,
   IllegalFilterFormatException,
   FilterComplexityLimit);
^{\star} Performs the modification of MO attributes. One or more MOs attributes
 * may be modified according to a SearchControl.
 ^{\star} All MOs in the scope constitute a set that the filter works on.
 * All matched MOs will have their attributes modified by this operation.
 * The returned ModifyResultIterator is used to retrieve the DNs of the
 * modified MOs together with the values of the modified attributes, and
 * the errors that may have occurred preventing modification of some
```

```
* attributes.
       * For the special case when no managed objects are matched in
       * modify managed objects, the ModifyResultIterator will be returned.
       * Executing the next_basicCmInformations in the ModifyResultIterator
       * will return FALSE for completion.
       * @parm base object: the start MO in the containment tree.
       * @parm search control: the SearchControl to use; field "contents" has no
          meaning here and shall be ignored.
       * @parm modifications: the values for the attributes to modify and
          the way those values are to be applied to the attributes.
       * @returns: a ModifyResultIterator (see above).
       * @raises GenericIRPManagementSystem::OperationNotSupported: The operation
          is not supported
       * @raises GenericIRPManagementSystem::InvalidParameter: An invalid
          parameter value has been provided
       * @raises UndefinedMOException: The MO does not exist.
       * @raises IllegalDNFormatException: The DN syntax string is malformed.
       * @raises IllegalScopeTypeException: The ScopeType in scope contains
          an illegal value.
       ^{\star} @raises IllegalScopeLevelException: The scope level is negative (<0).
       * @raises IllegalFilterFormatException: The filter string is malformed.
       * @raises FilterComplexityLimit: The filter syntax is correct,
          but the filter is too complex to be processed by the IRPAgent.
      ModifyResultIterator modify managed objects (
         in GenericIRPManagementConstDefs::DN base object,
         in BasicCMIRPConstDefs::SearchControl search control,
         in BasicCMIRPConstDefs::AttributeModificationSet modifications
        ModifyManagedObjects,
        GenericIRPManagementSystem::OperationNotSupported,
         GenericIRPManagementSystem::InvalidParameter,
         UndefinedMOException,
         Illegal DN FormatException,
         UndefinedScopeException,
         {\tt IllegalScopeTypeException,}
         IllegalScopeLevelException,
         IllegalFilterFormatException,
         FilterComplexityLimit);
   };
};
#endif // BASIC CM IRP SYSTEM IDL
```

# Annex B (informative): Change history

	Change history							
Date	TSG#	TSG Doc.	CR	Rev	Subject/Comment	Cat	Old	New
Jun 2001	S_12	SP-010283			Approved at TSG SA #12 and placed under Change Control		2.0.0	4.0.0
Sep 2001	S_13	SP-010476	0001		Correction of invokeldentifier usage	F	4.0.0	4.1.0
Mar 2002	S_15	SP-020019	0002		Correction of erroneous CORBA module names and mapping tables	F	4.1.0	4.2.0
Mar 2002	S_15	SP-020019	0003		Corrections to Basic CM IRP CORBA Solution Set IDLs	F	4.1.0	4.2.0
Mar 2002		SP-020038	0004		Addition of missing CORBA exception "ManagedGenericIRPSystem::ValueNotSupported" onto CORBA method "find_managed_objects"	F		4.2.0
Jun 2002	S_16	SP-020294	0005		Correcting IDL definitions of notification structured event Name Value pair names	F		4.3.0
Jul 2002		-			Updated the Version number (420->431) and the Date on the cover page			4.3.1
Sep 2002		SP-020483	0006		Add Active Basic CM feature - CORBA Solution Set	В		5.0.0
Mar 2003	S_19	SP-030139	0007		Add CORBA equivalents to IS operations "get{Operation Notification}Profile" - alignment with 32.602 & 32.312	F	5.0.0	5.1.0
Mar 2003		SP-030139	8000		Correction of IDL errors	F		5.1.0
Mar 2003	S_19	SP-030144	0009		Add description for notifications of each activeCM operation and one exception for createMO - alignment with 32.602, Information Service	F	5.0.0	5.1.0
Jun 2003	S_20	SP-030279	0010		Alignment with Basic CM IRP information service (32.602) - add one exception for the operation createMO	F	5.1.0	5.2.0
Mar 2004	S_23	SP-040105			Automatic upgrade to Rel-6 (no CR)		5.2.0	6.0.0
Sep 2004	S_25	SP-040567	0012		Removal of Rules for NRM extensions - Align with 32.622 (Generic NRM IS)	Α	6.0.0	6.1.0
Sep 2004	S_25	SP-040566	0014		Removal of unused/duplicate definition of types MOReference and MOReferenceSet	Α	6.0.0	6.1.0
Dec 2004	S_26	SP-040806	0015		Align the IDL style in the CORBA SS with the IDL Style Guide in 32.150	F	6.1.0	6.2.0
Mar 2005	S_27	SP-050044	0016		IDL incompliant to the style guide	F	6.2.0	6.3.0
Mar 2005	S_27	SP-050044	0017		Generic System Context, update of reference to IS specification	F	6.2.0	6.3.0
Apr 2005					Changed back TS Title from Bulk (v630) to Basic (620); erroneously changed with corrupted TS cover.		6.3.0	6.3.1
Sep 2005	SA_29	SP-050461	0018		Align the CORBA SS IDL with TS 32.150 Style Guide	F	6.3.1	6.4.0
	SA_36				Automatic upgrade to Rel-7 (no CR) at freeze of Rel-7. Deleted reference to CMIP SS, discontinued from R7 onw ards.		6.1.0	7.0.0
Dec 2008	SA_42				Upgrade to Release 8		7.0.0	8.0.0
Dec 2009	SA_46	SP-090718	0020		Increase the linked IS version by the CR for IS to clarify scope parameters for getMoAttributes operation	F	8.0.0	8.1.0
Dec 2009	SA_46	SP-090719	0019		Use the inherited ManagedGenericIRP methods	F	8.1.0	9.0.0
Sep 2010	SA_49	SP-100488	0021		Correct the data type 'MOAttributeName' in IDL specification	F	9.0.0	9.1.0