

3GPP TS 32.623-4 V2.0.0 (2001-06)

Technical Specification

**3rd Generation Partnership Project;
Technical Specification Group Services and System Aspects;
3G Configuration Management:
GERAN Network Resources IRP: CMIP Solution Set;
(Release 4)**



The present document has been developed within the 3rd Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP.

The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification. Specifications and reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organizational Partners' Publications Offices.

Keywords

Configuration Management

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2001, 3GPP Organizational Partners (ARIB, CWTS, ETSI, T1, TTA, TTC).
All rights reserved.

Contents

Foreword	5
Introduction	5
1 Scope	7
2 References.....	7
3 Definitions, symbols and abbreviations	7
3.1 Definitions	7
3.2 Abbreviations	8
4 Basic aspects	8
4.1 Explanation	8
4.2 Mapping.....	8
4.2.1 Mapping of MOCs	8
4.2.2 Mapping of Attributes.....	9
5 GDMO Definitions	9
5.1 Managed Object Classes.....	9
5.1.1 bssFunction.....	9
5.1.2 btsSiteMgr.....	9
5.1.3 gsmCell.....	10
5.1.4 externalGs mCell	10
5.1.5 gsmRelation	10
5.2 Packages	10
5.2.1 bssFunctionBasicPackage	10
5.2.2 btsSiteMgrBasicPackage	11
5.2.3 btsSiteMgrGeoPositionPackage	11
5.2.4 gsmCellBasicPackage	11
5.2.5 gsmCellMandatoryPackage	12
5.2.6 gsmCellOptionalPackage	12
5.2.7 externalGs mCellBasicPackage.....	13
5.2.8 externalGs mCellMandatoryPackage	13
5.2.9 gsmRelationBasicPackage	13
5.2.10 gsmRelationOptionalPackage	14
5.3 Attributes	14
5.3.1 bssFunctionId	14
5.3.2 btsSiteMgrId.....	14
5.3.3 longitude.....	15
5.3.4 latitude	15
5.3.5 gsmCellId	15
5.3.6 cellIdentity	15
5.3.7 racc	16
5.3.8 gsmRelationId	16
5.3.9 externalGs mCellId	16
5.3 Name Binding.....	17
5.3.1 bssFunction - managedElement	17
5.3.2 btsSiteMgr - bssFunction	17
5.3.3 gsmCell - btsSiteMgr.....	17
5.3.4 gsmRelation - gsmCell	18
5.3.5 externalGs mCell - subNetwork.....	18
5.3.6 vsDataContainer - bssFunction	19
5.3.7 vsDataContainer - btsSiteMgr.....	19
5.3.8 vsDataContainer - gsmCell	19
5.3.9 vsDataContainer - gsmRelation	20

6 ASN.1 Definitions21

Annex A (informative): Change history22

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

Due to the growing number of specifications to model new services and Resource Models for Configuration Management (CM), as well as the expected growth in size of each of them from 3GPP Release 4 onwards, a new structure of the specifications is already needed in Release 4. This structure is needed for several reasons, but mainly to enable more independent development and release for each part, as well as a simpler document identification and version handling. Another benefit would be that it becomes easier for bodies outside 3GPP, such as the ITU-T, to refer to telecom management specifications from 3GPP. The new structure of the specifications does not lose any information or functionality supported by the Release 1999. The restructuring also includes defining new IRPs for the Network Resource Model (NRM) parts of R99 Basic CM IRP (Generic, Core Network and UTRAN NRM). These IRPs are named "Network Resources IRP".

Further, the Notification IRP (in Release 1999: 32.106-1 to -4) and the Name convention for Managed Objects (in Release 1999: 32.106-8) have been moved to a separate number series used for specifications common between several management areas (e.g. CM, FM, PM).

Finally, in addition to the restructuring mentioned above, the need to define some new functionality and IRPs for CM compared to Release 1999, has also been identified. Firstly, a new Bulk CM IRP, and secondly an a GERAN Network Resources IRP, have been created. Thirdly, the Generic, UTRAN and GERAN Network Resources IRPs have been extended with support for GSM-UMTS Inter-system handover (ISH), and the 32.600 (Concept and High-level Requirements) has been modified to cover the high-level Bulk CM and ISH requirements.

Table: Mapping between Release '99 and the new specification numbering scheme

R99 Old no.	Old (R99) specification title	Rel-4 spec. no. with Bulk CM /ISH	Rel-4 specification title with Bulk CM/ ISH
32.106-1	3G Configuration Management: Concept and Requirements	32.600	3G Configuration Management: Concept and High-level Requirements
32.106-1	<Notification IRP requirements from 32.106-1 and 32.106-2>	32.301-1	Notification IRP: Requirements
32.106-2	Notification IRP: IS	32.301-2	Notification IRP: Information Service
32.106-3	Notification IRP: CORBA SS	32.301-3	Notification IRP: CORBA SS
32.106-4	Notification IRP: CMIP SS	32.301-4	Notification IRP: CMIP SS
32.106-8	Name convention for Managed Objects	32.300	Name Convention for Managed Objects
-	-	32.602-1	Bulk CM IRP: Requirements
-	-	32.602-2	Bulk CM IRP: Information Service
-	-	32.602-3	Bulk CM IRP: CORBA SS
-	-	32.602-4	Bulk CM IRP: CMIP SS
-	-	32.602-5	Bulk CM IRP: XML file format definition
32.106-1	<Basic CM IRP Generic NRM requirements from 32.106-1 and 32.106-5>	32.620-1	Generic Network Resources IRP: Requirements
32.106-5	Basic CM IRP IM (Generic NRM part)	32.620-2	Generic Network Resources IRP: NRM
32.106-6	Basic CM IRP CORBA SS (Generic NRM related part)	32.620-3	Generic Network Resources IRP: CORBA SS
32.106-7	Basic CM IRP CMIP SS (Generic NRM related part)	32.620-4	Generic Network Resources IRP: CMIP SS
32.106-1	<Basic CM IRP UTRAN NRM requirements from 32.106-1 and 32.106-5>	32.622-1	UTRAN Network Resources IRP: Requirements
32.106-5	Basic CM IRP IM (UTRAN NRM part)	32.622-2	UTRAN Network Resources IRP: NRM
32.106-6	Basic CM IRP CORBA SS (UTRAN NRM related part)	32.622-3	UTRAN Network Resources IRP: CORBA SS
32.106-7	Basic CM IRP CMIP SS (UTRAN NRM related part)	32.622-4	UTRAN Network Resources IRP: CMIP SS
-	-	32.623-1	GERAN Network Resources IRP: Requirements
-	-	32.623-2	GERAN Network Resources IRP: NRM
-	-	32.623-3	GERAN Network Resources IRP: CORBA SS
-	-	32.623-4	GERAN Network Resources IRP: CMIP SS

The present document is 3GPP TS 32.623-4: GERAN Network Resource IRP: CMIP Solution Set.

1 Scope

The present document specifies the Common Management Information Protocol (CMIP) Solution Set (SS) for the GERAN Network Resource Integration Reference Point (IRP): Network Resource Model defined in 3GPP TS 32.623-2. In detail:

- Clause 4 contains an introduction to some concepts that are the base for some specific aspects of the CMIP interfaces.
- Clause 5 contains the GDMO definitions for the Alarm Management over the CMIP interfaces
- Clause 6 contains the ASN.1 definitions supporting the GDMO definitions provided in clause 5.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "3G Telecom Management principles and high level requirements".
- [2] 3GPP TS 32.102: "3G Telecom Management architecture".
- [3] 3GPP TS 32.301-4: "Telecommunication Management; Notification Management; Part 4: Notification Integration Reference Point; CMIP Solution Set".
- [4] 3GPP TS 32.623-2: "Telecommunication Management; Configuration Management: GERAN Network Resource Integration Reference Point: Network Resource Model".
- [5] ITU-T Recommendation X.710 (1991): "Common Management Information Service Definition for CCITT Applications".
- [6] ITU-T Recommendation X.721 (02/92): "Information Technology - Open Systems Interconnection – Structure of Management Information: Definition of Management Information".
- [7] ITU-T Recommendation X.730 (01/92): "Information Technology - Open Systems Interconnection – Systems Management: Object Management Function".
- [8] ITU-T Recommendation X.733 (02/92): "Information Technology - Open Systems Interconnection - Alarm Reporting Function".
- [9] ITU-T Recommendation M.3100 (07/95): "Maintenance Telecommunications Management Network – Generic Network Information Model".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TS 32.600 and 3GPP TS 32.623-2 apply.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CMIP	Common Management Information Protocol
DN	Distinguished Name
GDMO	Guidelines for the Definition of Managed Objects
GERAN	GSM-EDGE Radio Access Network
IDL	Interface Definition Language
IEC	International Electro-technical Commission
ISO	International Standards Organization
ITU-T	International Telecommunication Union, Telecommunication Sector
MIB	Management Information Base
MIM	Management Information Model
MIT	Management Information Tree (or Naming Tree)
MOC	Managed Object Class
MOI	Managed Object Instance
NE	Network Element
NR	Network Resource
NRM	Network Resource Model
TMN	Telecommunications Management Network
UTRAN	UMTS Terrestrial Radio Access Network

4 Basic aspects

4.1 Explanation

A technology independent GERAN network resource model is defined in 3GPP TS 32.623-2 for 3G networks. This document provides an implementation of this UTRAN network resource model by using CMIP technology.

4.2 Mapping

The semantic of the GERAN Network Resource Model is defined in 3GPP TS 32.623-2. The specification of the information object classes defined there is independent of any implementation technology and protocol. This subclause maps these technology and protocol independent definitions onto the equivalencies of the CMIP Solution Set of the GERAN Network Resource IRP.

4.2.1 Mapping of MOCs

Table 2 maps the information object classes defined in the UTRAN Network Resource Model onto the equivalent MOCs of the CMIP Solution Set.

Table 1: Mapping of MOCs

Information Objects of the Generic UTAN IRP NRM	MOCs of this CMIP SS
BssFunction	bssFunction
BtsSiteMgr	btsSiteMgr
GsmCell	gsmCell
GsmRelation	gsmRelation
ExternalGsmCell	externalGsmCell

4.2.2 Mapping of Attributes

Table 2: Mapping of Attributes

Attribute defined in 3GPP TS 32.623-2	Attribute defined in this CMIP SS
bssFunctionId	bssFunctionId
btsSiteMgrId	btsSiteMgrId
latitude	latitude
longitude	longitude
gsmCellId	gsmCellId
cellIdentity	cellIdentity
cellAllocation	cellAllocation (GSM 12.20 : 6.1996)
ncc	bsIdentityCode.ncc (GSM 12.20 : 6.1996)
bcc	bsIdentityCode.bcc (GSM 12.20 : 6.1996)
lac	lac (3GPP TS32.622-4: 5.2001)
rac	rac (3GPP TS32.622-4: 5.2001)
racc	racc
tsc	tsc (GSM 12.20 : 6.1996)
rxLevAccessMin	rxLevAccessMin (GSM 12.20 : 6.1996)
msTxPwrMaxCCH	msTxPwrMaxCCH (GSM 12.20 : 6.1996)
hoppingSequenceNumber	hoppingSequenceNumber (GSM 12.20 : 6.1996)
plmnPermitted	plmnPermitted (GSM 12.20 : 6.1996)
gsmRelationId	gsmRelationId
relationType	relationType (3GPP TS32.622-4: 5.2001)
adjacentCell	adjacentCell (3GPP TS32.622-4: 5.2001)
bcchFrequency	bcchFrequency (GSM 12.20 : 6.1996)
externaGsmCellId	externalGsmCellId

5 GDMO Definitions

5.1 Managed Object Classes

5.1.1 bssFunction

bssFunction MANAGED OBJECT CLASS

DERIVED FROM "3GPP TS 32.620-4: 6.2001": managedFunction;

CHARACTERIZED BY

bssFunctionBasicPackage;

REGISTERED AS {ts32-623ObjectClass 1};

5.1.2 btsSiteMgr

btsSiteMgr MANAGED OBJECT CLASS

DERIVED FROM "3GPP TS 32.620-4: 6.2001": managedFunction;

CHARACTERIZED BY

btsSiteMgrBasicPackage;

CONDITIONAL PACKAGES

btsSiteMgrGeoPositionPackage PRESENT IF

"the attributes defined in this package are supported by an instance of this class.";

REGISTERED AS {ts32-623ObjectClass 2};

5.1.3 gsmCell

gsmCell MANAGED OBJECT CLASS

DERIVED FROM "3GPP TS 32.620-4: 6.2001": managedFunction;
CHARACTERIZED BY
gsmCellBasicPackage,
gsmCellMandatoryPackage,
CONDITIONAL PACKAGES
gsmCellOptionalPackage PRESENT IF
"the attributes defined in this package are supported by an instance of this class.";
REGISTERED AS {ts32-623ObjectClass 3};

5.1.4 externalGsmCell

externalUtranCell MANAGED OBJECT CLASS

DERIVED FROM "3GPP TS 32.620-4: 6.2001": managedFunction;
CHARACTERIZED BY
externalGsmCellBasicPackage,
externalGsmCellMandatoryPackage,
CONDITIONAL PACKAGES
gsmCellOptionalPackage PRESENT IF
"the attributes defined in this package are supported by an instance of this class.";
REGISTERED AS {ts32-623ObjectClass 4};

5.1.5 gsmRelation

gsmRelation MANAGED OBJECT CLASS

DERIVED FROM "Recommendation X.721: 1992":top;
CHARACTERIZED BY
gsmRelationBasicPackage;
CONDITIONAL PACKAGES
gsmRelationOptionalPackage PRESENT IF
"the attributes defined in this package are supported by an instance of this class.";
"Recommendation M.3100: 1995":createDeleteNotificationsPackage PRESENT IF
"the objectCreation and the objectDeletion defined in Recommendation
X.721 are supported by an instance of this class.",
"Recommendation M.3100: 1995":attributeValueChangeNotificationPackage PRESENT IF
"the attributeValueChange notifications defined in Recommendation X.721
are supported by an instance of this class.",
REGISTERED AS {ts32-623ObjectClass 5};

5.2 Packages

5.2.1 bssFunctionBasicPackage

bssFunctionBasicPackage PACKAGE

BEHAVIOUR

bssFunctionBasicPackageBehaviour;

ATTRIBUTES

bssFunctionId GET;

REGISTERED AS {ts32-623Package 1};

bssFunctionBasicPackageBehaviour BEHAVIOUR

DEFINED AS

“The Managed Object Class bssFunction represents BSS functionality. For more information about the BSS, see GSM 03.02”

5.2.2 btsSiteMgrBasicPackage

btsSiteMgrBasicPackage PACKAGE

BEHAVIOUR

btsSiteMgrBasicPackageBehaviour;

ATTRIBUTES

btsSiteMgrId GET;

REGISTERED AS {ts32-623Package 2};

btsSiteMgrBasicPackageBehaviour BEHAVIOUR

DEFINED AS

“The ‘BtsSiteMgr’ managed object contains site specific information for a BTS site.”

5.2.3 btsSiteMgrGeoPositionPackage

btsSiteMgrGeoPositionPackage PACKAGE

BEHAVIOUR

btsSiteMgrGeoPositionPackageBehaviour;

ATTRIBUTES

longitude GET-REPLACE,

latitude GET-REPLACE;

REGISTERED AS {ts32-623Package 3};

btsSiteMgrGeoPositionPackageBehaviour BEHAVIOUR

DEFINED AS

“This package contains the attributes describing the geographic position of a BTS site.”

5.2.4 gsmCellBasicPackage

gsmCellBasicPackage PACKAGE

BEHAVIOUR

gsmCellBasicPackageBehaviour;
ATTRIBUTES
gsmCellId GET;
REGISTERED AS {ts32-623Package 4};

gsmCellBasicPackageBehaviour BEHAVIOUR

DEFINED AS

"The managed object class gsmCell represents the GSM radio cell.";

5.2.5 gsmCellMandatoryPackage

gsmCellMandatoryPackage PACKAGE

BEHAVIOUR

gsmCellMandatoryPackageBehaviour;

ATTRIBUTES

cellIdentity GET-REPLACE,

"GSM 12.20: 6. 1996": cellAllocation GET-REPLACE,

"GSM 12.20: 6. 1996": bsIdentityCode GET-REPLACE,

"3GPP TS 32.622-4: 6.2001": lac GET-REPLACE,

"GSM 12.20: 6. 1996": tsc GET-REPLACE,

"GSM 12.20: 6. 1996": rxLevAccessMin GET-REPLACE,

"GSM 12.20: 6. 1996": msTxPwrMaxCCH GET-REPLACE,

"GSM 12.20: 6. 1996": hoppingSequenceNumber GET-REPLACE,

"GSM 12.20: 6. 1996": plmnPermitted GET-REPLACE;

REGISTERED AS {ts32-623Package 5};

gsmCellMandatoryPackageBehaviour BEHAVIOUR

DEFINED AS

"This package contains the elementary mandatory attributes of a gsmCell.";

5.2.6 gsmCellOptionalPackage

gsmCellOptionalPackage PACKAGE

BEHAVIOUR

gsmCellOptionalPackageBehaviour;

ATTRIBUTES

"3GPP TS 32.622-4: 6.2001": rac GET-REPLACE,

racc GET-REPLACE;

REGISTERED AS {ts32-623Package 6};

gsmCellOptionalPackageBehaviour BEHAVIOUR

DEFINED AS

"This package contains the optional GPRS attributes of a gsmCell.";

5.2.7 externalGsmCellBasicPackage

externalGsmCellBasicPackage PACKAGE

BEHAVIOUR

externalUtranCellBasicPackageBehaviour;

ATTRIBUTES

externalGsmCellId GET;

REGISTERED AS {ts32-623Package 7};

externalGsmCellBasicPackageBehaviour BEHAVIOUR

DEFINED AS

"This Managed Object Class represents a radio cell controlled by another IRPAgent. It a necessary attribute for inter-system handover. This MOC is a subreplication of a MOC in another NEM.";

5.2.8 externalGsmCellMandatoryPackage

externalGsmCellMandatoryPackage PACKAGE

BEHAVIOUR

externalGsmCellMandatoryPackageBehaviour;

ATTRIBUTES

cellIdentity GET-REPLACE,

"GSM 12.20: 6. 1996": bsIdentityCode GET-REPLACE,

"3GPP TS 32.622-4: 6.2001": lac GET-REPLACE,

"GSM 12.20: 6. 1996": bcchFrequency GET-REPLACE;

REGISTERED AS {ts32-623Package 8};

externalGsmCellMandatoryPackageBehaviour BEHAVIOUR

DEFINED AS

"This package contains the elementary mandatory attributes of a externalGsmCell.";

5.2.9 gsmRelationBasicPackage

gsmRelationBasicPackage PACKAGE

BEHAVIOUR

gsmRelationBasicPackageBehaviour;

ATTRIBUTES

gsmRelationId GET,

"3GPP TS 32.622: 6.2001": relationType GET-REPLACE,

"3GPP TS 32.622: 6.2001": adjacentCell GET-REPLACE;

REGISTERED AS {ts32-623Package 9};

gsmRelationBasicPackageBehaviour BEHAVIOUR

DEFINED AS

"The 'GsmRelation' managed object contains radio network related parameters for the relation to the 'GsmCell' or 'ExternalGsmCell' managed object. Note: In

handover relation terms, the cell containing the GSM Relation object is the source cell for the handover. The cell referred to in the GSM relation object is the target cell for the handover. This defines a one-way handover relation where the direction is *from* source cell to target cell.”;

5.2.10 gsmRelationOptionalPackage

gsmRelationOptionalPackage PACKAGE

BEHAVIOUR

gsmRelationOptionalPackageBehaviour;

ATTRIBUTES

“GSM 12.20: 6. 1996”: bsIdentityCode GET-REPLACE,

“3GPP TS 32.622-4: 6.2001”: lac GET-REPLACE,

“GSM 12.20: 6. 1996”: bcchFrequency GET-REPLACE;

REGISTERED AS {ts32-623Package 6};

gsmRelationOptionalPackageBehaviour BEHAVIOUR

DEFINED AS

"This package contains the optional attributes of a gsmRelation.";

5.3 Attributes

5.3.1 bssFunctionId

bssFunctionId ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;

MATCHES FOR EQUALITY;

BEHAVIOUR

bssFunctionIdBehaviour;

REGISTERED AS {ts32-623Attribute 1};

bssFunctionIdBehaviour BEHAVIOUR

DEFINED AS

"This attribute identifies a bssFunction object."

5.3.2 btsSiteMgrId

btsSiteMgrId ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;

MATCHES FOR EQUALITY;

BEHAVIOUR

btsSiteMgrIdBehaviour;

REGISTERED AS {ts32-623Attribute 2};

btsSiteMgrIdBehaviour BEHAVIOUR

DEFINED AS

"This attribute identifies a btsSiteMgr object."

5.3.3 longitude

longitude ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-623TypeModule.Longitude;
MATCHES FOR EQUALITY;
BEHAVIOUR
longitudeBehaviour;
REGISTERED AS {ts32-623Attribute 3};

longitudeBehaviour BEHAVIOUR

DEFINED AS
"Used for geographical positioning of the site manager.";

5.3.4 latitude

latitude ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-623TypeModule.Latitude;
MATCHES FOR EQUALITY;
BEHAVIOUR
latitudeBehaviour;
REGISTERED AS {ts32-623Attribute 4};

latitudeBehaviour BEHAVIOUR

DEFINED AS
"Used for geographical positioning of the site manager.";

5.3.5 gsmCellId

gsmCellId ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;
MATCHES FOR EQUALITY;
BEHAVIOUR
gsmCellIdBehaviour;
REGISTERED AS {ts32-623Attribute 5};

btsSiteMgrIdBehaviour BEHAVIOUR

DEFINED AS
"Cell Identity (Ref GSM 03.03).";

5.3.6 cellIdentity

cellIdentity ATTRIBUTE

WITH ATTRIBUTE SYNTAX GSM1220TypeModule.CellIdentity;
MATCHES FOR EQUALITY;
BEHAVIOUR
cellIdentityBehaviour;

REGISTERED AS {ts32-623Attribute 6};

cellIdentityBehaviour BEHAVIOUR

DEFINED AS

"Location Area Code, LAC (Ref. 3 GPP TS 23.003)"

5.3.7 racc

racc ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-622TypeModule.Racc;

MATCHES FOR EQUALITY;

BEHAVIOUR

raccBehaviour;

REGISTERED AS {ts32-623Attribute 7};

raccBehaviour BEHAVIOUR

DEFINED AS

"Routing Area Colour Code, RACC."

5.3.8 gsmRelationId

gsmRelationId ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;

MATCHES FOR EQUALITY;

BEHAVIOUR

gsmRelationIdBehaviour;

REGISTERED AS {ts32-623Attribute 8};

gsmRelationIdBehaviour BEHAVIOUR

DEFINED AS

"This attribute identifies a gsmRelation object.";

5.3.9 externalGsmCellId

externalGsmCellId ATTRIBUTE

WITH ATTRIBUTE SYNTAX TS32-106-7TypeModule.GeneralObjectId;

MATCHES FOR EQUALITY;

BEHAVIOUR

externalGsmCellIdBehaviour;

REGISTERED AS {ts32-623Attribute 9};

externalGsmCellIdBehaviour BEHAVIOUR

DEFINED AS

"This attribute identifies a externalGsmCell object.";

5.3 Name Binding

5.3.1 bssFunction - managedElement

bssFunction-managedElement NAME BINDING

SUBORDINATE OBJECT CLASS bssFunction;

NAMED BY SUPERIOR OBJECT CLASS "3GPP TS 32.620-4: 6.2001": managedElement;

WITH ATTRIBUTE bssFunctionId;

BEHAVIOUR

bssFunction-managedElementBehaviour;

CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-623NameBinding 1};

rncFunction-managedElementBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a managedElement contains and controls a bssFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

5.3.2 btsSiteMgr - bssFunction

btsSiteMgr-bssFunction NAME BINDING

SUBORDINATE OBJECT CLASS btsSiteMgr;

NAMED BY SUPERIOR OBJECT CLASS bssFunction;

WITH ATTRIBUTE btsSiteMgrId;

BEHAVIOUR

btsSiteMgr-bssFunctionBehaviour;

CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-623NameBinding 2};

btsSiteMgr-bssFunctionBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a bssFunction contains and controls a btsSiteMgr. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

5.3.3 gsmCell - btsSiteMgr

gsmCell-btsSiteMgr NAME BINDING

SUBORDINATE OBJECT CLASS gsmCell;

NAMED BY SUPERIOR OBJECT CLASS btsSiteMgr;

WITH ATTRIBUTE gsmCellId;

BEHAVIOUR

gsmCell-btsSiteMgrBehaviour;

CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-623NameBinding 3};

gsmCell-btsSiteMgrBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a btsSiteMgr contains and controls a gsmCell. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

5.3.4 gsmRelation - gsmCell

gsmRelation-gsmCell NAME BINDING

SUBORDINATE OBJECT CLASS gsmRelation;

NAMED BY SUPERIOR OBJECT CLASS gsmCell;

WITH ATTRIBUTE gsmRelationId;

BEHAVIOUR

gsmRelation-gsmCellBehaviour;

CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-623NameBinding 4};

gsmRelation-gsmCellBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a gsmCell contains and controls a gsmRelation. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

5.3.5 externalGsmCell - subNetwork

externalGsmCell-subNetwork NAME BINDING

SUBORDINATE OBJECT CLASS externalGsmCell;

NAMED BY SUPERIOR OBJECT CLASS "3GPP TS 32.620-4: 05.2001": subNetwork;

WITH ATTRIBUTE externalGsmCellId;

BEHAVIOUR

externalGsmCell-subNetworkBehaviour;

CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;

DELETE ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {ts32-623NameBinding 5};

externalUtranCell-subNetworkBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a subNetwork contains and controls an externalGsmCell. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

5.3.6 vsDataContainer - bssFunction

vsDataContainer-r-bssFunction NAME BINDING

SUBORDINATE OBJECT CLASS “3GPP TS 32.620-4: 06.2001”: vsDataContainer;;
NAMED BY SUPERIOR OBJECT CLASS bssFunction;
WITH ATTRIBUTE vsDataContainerId;
BEHAVIOUR
vsDataContainer-bssFunctionBehaviour;
CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-623NameBinding 6};

vsDataContainer-r-bssFunctionBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a bssFunction contains and controls a vsDataContainer. When automatic instance naming is used, the choice of name bindings is left as a local matter. This containment relation shall be used only with BulkCmIRP CMIP SS defined in 3GPP TS 32.602-4.";

5.3.7 vsDataContainer - btsSiteMgr

vsDataContainer-r-btsSiteMgr NAME BINDING

SUBORDINATE OBJECT CLASS “3GPP TS 32.620-4: 06.2001”: vsDataContainer;;
NAMED BY SUPERIOR OBJECT CLASS btsSiteMgr;
WITH ATTRIBUTE vsDataContainerId;
BEHAVIOUR
vsDataContainer-btsSiteMgrBehaviour;
CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-623NameBinding 7};

vsDataContainer-r-btsSiteMgrBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a btsSiteMgr contains and controls a vsDataContainer. When automatic instance naming is used, the choice of name bindings is left as a local matter. This containment relation shall be used only with BulkCmIRP CMIP SS defined in 3GPP TS 32.602-4.";

5.3.8 vsDataContainer - gsmCell

vsDataContainer-r-gsmCell NAME BINDING

SUBORDINATE OBJECT CLASS “3GPP TS 32.620-4: 06.2001”: vsDataContainer;;
NAMED BY SUPERIOR OBJECT CLASS gsmCell;
WITH ATTRIBUTE vsDataContainerId;
BEHAVIOUR
vsDataContainer-gsmCellBehaviour;

CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-623NameBinding 8};

vsDataContainer-gsmCellBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a gsmCell contains and controls a vsDataContainer. When automatic instance naming is used, the choice of name bindings is left as a local matter. This containment relation shall be used only with BulkCmIRP CMIP SS defined in 3GPP TS 32.602-4.";

5.3.9 vsDataContainer - gsmRelation

vsDataContainer-gsmRelation NAME BINDING

SUBORDINATE OBJECT CLASS "3GPP TS 32.620-4: 06.2001": vsDataContainer;;
NAMED BY SUPERIOR OBJECT CLASS gsmRelation;
WITH ATTRIBUTE vsDataContainerId;
BEHAVIOUR
vsDataContainer-gsmCellRelationBehaviour;
CREATE WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-622NameBinding 9};

vsDataContainer-gsmRelationBehaviour BEHAVIOUR

DEFINED AS

"The name binding represents a relationship in which a gsmRelation contains and controls a vsDataContainer. When automatic instance naming is used, the choice of name bindings is left as a local matter. This containment relation shall be used only with BulkCmIRP CMIP SS defined in 3GPP TS 32.602-4.";

6 ASN.1 Definitions

```
TS32-623TypeModule {ccitt (0) identified-organization (4) etsi (0)
    mobileDomain (0) umts-Operation-Maintenance (3) ts-32-623 (623)
    informationModel (0) asn1Module (2) version1 (1)}
```

```
DEFINITIONS IMPLICIT TAGS ::=
```

```
BEGIN
```

```
--EXPORTS everything
```

```
--IMPORTS
```

```
-- 3GPP TS 32.623-4 related Object Identifiers
```

```
baseNodeUMTS OBJECT IDENTIFIER ::= { itu-t(0) identified-organization(4) etsi(0) mobileDomain(0)
    umts-Operation-Maintenance(3)}
```

```
ts32-623 OBJECT IDENTIFIER ::= { baseNodeUMTS ts-32-623(623)}
```

```
ts32-623InfoModel OBJECT IDENTIFIER ::= { ts32-623 informationModel(0)}
```

```
ts32-623ObjectClass OBJECT IDENTIFIER ::= { ts32-623InfoModel managedObjectClass(3)}
```

```
ts32-623Package OBJECT IDENTIFIER ::= { ts32-623InfoModel package(4)}
```

```
ts32-623Parameter OBJECT IDENTIFIER ::= { ts32-623InfoModel parameter(5)}
```

```
ts32-623NameBinding OBJECT IDENTIFIER ::= { ts32-623InfoModel nameBinding(6)}
```

```
ts32-623Attribute OBJECT IDENTIFIER ::= { ts32-623InfoModel attribute(7)}
```

```
ts32-623Action OBJECT IDENTIFIER ::= { ts32-623InfoModel action(9)}
```

```
ts32-623Notification OBJECT IDENTIFIER ::= { ts32-623InfoModel notification(10)}
```

```
-- Start of 3GPP SA5 own definitions
```

```
Longitude ::= GraphicString
```

```
Latitude ::= GraphicString
```

```
Racc ::= Integer
```

```
END -- of TS32-622TypeModule
```

Annex A (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
Jun 2001	S_12	SP-010283	--	--	Approved at TSG SA #12 and placed under Change Control	2.0.0	4.0.0