3GPP TS 32.663 V9.0.0 (2009-12)

Technical Specification

3rd Generation Partnership Project;
Technical Specification Group Services and System Aspects;
Telecommunication management;
Configuration Management (CM);
Kernel CM Integration Reference Point (IRP);
Common Object Request Broker Architecture (CORBA)
Solution Set (SS)
(Release 9)





This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification. Specifications and reports for implementation of the 3GPP TM system should be obtained via the 3GPP Organizational Partners' Publications Offices.

Keywords GSM, UMTS, management, CORBA, architecture

3GPP

Postal address

3GPP support office address
650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet http://www.3gpp.org

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

©2009, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TTA, TTC).
All rights reserved.

UMTSTM is a Trade Mark of ETSI registered for the benefit of its members $3GPP^{TM}$ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners LTETM is a Trade Mark of ETSI currently being registered for the benefit of its Members and of the 3GPP Organizational Partners GSM® and the GSM logo are registered and owned by the GSM Association

Contents

Forev	word		4
Introd	duction		4
1	Scope		5
2	_		
3 3.1 3.2	Definitions	viations	ε
4	Void		6
5 5.1 5.2 5.3	Notifications Filter language	ished Names and Versions	6
6 6.1 6.2 6.3 6.4	Void Operation and Notif Operation parameter	ication mapping mapping	7 7
7	Use of OMG Structur	red Event	10
8 8.1 8.2	Void	sionsved	13
Anne	ex A (normative):	IDL specification (file name "KernelCmConstDefs.idl")	14
Anne	ex B (normative):	IDL specification (file name "KernelCmIRPSystem.idl")	16
Anne	ex C (normative):	IDL specification (file name "KernelCmNotifications.idl")	17
Anne	ex D (informative):	Change history	20
		∵	

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

32.661	Configuration Management (CM); Kernel CM Requirements
32.662	Configuration Management (CM); Kernel CM Information Service (IS)
32.663	Configuration Management (CM); Kernel CM Integration Reference Point (IRP); Common Object Request Broker Architecture (CORBA) Solution Set (SS)
32.665	Configuration Management (CM); Kernel CM Integration Reference Point (IRP); eXtensible Markup Language (XML) definitions
32.667:	Configuration Management (CM); Kernel CM Integration Reference Point (IRP); SOAP Solution Set (SS)

Configuration Management (CM), in general, provides the operator with the ability to assure correct and effective operation of the 3G network as it evolves. CM actions have the objective to control and monitor the actual configuration on the Network Elements (NEs) and Network Resources (NRs), and they may be initiated by the operator or by functions in the Operations Systems (OSs) or NEs.

CM actions may be requested as part of an implementation programme (e.g. additions and deletions), as part of an optimisation programme (e.g. modifications), and to maintain the overall Quality of Service (QoS). The CM actions are initiated either as single actions on single NEs of the 3G network, or as part of a complex procedure involving actions on many resources/objects in one or several NEs.

[12]

[13]

1 Scope

The purpose of the present document is to define the mapping of the Kernel CM IRP: IS (see 3GPP TS 32.662 [4]) to the protocol specific details necessary for implementation of this IRP in a CORBA/IDL environment.

This Solution Set specification is related to 3GPP TS 32.662 V9.0.X [4].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.

management: Information Service (IS)".

(CORBA) Solution Set (SS)".

management: Requirements".

• For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document.

Release as th	ne present document.
[1]	3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
[2]	3GPP TS 32.102: "Telecommunication management; Architecture".
[3]	3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
[4]	3GPP TS 32.662: "Telecommunication management; Configuration Management (CM); Kernel CM: Information Service (IS)".
[5]	3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects".
[6]	Object Management Group 98 (November 1998): "Notification Service: Joint Revised Submission OMG TC Document telecom/98-11-01".
[7]	OMG CORBA Services (November 1996): "Common Object Services Specification" (clause 4 contains the Event Service specification).
[8]	The Common Object Request Broker: Architecture and Specification (for specification of valid version, see [1]).
[9]	3GPP TS 32.303: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)".
[10]	3GPP TS 32.111-3: "Telecommunication management; Fault Management; Part 3: Alarm Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)".
[11]	3GPP TS 32.312: "Telecommunication management; Generic Integration Reference Point (IRP)

3GPP TS 32.673: "Telecommunication management; Configuration Management (CM); State Management Integration Reference Point (IRP): Common Object Request Broker Architecture

3GPP TS 32.311: "Telecommunication management; Generic Integration Reference Point (IRP)

3 Definitions and abbreviations

3.1 **Definitions**

For the purposes of the present document, the terms and definitions given in 3GPP TS 32.101 [1], 3GPP TS 32.102 [2], 3GPP TS 32.600 [3] and 3GPP TS 32.662 [4] apply.

IRP document version number string (or "IRPVersion"): see 3GPP TS 32.311 [13].

3.2 **Abbreviations**

For the purposes of the present document, the following abbreviations apply:

CORBA Common Object Request Broker Architecture DN Distinguished Name IDL Interface Definition Language (OMG) **IRP** Integration Reference Point Information Service IS MO Managed Object Managed Object Class MOC NRM Network Resource Model OM G Object Management Group

SS Solution Set

VSE Vendor Specific Extensions

4 Void

5 Architectural features

The overall architectural feature of Kernel Configuration Management IRP is specified in 3GPP TS 32.662 [4]. This clause specifies features that are specific to the CORBA SS.

Notifications 5.1

Notifications are sent according to the Notification IRP: CORBA SS (see 3GPP TS 32.303 [9]).

The contents of the Kernel CM IRP notifications are defined in the present document.

5.2 Filter language

The filter language used in the SS is the Extended Trader Constraint Language (see OMG Notification Service [6]). IRPAgents may throw a FilterComplexityLimit exception when a given filter is too complex.

5.3 Syntax for Distinguished Names and Versions

The format of a Distinguished Name is defined in 3GPP TS 32.300 [5].

The version of this IRP is represented as a string (see also clause 3.1).

6 Mapping

6.1 Void

6.2 Operation and Notification mapping

The Kernel CM IRP: IS (see 3GPP TS 32.662 [4]) defines semantics of operation and notification visible across the Kernel Configuration Management IRP. The following table in this subclause indicates mapping of these operations and notifications to their equivalents defined in this SS.

Table 6.2.1: Mapping from IS Notification/Operation to SS equivalents

IS Operation/ notification	SS Method	Qualifier
(3GPP TS 32.662 [4])		
getNRMIRPVersion	get_nm_irp_version	M
notifyObjectCreation	See Notification IRP: CORBASS [9]	0
notifyObjectDeletion	See Notification IRP: CORBASS [9]	0
notifyAttributeValueChange	See Notification IRP: CORBASS [9]	0
notifyStateChange	See Notification IRP: CORBASS [9]	0
getIRPVersion	get_kernel_cm_irp_versions	М
getOperationProfile	get_kernel_cm_irp operations_profile	0
getNotificationProfile	get_kernel_cm_irp_notification_profile	0
notifyCMSynchronizationRecommended	See Notification IRP: CORBASS [9]	0

6.3 Operation parameter mapping

The Kernel CM IRP: IS (see 3GPP TS 32.662 [4]) defines semantics of parameters carried in operations across the Kernel Configuration Management IRP. The following tables in this subclause indicate the mapping of these parameters, as per operation, to their equivalents defined in this SS.

Table 6.3.1: Mapping from IS getNRMIRPVersion parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
versionNumberList	ManagedGenericIRPConstDefs::VersionNumberSet version_number_list	M
vSEVersionNumberList	ManagedGenericIRPConstDefs::VersionNumberSet	M
	vse_version_number_list	
status	Exceptions:	M
	GetNRMIRPVersion	

Table 6.3.2: Mapping from IS getIRPVersion parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
versionNumberList	Return value of type ManagedGenericIRPConstDefs::VersionNumberSet	M
status	exception GetKernelCmIRPVersionsException	M

Table 6.3.3: Mapping from IS getOperationProfile parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
irpVersion	ManagedGenericIRPConstDefs::VersionNumber kernel_cm_irp_version	M
operationNameProfile,	Return value of type ManagedGenericIRPConstDefs::MethodList	M
operationParameterProfile		
status	Exceptions:	M
	GetKernelCMIRPOperations ProfileException,	
	ManagedGenericIRPSystem::OperationNotSupported,	
	ManagedGenericIRPSystem::InvalidParameter	

Table 6.3.4: Mapping from IS getNotificationProfile parameters to SS equivalents

IS Operation parameter	SS Method parameter	Qualifier
irpVersion	ManagedGenericIRPConstDefs::VersionNumber kernel_cm_irp_version	M
notificationNameProfile,	Return value of type ManagedGenericIRPConstDefs::MethodList	М
notification Parameter Profile		
status	Exceptions:	M
	GetKernelCMIRPNotificationProfileException,	
	ManagedGenericIRPSystem::OperationNotSupported,	
	ManagedGenericIRPSystem::InvalidParameter	

6.4 Notification attribute mapping

The Kernel CM IRP: IS (see 3GPP TS 32.662 [4]) identifies and defines the semantics of attributes for notifyObjectCreation, notifyObjectDeletion, notifyAttributeValueChange, notifyStateChange and notifyCMSynchronizationRecommended for use for its IRP. The following table in this subclause shows the mapping of the IS notifications to SS equivalents.

Table 6.4.1: Mapping from IS notifications to SS equivalents

IS notifications in 3 GPP TS 32.662 [4]	SS notifications	Qualifier
NotifyObjectCreation	push_structured_event	0
NotifyObjectDeletion	push_structured_event	0
NotifyAttributeValueChange	push_structured_event	0
NotifyStateChange	push_structured_event	0
NotifyCMSynchronizationRecommended	push_structured_event	0

The Kernel CM IRP: IS (see 3GPP TS 32.662 [4]) also qualifies the attributes. The following tables in this subclause show the mapping of these IS attributes to SS equivalents.

Table 6.4.2: Mapping from IS Notification Header attributes to SS equivalent

IS Attribute of Notification Header in 3 GPP TS 32.662 [4]	SS Attribute	Qualifier
objectClass, objectInstance	NotificationIRPConstDefs::AttributeNameValue:: MANAGED_OBJECT_INSTANCE	M
notificationId	NotificationIRPConstDefs::AttributeNameValue:: NOTIFICATION_ID	M
eventTime	NotificationIRPConstDefs::AttributeNameValue:: EVENT_TIME	M
systemDN	NotificationIRPConstDefs::AttributeNameValue:: SYSTEM_DN	0
notificationType		М

Table 6.4.3: Mapping from IS notifyObjectCreation attributes to SS equivalent OBJECT_CREATION

IS Attribute of notifyObjectCreation in 3 GPP TS 32.662 [4]	SS Attribute	Qualifier
notificationHeader	See table 6.4.2	M
correlatedNotifications	KernelCmNotifications::MOCreation::CORRELATED_NOTIFICATIONS	0
additionalText	KernelCmNotifications::MOCreation::ADDITIONAL_TEXT	0
sourceIndicator	KernelCmNotifications::MOCreation::SOURCE_INDICATOR	0
attributeList	KernelCmNotifications::MOCreation::InitialAttributeValues (contained in remainder_of_body)	0

Table 6.4.4: Mapping from IS notifyObjectDeletion attributes to SS equivalent OBJECT_DELETION

IS Attribute of notifyObjectDeletion in 3 GPP TS 32.662 [4]	SS Attribute	Qualifier
notificationHeader	See table 6.4.2	М
correlatedNotifications	KernelCmNotifications::MODeletion::CORRELATED_NOTIFICATIONS	0
additionalText	KernelCmNotifications::MODeletion::ADDITIONAL_TEXT	0
sourceIndicator	KernelCmNotifications::MODeletion::SOURCE_INDICATOR	0
attributeList	KernelCmNotifications::MODeletion::AttributeValues (contained in remainder_of_body)	0

Table 6.4.5: Mapping from IS notifyAttributeValueChange attributes to SS equivalent ATTRIBUTE_VALUE_CHANGE

IS Attribute of notifyAttributeValue Change in 3 GPP TS 32.662 [4]	SS Attribute	Qualifier
notificationHeader	See table 6.4.2	М
correlatedNotifications	KernelCmNotifications::AttributeValueChange::CORRELATED_NOTIFICATIONS	0
additionalText	KernelCmNotifications::AttributeValueChange::ADDITIONAL_TEXT	0
sourceIndicator	KernelCmNotifications::AttributeValueChange::SOURCE_INDICATOR	0
attributeValueChangeDefinition	KernelCmNotifications::AttributeValueChange::ModifiedAttributeSet (contained in remainder_of_body)	М

Table 6.4.6: Mapping from IS notifyCMSynchronizationRecommended attributes to SS equivalent REQUEST_CM_SYNCHRONIZATION

IS Attribute of notifyCMSynchronization Recommended in 3 GPP TS 32.662 [4]	SS Attribute	Qualifier
notificationHeader	See table 6.4.2	M
baseMOClass	KernelCmNotifications::CMSynchronizationRecommended::BASE_MO_CLASS	M
baseMOInstance	KernelCmNotifications::CMSynchronizationRecommended::BASE_MO_INSTANCE	M
scope	KernelCmNotifications::CMSynchronizationRecommended::SCOPE	M
additionalText	KernelCmNotifications::CMSynchronizationRecommended::ADDITIONAL_TEXT	0

Table 6.4.7: Mapping from IS notifyStateChange attributes to SS equivalent STATE_CHANGE

IS Attribute of notifyStateChange Change in 3 GPP TS 32.662 [4]	SS Attribute	Qualifier		
notificationHeader	See table 6.4.2	M		
stateChange	StateManagementIRPConstDefs::AttributeNameValue (see note)	M		
correlatedNotifications	KernelCmNotifications::StateChange::CORRELATED_NOTIFICATIONS	0		
additionalText	KernelCmNotifications::StateChange::ADDITIONAL_TEXT	0		
sourceIndicator	KernelCmNotifications::StateChange::SOURCE_INDICATOR	0		
NOTE: The stateChange attribute is mapped into name-value pairs that contain the state identifier in the name and the new and optional old state values in the attribute field (See TS 32.673 [12] StateManagementIRPConstDefs IDL <state name="">OldNewValue structures).</state>				

7 Use of OMG Structured Event

In CORBA SS, OMG defined StructuredEvent (see OMG Notification Service [6]) is used to carry notifications. This clause identifies the OMG defined StructuredEvent attributes that carry the attributes of notifications defined in 3GPP TS 32.662 [4].

The composition of OMG Structured Event, as defined in OMG Notification Service [6], is:

```
Header
Fixed Header
domain_name
type_name
event_name
Variable Header

Body
filterable_body_fields
remainder of body
```

The following table in this clause lists all OMG Structured Event attributes in its leftmost column. The second column identifies the SS attributes, if any, that shall be carried there.

Attributes that are denoted as "optional" may be absent from the OMG Structured Event. As an example, if the optional additionalText attribute is not used for a particular notification, then the IRPAgent may exclude additionalText from the filterable body fields for that particular notification. Individual notifications from the same IRPAgent may include or exclude the same optional attribute.

Table 7.1: Use of OMG Structured Event

IS Parameters	OMG CORBA Structured Event attribute	Comment
There is no corresponding IS parameter	domain_name	It contains the supported SS document version (see clause 4). This version is defined by the string constant KernelCmIRPSystem::VERSION defined in this specification.
notificatio nType	type_name	It is an attribute of notificationHeader. It shall indicate one of the following: Object Creation, Object Deletion, Attribute Value Change, State Change and CM Synchronization Recommended. It is a string. Its value is either defined by KernelCmNotifications::MOCreation::EVENT_TYPE, KernelCmNotifications::MODeletion::EVENT_TYPE, KernelCmNotifications::AttributeValueChange::EVENT_TYPE, KernelCmNotifications::StateChange::EVENT_TYPE or KernelCmNotifications::CMSynchronizationRecommended::EVENT_TYPE
There is no corresponding IS parameter	event_name	It shall be set to an empty string.
There is no corresponding IS parameter	variable Header	
objectClass, objectInstance	One NV pair of filterable_body_fields	NV stands for name-value pair. Order arrangement of NV pairs is not significant. The name of NV-pair is always encoded in string. Name of this NV pair is the MAN AGED_OBJECT_INSTANCE of interface AttributeNameValue of module NotificationIRPConstDefs. Value of NV pair is a string. See corresponding table in Notification IRP: CORBA SS (3GPP TS 32.303 [9]).
notificatio nId	One NV pair of remainder_of_body	Name of NV pair is the NOTIFICATION_ID of interface AttributeNameValue of module NotificationIRPConstDefs. Value of NV pair is a long. See corresponding table in Notification IRP: CORBASS (3GPP TS 32.303 [9]).
eventTime	One NV pair of filterable_body_fields	Name of NV pair is the EVENT_TIME of interface AttributeNameValue of module NotificationIRPConstDefs. Value of NV pair is IRPTime. See corresponding table in Notification IRP: CORBASS (3GPP TS 32.303 [9]).
systemDN	One NV pair of filterable_body_fields	Name of NV pair is the SYSTEM_DN of interface AttributeNameValue of module NotificationIRPConstDefs. Value of NV pair is a string. See corresponding table in Notification IRP: CORBASS [9].
correlatedN otification s	One NV pair of remainder_of_body	It is an attribute of the Object Creation, Object Deletion and Attribute Value Change notifications. Name of NV pair is the KemelCmNotifications::NotificationCommon::CORRELATED_NOTIFICATIONS. Value of NV pair is a NotificationIRPConstDefs::CorrelatedNotificationSet defined in 3GPP TS 32.303 [9].
additionalT ext	One NV pair of remainder_of_body	It is an attribute of the Object Creation, Object Deletion, Attribute Value Change and CM Synchronization Recommended notifications. Name of NV pair is the KemelCmNotifications::NotificationCommon::ADDITIONAL_TEXT Value of NV pair is a string.

sourceIndic ator	One NV pair of remainder_of_body	It is an attribute of the Object Creation, Object Deletion and Attribute Value Change no tifications.
	,	Name of NV pair is the KemelCmConstDefs::AttributeNameValue::SOURCE_INDICATOR.
		Value of NV pair is the KernelCmNotifications::NotificationCommon::RESOURCE_OPERATION or MANAGEMENT_OPERATION or UNKNOWN_OPERATION.
	remainder_of_non_filterable_ body (see 3GPP TS 32.303	It is used to transport attribute information.
	[9])	For Object Creation notification, this is defined by KernelCmNotifications::MOCreation::InitialAttributeValues. For Object Deletion notification, this is defined by KernelCmNotifications::MODeletion::AttributeValues.
		The name component of InitialAttributeValues and AttributeValues will be set to attribute names defined in KernelCmNRMDefs.
attributeVa lueChangeDe	remainder_of_non_filterable_ body (see 3GPP TS 32.303	For Attribute Value Change notification, this is defined by KernelCmNotifications::AttributeValueChange::ModifiedAttributeSet.
	[9])	The name component of ModifiedAttributeSet will be set to attribute name defined in KernelCmNRMDefs.
mentIRPCons	A set of up to 9 Name-value pairs See table 7.2. All these 9 NV	For state change notifications a series of up to 9 name-value pairs might be sent corresponding with the new and old values of each state/status attribute which has changed it's value.
	pairs are part of the remainder_of_body	The new values of each state/status attributes that have changed are sent.
		The IRP agent may optionally send the old state/status changes. The name of the name-value pairs are defined by State ManagementIRPConstDefs::AttributeNameValue
baseMOClass	One NV pair of remainder_of_body	It is an attribute of the CMSynchronizationRecommended notification. Name of NV pair is a string,
		KernelCmNotifications::CMSynchronizationRecommended::BASE_MO_CLASS.
		Value of NV pair is a string. This string conveys the semantics of the Managed Object Class.
baseMOInsta nce	One NV pair of remainder_of_body	It is an attribute of the CMSynchronizationRecommended notification. Name of NV pair is the KemelCmNotifications::CMSynchronizationRecommended::BASE_MO_INSTANCE.
		Value of NV pair is a string. This is the DN string of the Managed Object Instance.
scope	One NV pair of remainder_of_body	It is an attribute of the CMSynchronizationRecommended notification. Name of NV pair is the KemelCmNotifications::CMSynchronizationRecommended::SCOPE.
		Value of NV pair is KernelCmConstDefs::ScopePara.

Table 7.2 Name - value pairs for state change notifications

Name	Value
OPERATION AL_STATE	StateManagementIRPConstDefs::OperationalStateOldNewValue
USAGE_STATE	StateManagementIRPConstDefs::UsageStateOldNewValue
ADMINISTRATIVE_STATE	StateManagementIRPConstDefs::AdministrativeStateOldNewValue
ALARM_STATUS	StateManagementIRPConstDefs::AlarmStatusOldNewValue
PROCEDURAL_STATUS	StateManagementIRPConstDefs::ProceduralStatusOldNewValue
AVAILABILITY_STATUS	StateManagementIRPConstDefs::AvailabilityStatusOldNewValue
CONTROL_STATUS	StateManagementIRPConstDefs::ControlStatusOldNewValue
STANDBY_STATUS	StateManagementIRPConstDefs::StandbyStatusOldNewValue
UNKNOWN_STATUS	StateManagementIRPConstDefs::UnknownStatusOldNewValue

8 Rules for NRM extensions

This clause discusses how the models and IDL definitions provided in the present document can be extended for a particular implementation and still remain compliant with 3GPP SA5's specifications.

8.1 Void

8.2 Extensions not allowed

The IDL specifications in the present document cannot be edited or altered. Any additional IDL specifications shall be specified in separate IDL files.

IDL interfaces (note: not MOCs) specified in the present document may not be subclassed or extended. New interfaces may be defined with vendor-specific methods.

Annex A (normative): IDL specification (file name "KernelCmConstDefs.idl")

```
//File: KernelCmConstDefs.idl
#ifndef _KERNEL_CM_CONST_DEFS_IDL_
#define _KERNEL_CM_CONST_DEFS_IDL_
// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"
module KernelCmConstDefs
{
    ^{\star} Information about one attribute
    \star - name defines the name of the attribute
    \mbox{\scriptsize \star} - value defines the value of the attribute
   struct MOAttribute
      string name;
      any value;
    ^{\star} A set of attribute names and values
   typedef sequence<MOAttribute> MOAttributeSet;
    ^{\star} ScopeType defines the kind of scope to use in a CM synchronization
    * request together with ScopePara.level, in the SCOPE field.
    ^{\star} ScopePara.level is always >= 0. If a level is bigger than the
    * depth of the tree there will be no exceptions thrown.
    * BASE_ONLY: level ignored, just return the base object.
    * BASE NTH LEVEL: return all subordinate objects that are on "level"
    * distance from the base object, where 0 is the base object.
    ^{\star} BASE_SUBTREE: return the base object and all of its subordinates
    * down to and including the nth level.
    * BASE ALL: level ignored, return the base object and all of it's
    * subordinates.
   enum ScopeType
      BASE ONLY,
      BASE_NTH_LEVEL,
BASE_SUBTREE,
      BASE ALL
   struct ScopePara
      ScopeType type;
      unsigned long level;
   /* The format of Distinguished Name (DN) is specified in 3GPP TS 32.300
   "Name Conventions for Managed Objects".
   typedef string DN;
   typedef sequence <long> NotifIdSet;
   This holds identifiers of notifications that are correlated.
   struct CorrelatedNotification
      DN source;
                  // Contains DN of MO that emitted the set of notifications
                   // DN string format in compliance with Name Convention for
                   // Managed Object.
                   // This may be a zero-length string. In this case, the MO
                   // is identified by the value of the MOI attribute
                   // of the Structured Event, i.e., the notification.
```

```
NotifIdSet notif_id_set; // Set of related notification ids
};

/*

Correlated Notification sets are sets of Correlated Notification structures.

*/

typedef sequence <CorrelatedNotification> CorrelatedNotificationSet;

/*

This block identifies attributes which are included as part of the Kernel CM IRP. These attribute values should not clash with those defined for the attributes of notification header (see IDL of Notification IRP).

*/

interface AttributeNameValue
{

   const string SOURCE_INDICATOR = "SOURCE";
   const string ADDITIONAL_TEXT = "ADD_TEXT";
   const string CORRELATED_NOTIFICATIONS = "CORREL_NOTIFS";
   const string BASE_MO_CLASS = "BASE_MOC";
   const string BASE_MO_INSTANCE = "BASE_MOI";
   const string SCOPE = "SCOPE";
};

#endif // _KERNEL_CM_CONST_DEFS_IDL_
```

Annex B (normative): IDL specification (file name "KernelCmIRPSystem.idl")

```
//File: KernelCmIRPSystem.idl
#ifndef _KERNEL_CM_IRP_SYSTEM_IDL_
#define _KERNEL_CM_IRP_SYSTEM_IDL_
#include <ManagedGenericIRPConstDefs.idl>
#include <ManagedGenericIRPSystem.idl>
// This statement must appear after all include statements
#pragma prefix "3qppsa5.org"
module KernelCmIRPSystem
   exception GetKernelCMIRPNotificationProfileException { string reason; };
   exception GetKernelCMIRPOperationsProfileException { string reason; };
   exception GetNRMIRPVersion { string reason; };
   exception GetKernelCMIRPVersionsException { string reason; };
    ^{\star} The KernelCmIrpOperations interface.
    \mbox{\ensuremath{^{\star}}} Supports a number of Resource Model versions.
   interface KernelCmIrpOperations
      Return the list of all supported Kernel CM IRP versions.
      ManagedGenericIRPConstDefs::VersionNumberSet get kernel cm irp versions (
      raises (GetKernelCMIRPVersionsException);
       ^{\star} Get the version(s) of the interface
       \star @raises GetNRMIRPVersion when the system for some reason
          can not return the supported versions.
       ^{\star} @returns all supported versions.
      void get nrm irp version
         out ManagedGenericIRPConstDefs::VersionNumberSet version_number_list,
         out ManagedGenericIRPConstDefs::VersionNumberSet vse version number list
      raises (GetNRMIRPVersion);
      Return the list of all supported operations and their supported
      parameters for a specific KernelCM IRP version.
      ManagedGenericIRPConstDefs::MethodList get kernel cm irp operations profile (
         in ManagedGenericIRPConstDefs::VersionNumber kernel cm irp version
      raises (GetKernelCMIRPOperationsProfileException,
              ManagedGenericIRPSystem::OperationNotSupported,
              ManagedGenericIRPSystem::InvalidParameter);
      Return the list of all supported notifications and their supported
      parameters for a specific KernelCM IRP version.
      ManagedGenericIRPConstDefs::MethodList
         get_kernel_cm_irp_notification_profile
         in ManagedGenericIRPConstDefs::VersionNumber kernel cm irp version
      raises (GetKernelCMIRPNotificationProfileException,
              ManagedGenericIRPSystem::OperationNotSupported,
              ManagedGenericIRPSystem::InvalidParameter);
   };
#endif // _KERNEL_CM_IRP_SYSTEM_IDL_
```

Annex C (normative): IDL specification (file name "KernelCmNotifications.idl")

```
//File: KernelCmNotifications.idl
#ifndef _KERNEL_CM_NOTIFICATIONS_IDL_
#define _KERNEL_CM_NOTIFICATIONS_IDL_
#include <KernelCmConstDefs.idl>
#include <NotificationIRPNotifications.idl>
// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"
module KernelCmNotifications
{
    ^{\star} This interface defines fields that are common for all
       notification types.
    * All constants in the scope of this interface will be
      visible in the interfaces that inherits this.
    * For instance constant
    * NotificationCommon::MANAGED_OBJECT_CLASS
      can be addressed by MODeletion:: MANAGED OBJECT CLASS
   interface NotificationCommon: NotificationIRPNotifications::Notify
       ^{\star} \, This constant defines the name of the
       ^{\star} \, source indicator property.
      const string SOURCE INDICATOR =
         KernelCmConstDefs::AttributeNameValue::SOURCE INDICATOR;
       * Valid values for the SOURCE_INDICATOR
       * property
      const string RESOURCE OPERATION = "RESOURCE OPERATION";
      const string MANAGEMENT OPERATION = "MANAGEMENT OPERATION";
      const string SON OPERATION = "SON OPERATION";
      const string UNKNOWN_OPERATION = "UNKNOWN";
       ^{\star} \, This constant defines the name of the
          additional text property.
       * The data type for the value of this property
       ^{\star} is a string.
      const string ADDITIONAL TEXT =
         KernelCmConstDefs::AttributeNameValue::ADDITIONAL TEXT;
       * This constant defines the name of the
       * correlated notifications property.
       * The value part of the property is
            KernelCmConstDefs::CorrelatedNotificationSet
      const string CORRELATED NOTIFICATIONS =
         KernelCmConstDefs::AttributeNameValue::CORRELATED NOTIFICATIONS;
   };
    ^{\star} Constant definitions for the MO deleted notification
   interface MODeletion : NotificationCommon
      const string EVENT TYPE = "x7";
       * This information mapped into the remainder_of_body
       * in the StructuredEvent
      typedef KernelCmConstDefs::MOAttributeSet AttributeValues;
```

```
\star Constant definitions for the MO created notification
interface MOCreation: NotificationCommon
  const string EVENT TYPE = "x6";
   * This information mapped into the remainder_of_body
    * in the StructuredEvent
   typedef KernelCmConstDefs::MOAttributeSet InitialAttributeValues;
};
^{\star} Constant definitions for the Attribute Value Change
   notification
interface AttributeValueChange : NotificationCommon
   const string EVENT_TYPE = "x8";
   * Information about modified attributes for
    ^{\star} one MO instance.
    \star - name defines the name of the attribute
    \star - new value defines the new value of the attribute
    \star - old value defines the previous value of the attribute
        The value is optional, which means that it may contain
         an empty any (null inserted in the any).
   struct ModifiedAttribute
      string name;
     any new value;
     any old_value;
    * This information mapped into the remainder_of_body
    \star in the StructuredEvent.
   typedef sequence<ModifiedAttribute> ModifiedAttributeSet;
* Constant definitions for the CM Synchronization Recommended notification
interface CMSynchronizationRecommended: NotificationIRPNotifications::Notify
   const string EVENT TYPE = "x9";
   * This constant defines the name of the
    * additional text property.
    * The data type for the value of this property
    * is a string.
   const string ADDITIONAL TEXT =
     KernelCmConstDefs::AttributeNameValue::ADDITIONAL_TEXT;
   ^{\star} \, This constant defines the name of the
    * base MO class property.
    * The value part of this property will carry
    ^{\star} the base MO class name as a string.
   const string BASE_MO_CLASS =
      KernelCmConstDefs::AttributeNameValue::BASE MO CLASS;
   ^{\star} \, This constant defines the name of the
   * base MO instance property.
    * The value part of this property will carry
    ^{\star} the base \tilde{\text{MO}} distinguished name as a string.
```

```
const string BASE_MO_INSTANCE =
    KernelCmConstDefs::AttributeNameValue::BASE_MO_INSTANCE;

/**
    * This constant defines the name of the
    * scope property.
    * The data type for the value of this property
    * is KernelCmConstDefs::ScopePara.
    */
    const string SCOPE =
        KernelCmConstDefs::AttributeNameValue::SCOPE;
};

/**
    * Constant definitions for the State Change notification
    */
    interface StateChange : NotificationCommon
    {
        const string EVENT_TYPE = "xA";
    };

#endif // KERNEL CM NOTIFICATIONS IDL
```

Annex D (informative): Change history

	Change history							
Date	TSG#	TSG Doc.	CR	Rev		Cat	Old	New
Sep 2002	SA_17	SP-020466			Submitted to TSG SA #17 for Approval		1.0.0	5.0.0
Mar 2003	SA_19	SP-030143	0001		CORBA IDL Compiler Errors	F	5.0.0	5.1.0
Mar 2003	SA_19	SP-030145	0002		Add IDL definition of notifyCMSynchronizationRecommended notification for KernelCM IRP	В	5.1.0	6.0.0
Jun 2004	SA_24	SP-040261	0004		Add Missing CorrelatedNotificationSetType definition	Α	6.0.0	6.1.0
Sep 2004	SA_25	SP-040568	0007		Add missing DN definition	Α	6.1.0	6.2.0
Sep 2004	SA_25	SP-040568	0009		Add missing IDL for get_kernel_CM_IRP_versions	Α	6.1.0	6.2.0
Sep 2004	SA_25	SP-040569	0010		Add State Management Support to Kernel CM IRP CORBA SS	В	6.1.0	6.2.0
Dec 2004	SA_26	SP-040812	0011		Correct the mapping of IS-defined non-filterable parameters to SS-defined non-filterable fields (instead of filterable fields) - Align with IS in 32.662	F	6.2.0	6.3.0
Mar 2005	SA_27	SP-050050	0012		IDL incompliant to the style guide	F	6.3.0	6.4.0
Jun 2005	SA_28	SP-050299	0013		Correct CORBA SS mapping of notification filterable/non-filterable IS parameters	F	6.4.0	6.5.0
Sep 2005	SA_29	SP-050461	0014		Align the CORBA SS IDL with TS 32.150 Style Guide	F	6.5.0	6.6.0
Mar 2006	SA_31	SP-060089	0015		Correct case sensitive parameter name	F	6.6.0	6.7.0
Jun 2007	SA_36				Automatic upgrade to Rel-7 (no CR) at freeze of Rel-7. Deleted reference to CMIP SS, discontinued from R7 onw ards.		6.7.0	7.0.0
Dec 2008	SA_42				Upgrade to Release 8		7.0.0	8.0.0
Mar 2009	SA_43	SP-090207	0016		Indicating Self-X in sourceIndicator of create-/delete-/change-notifications	F	8.0.0	8.1.0
Dec 2009	-	-	-	-	Update to Rel-9 version		8.1.0	9.0.0