

# 3GPP TS 32.675 V9.0.0 (2009-12)

---

*Technical Specification*

**3rd Generation Partnership Project;  
Technical Specification Group Services and System Aspects;  
Telecommunication Management;  
Configuration Management (CM);  
State Management Integration Reference Point (IRP);  
Bulk CM eXtensible Markup Language (XML)  
file format definition  
(Release 9)**

---



The present document has been developed within the 3<sup>rd</sup> Generation Partnership Project (3GPP<sup>TM</sup>) and may be further elaborated for the purposes of 3GPP. The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification. Specifications and reports for implementation of the 3GPP<sup>TM</sup> system should be obtained via the 3GPP Organizational Partners' Publications Offices.

---

Keywords

---

UMTS, management, alarm, CORBA,  
architecture

**3GPP**

Postal address

---

3GPP support office address

---

650 Route des Lucioles - Sophia Antipolis  
Valbonne - FRANCE  
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

---

<http://www.3gpp.org>

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© 2009, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TTA, TTC).  
All rights reserved.

UMTS™ is a Trade Mark of ETSI registered for the benefit of its members  
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners  
LTE™ is a Trade Mark of ETSI currently being registered for the benefit of its Members and of the 3GPP Organizational Partners  
GSM® and the GSM logo are registered and owned by the GSM Association

---

# Contents

Foreword .....	4
Introduction .....	4
1 Scope .....	5
2 References.....	5
3 Definitions and abbreviations .....	5
3.1 Definitions .....	5
3.2 Abbreviations.....	7
4 Structure and content of configuration data XML files.....	7
<b>Annex A (normative): Configuration data file NRM-specific XML schema (file name "stateManagementIRP.xsd") .....</b>	<b>8</b>
<b>Annex B (informative): Void.....</b>	<b>10</b>
<b>Annex C (informative): Change history.....</b>	<b>11</b>

---

## Foreword

This Technical Specification (TS) has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

## Introduction

The present document is part of a TS-family covering the 3<sup>rd</sup> Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

- 32.671 Configuration Management (CM); State Management Integration Reference Point (IRP); Requirements
- 32.672 Configuration Management (CM); State Management Integration Reference Point (IRP); Information Service (IS)
- 32.673 Configuration Management (CM); State Management Integration Reference Point (IRP); Common Object Request Broker Architecture (CORBA) Solution Set (SS)
- 32.675 Configuration Management (CM); State Management Integration Reference Point (IRP); Bulk CM eXtensible Markup Language (XML) file format definition**

Configuration Management (CM), in general, provides the operator with the ability to assure correct and effective operation of the 3G network as it evolves. CM actions have the objective to control and monitor the actual configuration on the Network Elements (NEs) and Network Resources (NRs), and they may be initiated by the operator or by functions in the Operations Systems (OSs) or NEs.

CM actions may be requested as part of a deployment program (e.g. additions and deletions), as part of an optimisation program (e.g. modifications), and to maintain the overall Quality of Service (QoS). The CM actions are initiated either as single actions on single NEs of the 3G network, or as part of a complex procedure involving actions on many resources/objects in one or several NEs.

---

# 1 Scope

The present document specifies the XML file format definition for the Bulk Configuration Management IRP IS [2] for the IRP whose semantics is specified in State Management IRP: Information Service (IS) (3GPP TS 32.672 [1]).

Bulk CM XML file formats are based on XML [4], XML Schema [5] [6] [7] and XML Namespace [8] standards.

This File Format Definition specification is related to 3GPP TS 32.672 V9.0.X.

---

# 2 References

The following documents contain provisions, which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.672: "Telecommunication management; Configuration Management (CM); State Management Integration Reference Point (IRP): Information Service (IS)".
- [2] 3GPP TS 32.612: "Telecommunication management; Configuration Management (CM); Bulk CM Integration Reference Point (IRP); Information Service (IS)".
- [3] 3GPP TS 32.615: "Telecommunication management; Configuration Management (CM); Bulk CM Integration Reference Point (IRP); eXtensible Markup Language (XML) file format definition".
- [4] W3C REC-xml-20001006: "Extensible Markup Language (XML) 1.0 (Second Edition)".
- [5] W3C REC-xmlschema-0-20010502: "XML Schema Part 0: Primer".
- [6] W3C REC-xmlschema-1-20010502: "XML Schema Part 1: Structures".
- [7] W3C REC-xmlschema-2-20010502: "XML Schema Part 2: Datatypes".
- [8] W3C REC-xml-names-19990114: "Namespaces in XML".
- [9] ITU-T Recommendation X.721: "Information technology - Open Systems Interconnection - Structure of management information: Definition of management information".

---

# 3 Definitions and abbreviations

## 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**XML file:** file containing an XML document

**XML document:** composed of the succession of an optional XML declaration followed by a root XML element

NOTE: See [4]; in the scope of the present document.

**XML declaration:** it specifies the version of XML being used

NOTE: See [4].

**XML element:** has a type, is identified by a name, may have a set of XML attribute specifications and is either composed of the succession of an XML start-tag followed by the XML content of the XML element followed by an XML end-tag, or composed simply of an XML empty-element tag; each XML element may contain other XML elements

NOTE: See [4].

**empty XML element:** having an empty XML content; an empty XML element still possibly has a set of XML attribute specifications; an empty XML element is either composed of the succession of an XML start-tag directly followed by an XML end-tag, or composed simply of an XML empty-element tag

NOTE: See [4].

**XML content (of an XML element):** empty if the XML element is simply composed of an XML empty-element tag; otherwise the part, possibly empty, of the XML element between its XML start-tag and its XML end-tag

**XML start-tag:** the beginning of a non-empty XML element is marked by an XML start-tag containing the name and the set of XML attribute specifications of the XML element

NOTE: See [4].

**XML end-tag:** the end of a non-empty XML element is marked by an XML end-tag containing the name of the XML element

NOTE: See [4].

**XML empty-element tag:** composed simply of an empty-element tag containing the name and the set of XML attribute specifications of the XML element

NOTE: See [4].

**XML attribute specification:** has a name and a value

NOTE: See [4].

**DTD:** defines structure and content constraints to be respected by an XML document to be valid with regard to this DTD

NOTE: See [4].

**XML schema:** more powerful than a DTD, an XML schema defines structure and content constraints to be respected by an XML document to conform with this XML schema; through the use of XML namespaces several XML schemas can be used together by a single XML document; an XML schema is itself also an XML document that shall conform with the XML schema for XML schemas

NOTE: See [5], [6] and [7].

**XML namespace:** enables qualifying element and attribute names used in XML documents by associating them with namespaces identified by different XML schemas

NOTE: See [8], in the scope of the present document.

**XML complex type:** defined in an XML schema; cannot be directly used in an XML document; can be the concrete type or the derivation base type for an XML element type or for another XML complex type; ultimately defines constraints for an XML element on its XML attribute specifications and/or its XML content

NOTE: See [5], [6] and [7].

**XML element type:** declared by an XML schema; can be directly used in an XML document; as the concrete type of an XML element, directly or indirectly defines constraints on its XML attribute specifications and/or its XML content; can also be the concrete type or the derivation base type for another XML element type

NOTE: See [5], [6] and [7].

## 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CM	Configuration Management
DTD	Document Type Definition
EDGE	Enhanced Data for GSM Evolution
GERAN	GSM/EDGE Radio Access Network
GSM	Global System for Mobile communication
IRP	Integration Reference Point
IS	Information Service
NRM	Network Resource Model
UMTS	Universal Mobile Telecommunications System
UTRAN	Universal Terrestrial Radio Access Network
XML	eXtensible Markup Language

---

## 4 Structure and content of configuration data XML files

The overall description of the file format of configuration data XML files is provided by 3GPP TS 32.615 [3].

Annex A of the present document defines the XML schema `stateManagementIRP.xsd` for the State Management IRP: Information Service (IS) defined in 3GPP TS 32.672 [1].

The definition of the XML element types complies with the generic mapping rules defined in 3GPP TS 32.615 [3].

## Annex A (normative): Configuration data file NRM-specific XML schema (file name "stateManagementIRP.xsd")

The following XML schema stateManagementIRP.xsd is the specific schema for the State Management IRP: Information Service (IS) defined in 3GPP TS 32.672 [1].

```
<?xml version="1.0" encoding="UTF-8"?>
<!--
 3GPP TS 32.675 State Management IRP
 Bulk CM Configuration data file XML schema
 stateManagementIRP.xsd
-->
<schema
 targetNamespace=
   "http://www.3gpp.org/ftp/specs/archive/32_series/32.675#stateManagementIRP"
 elementFormDefault="qualified"
 xmlns="http://www.w3.org/2001/XMLSchema"
 xmlns:sm=
   "http://www.3gpp.org/ftp/specs/archive/32_series/32.675#stateManagementIRP"
>
<!-- State Management IRP related XML types -->
<simpleType name="operationalStateType">
  <restriction base="string">
    <enumeration value="enabled"/>
    <enumeration value="disabled"/>
  </restriction>
</simpleType>
<simpleType name="usageStateType">
  <restriction base="string">
    <enumeration value="idle"/>
    <enumeration value="active"/>
    <enumeration value="busy"/>
  </restriction>
</simpleType>
<simpleType name="administrativeStateType">
  <restriction base="string">
    <enumeration value="locked"/>
    <enumeration value="unlocked"/>
    <enumeration value="shuttingDown"/>
  </restriction>
</simpleType>
<simpleType name="alarmStatusType">
  <restriction base="string">
    <enumeration value="cleared"/>
    <enumeration value="indeterminate"/>
    <enumeration value="warning"/>
    <enumeration value="minor"/>
    <enumeration value="major"/>
    <enumeration value="critical"/>
  </restriction>
</simpleType>
<simpleType name="proceduralStatusElementType">
  <restriction base="string">
    <enumeration value="initializationRequired"/>
    <enumeration value="notInitialized"/>
    <enumeration value="initializing"/>
    <enumeration value="reporting"/>
    <enumeration value="terminating"/>
  </restriction>
</simpleType>
<complexType name="proceduralStatusType">
  <sequence minOccurs="0" maxOccurs="5">
    <element name="proceduralStatusElement" type="sm:proceduralStatusElementType"/>
  </sequence>
</complexType>
<simpleType name="availabilityStatusElementType">
  <restriction base="string">
    <enumeration value="inTest"/>
    <enumeration value="failed"/>
    <enumeration value="powerOff"/>
    <enumeration value="offLine"/>
  </restriction>
</simpleType>
```



```
<enumeration value="offDuty"/>
<enumeration value="dependency"/>
<enumeration value="degraded"/>
<enumeration value="notInstalled"/>
<enumeration value="logFull"/>
</restriction>
</simpleType>
<complexType name="availabilityStatusType">
  <sequence minOccurs="0" maxOccurs="9">
    <element name="availabilityStatusElement" type="sm:availabilityStatusElementType"/>
  </sequence>
</complexType>
<simpleType name="controlStatusElementType">
  <restriction base="string">
    <enumeration value="subjectToTest"/>
    <enumeration value="partOfServicesLocked"/>
    <enumeration value="reservedForTest"/>
    <enumeration value="suspended"/>
  </restriction>
</simpleType>
<complexType name="controlStatusType">
  <sequence minOccurs="0" maxOccurs="4">
    <element name="controlStatusElement" type="sm:controlStatusElementType"/>
  </sequence>
</complexType>
<simpleType name="standbyStatusType">
  <restriction base="string">
    <enumeration value="hotStandby"/>
    <enumeration value="coldStandby"/>
    <enumeration value="providingService"/>
  </restriction>
</simpleType>
<simpleType name="unknownStatusType">
  <restriction base="boolean">
    <pattern value="true"/>
    <pattern value="false"/>
  </restriction>
</simpleType>
<element name="operationalState" type="sm:operationalStateType"/>
<element name="usageState" type="sm:usageStateType"/>
<element name="administrativeState" type="sm:administrativeStateType"/>
<element name="alarmStatus" type="sm:alarmStatusType"/>
<element name="proceduralStatus" type="sm:proceduralStatusType"/>
<element name="availabilityStatus" type="sm:availabilityStatusType"/>
<element name="controlStatus" type="sm:controlStatusType"/>
<element name="standbyStatus" type="sm:standbyStatusType"/>
<element name="unknownStatus" type="sm:unknownStatusType"/>
</schema>
```

Annex B (informative):  
Void

## Annex C (informative): Change history

Change history								
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Cat	Old	New
Dec 2006	SA_34	SP-060732	0003	--	Add element definitions for states	F	6.2.0	7.0.0
Mar 2007	--	--	--	--	Delete reference to the 32.674 CMIP SS. Reason: SA#35 endorsed the SA5 decision to not propagate the CMIP Solution Sets to Rel-7 (TS 32.3x4, TS 32.4x4, TS 32.6x4)	--	7.0.0	7.0.1
Jun 2007	--	--	--	--	Updated Scope on reference to 32.672 IS V6.1.X to V7.0.X which was automatically upgraded to R7 at SA#36	--	7.0.1	7.0.2
Dec 2008	SA_42	--	--	--	Upgrade to Release 8	--	7.0.2	8.0.0
Dec 2009	SA_46	SP-090719	0004	--	Discontinue from Rel-9 onwards the XML schema extraction and storage	F	8.0.0	9.0.0